

L^AT_EX Class for the *Association for Computing Machinery**

Boris Veytsman[†]

2018/01/24, v1.49

Abstract

This package provides a class for typesetting publications of the Association for Computing Machinery.

Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 3 |
| 2 | User's guide | 3 |
| 2.1 | Installation | 3 |
| 2.2 | Invocation and options | 6 |
| 2.3 | Top matter | 7 |
| 2.4 | Algorithms | 20 |
| 2.5 | Figures and tables | 20 |
| 2.6 | Theorems | 22 |
| 2.7 | Online-only and offline-only material | 22 |
| 2.8 | Note about anonymous mode | 22 |
| 2.9 | Acknowledgments | 23 |
| 2.10 | Bibliography | 23 |
| 2.11 | Colors | 26 |
| 2.12 | Other notable packages and typographic remarks | 27 |
| 2.13 | A note for wizards: <code>acmart-preload-hook.tex</code> | 27 |
| 3 | Implementation | 29 |
| 3.1 | Identification | 29 |
| 3.2 | Preload hook | 29 |
| 3.3 | Options | 29 |
| 3.4 | Setting switches | 32 |

*©2016–2017, Association for Computing Machinery

[†]borisv@lk.net, boris@varphi.com

| | | |
|------|------------------------------------|----|
| 3.5 | Loading the base class and package | 33 |
| 3.6 | Citations | 34 |
| 3.7 | Paper size and paragraphing | 40 |
| 3.8 | Fonts | 44 |
| 3.9 | Floats | 45 |
| 3.10 | Lists | 46 |
| 3.11 | Top-matter data | 48 |
| 3.12 | Concepts system | 61 |
| 3.13 | Copyright system | 62 |
| 3.14 | Typesetting top matter | 67 |
| 3.15 | Headers and Footers | 82 |
| 3.16 | Sectioning | 86 |
| 3.17 | TOC lists | 88 |
| 3.18 | Theorems | 88 |
| 3.19 | Acknowledgments | 91 |
| 3.20 | Conditional typesetting | 92 |
| 3.21 | Additional bibliography commands | 92 |
| 3.22 | End of Class | 92 |

1 Introduction

The Association for Computing Machinery¹ is the world’s largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession. It was one of the early adopters of T_EX for its typesetting.

It provided several different classes for a number of journals and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and supporting different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all the different classes and packages and provide an up-to-date L^AT_EX package.

This package uses only free T_EX packages and fonts included in T_EXLive, MikT_EX and other popular T_EX distributions. It is intended to be published in these distributions itself, which minimizes users’ efforts in the installation and support of this package.

I am grateful to Michael D. Adams, Leif Andersen, Dirk Beyer, Benjamin Byholm, Michael Ekstrand, Matthew Fluet, Paolo G. Giarrusso, Ben Greenman, Jamie Davis, LianTze Lim, Ben Liblit, Kai Mindermann, Frank Mittelbach, Serguei Mokhov, Ross Moore, John Owens, Joel Nider, Tobias Pape, Mathias Rav, Andreas Reichinger, Matteo Riondato, Craig Rodkin, Bernard Rous, David Shamma, Stephen Spencer, Daniel Thomas, Zack Weinberg, John Wickerson and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User’s guide

This class uses many commands and customizatop options, so it might appear intimidating for a casual user. Do not panic! Many of these commands and options can be safely left with their default values or the values recommended by your conference or journal editors. If you have problems or questions, do not hesitate to ask me directly or the community at <https://github.com/borisveytsman/acmart>, <https://tex.stackexchange.com> or the closest T_EX Users Group. The world-wide T_EX Users Group is at <https://tug.org/>; please consider joining us if you use T_EX regularly.

2.1 Installation

Most probably, you already have this package installed in your favorite T_EX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since this package uses a number of relatively recent packages, especially the ones related to fonts.

The latest released version of this package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement by making a pull request.

Please note that the version on Github is a development (or experimental) version: please download it for testing new features. The production version is the one on CTAN and ACM sites.

¹<http://www.acm.org/>

Most users should not attempt to install this package themselves but should rather rely on their \TeX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex acmart.ins`. This will produce the file `acmart.cls`
2. Put the files `acmart.cls` and `ACM-Reference-Format.bst` in places where \LaTeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package. (This is probably the file you are reading now.)

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

This class uses a number of other packages. They are included in all major \TeX distributions (\TeX Live, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscls*, <http://www.ctan.org/pkg/amscls>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *etoolbox*, <http://www.ctan.org/pkg/etoolbox>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>
- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>

- *ifluatex*, <http://www.ctan.org/pkg/ifluatex>
- *ifxetex*, <http://www.ctan.org/pkg/ifxetex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>
- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *refcount*, <http://www.ctan.org/pkg/refcount>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

2.2 Invocation and options

To use this class, put in the preamble of your document

```
\documentclass[<options>]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example,

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option `format` describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words `format=` can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals and transactions, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case, you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

There are several Boolean options that can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting a Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option. It provides a version suitable for reviewers and copy editors.

The default for the option `screen` depends on the publication. At present it is `false` for all publications *but* PACM, since PACM is now electronic-only. Thus PACM titles (see Table 3) set this option to `true`. In the future this option may involve additional features suitable for on-screen versions of articles.

The option `natbib` is used when the corresponding BibTeX style is based on `natbib`. In most cases you do not need to set it. See Section 2.10.

The option `anonymous` is used for anonymous review processes and causes all author information to be obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The footer also includes the page range of the document. This helps detect missing pages in hard copies.

Table 1: The possible values for the format option

| Value | Meaning |
|-------------------------|--|
| <code>manuscript</code> | A manuscript. This is the default. |
| <code>acmsmall</code> | Small single-column format. Used for CIE, CSUR, DTRAP, JACM, JDIQ, JEA, JERIC, JETC, PACMHCI, PACMPL, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TEAC, TECS, THRI, TIIS, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TRET, TSAS, TSC, TSLP and TWEB, including special issues. |
| <code>acmlarge</code> | Large single-column format. Used for IMWUT, JOCCH, POMACS and TAP, including special issues. |
| <code>acmtog</code> | Large double-column format. Used for TOG, including annual conference Technical Papers. |
| <code>sigconf</code> | Proceedings format for most ACM conferences (with the exceptions listed below) and all ICPS volumes. |
| <code>sigplan</code> | Proceedings format for SIGPLAN conferences. |
| <code>sigchi</code> | Proceedings format for SIGCHI conferences. |
| <code>sigchi-a</code> | Format for SIGCHI extended abstracts. |

The option `author draft` is intended for author’s drafts that are not intended for distribution. It typesets a copyright block to give the author an idea of its size and the overall size of the paper but overprints it with the phrase “Unpublished working draft. Not for distribution.”, which is also used as a watermark. This option sets `timestamp` and `review` to true, but these can be overridden by setting these options to false *after* setting `author draft` to true.

2.3 Top matter

A number of commands set up *top matter* or (in computer science jargon) *metadata* for an article. They establish the publication name, article title, authors, DOI and other data. Some of these commands, like `\title` and `\author`, should be put by the authors. Others, like `\acmVolume` and `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

This class internally loads the `amsart` class, so many top-matter commands are inherited from `amsart` [2].

`\acmJournal` The macro `\acmJournal{<shortName>}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication *in uppercase*, for example,

```
\acmJournal{TOMS}
```

Table 2: Boolean options

| Option | Default | Meaning |
|---------------|----------|--|
| review | false | A review version: lines are numbered and hyperlinks are colored |
| screen | see text | A screen version: hyperlinks are colored |
| natbib | true | Whether to use the natbib package (see Section 2.10) |
| anonymous | false | Whether to make author(s) anonymous |
| authorversion | false | Whether to generate a special version for the authors' personal use or posting (see Section 2.3) |
| timestamp | false | Whether to put a time stamp in the footer of each page |
| authordraft | false | Whether author's-draft mode is enabled |
| acmthm | true | Whether to define theorem-like environments, see Section 2.6 |

The currently recognized journals are listed in Table 3. Note that conference proceedings published in *book* form do not set this macro.

It is expected that this command is inserted by the author of the manuscript when she decides to which journal to submit the manuscript.

`\acmConference` The macro `\acmConference[<short name>]{<name>}{<date>}{<venue>}` is used for conference proceedings published in the book form. The arguments are the following:

short name: the abbreviated name of the conference (optional).

name: the name of the conference.

date: the date(s) of the conference.

venue: the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November
12--16}{Dallas, TX, USA}
\acmConference{SA'15 Art Papers}{November 02--06, 2015}{Kobe, Japan}
```

`\acmBooktitle` By default we assume that conference proceedings are published in the book named *Proceedings of CONFERENCE*, where CONFERENCE is the name of the conference inferred from the command `\acmConference` above. However, sometimes the book title is different. The command `\acmBooktitle` can be used to set this title, for example,

```
\acmBooktitle{Companion to the first International Conference on the
Art, Science and Engineering of Programming (Programming '17)}
```


Table 3: ACM publications and arguments of the \acmJournal command

| Abbreviation | Publication |
|--------------|--|
| CIE | ACM Computers in Entertainment |
| CSUR | ACM Computing Surveys |
| DTRAP | Digital Threats: Research and Practice |
| IMWUT | PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies |
| JACM | Journal of the ACM |
| JDIQ | ACM Journal of Data and Information Quality |
| JEA | ACM Journal of Experimental Algorithmics |
| JERIC | ACM Journal of Educational Resources in Computing |
| JETC | ACM Journal on Emerging Technologies in Computing Systems |
| JOCCH | ACM Journal on Computing and Cultural Heritage |
| PACMHCI | PACM on Human-Computer Interaction |
| PACMPL | PACM on Programming Languages |
| POMACS | PACM on Measurement and Analysis of Computing Systems |
| TAAS | ACM Transactions on Autonomous and Adaptive Systems |
| TACCESS | ACM Transactions on Accessible Computing |
| TACO | ACM Transactions on Architecture and Code Optimization |
| TALG | ACM Transactions on Algorithms |
| TALLIP | ACM Transactions on Asian and Low-Resource Language Information Processing |
| TAP | ACM Transactions on Applied Perception |
| TCPS | ACM Transactions on Cyber-Physical Systems |
| TEAC | ACM Transactions on Economics and Computation |
| TECS | ACM Transactions on Embedded Computing Systems |
| THRI | ACM Transactions on Human-Robot Interaction |
| TIIS | ACM Transactions on Interactive Intelligent Systems |
| TISSEC | ACM Transactions on Information and System Security |
| TIST | ACM Transactions on Intelligent Systems and Technology |
| TKDD | ACM Transactions on Knowledge Discovery from Data |
| TMIS | ACM Transactions on Management Information Systems |
| TOCE | ACM Transactions on Computing Education |
| TOCHI | ACM Transactions on Computer-Human Interaction |
| TOCL | ACM Transactions on Computational Logic |
| TOCS | ACM Transactions on Computer Systems |
| TOCT | ACM Transactions on Computation Theory |
| TODAES | ACM Transactions on Design Automation of Electronic Systems |
| TODS | ACM Transactions on Database Systems |
| TOG | ACM Transactions on Graphics |
| TOIS | ACM Transactions on Information Systems |
| TOIT | ACM Transactions on Internet Technology |
| TOMACS | ACM Transactions on Modeling and Computer Simulation |
| TOMM | ACM Transactions on Multimedia Computing, Communications and Applications |
| TOMPECS | ACM Transactions on Modeling and Performance Evaluation of Computing Systems |
| TOMS | ACM Transactions on Mathematical Software |
| TOPC | ACM Transactions on Parallel Computing |
| TOPLAS | ACM Transactions on Programming Languages and Systems |
| TOPS | ACM Transactions on Privacy and Security |
| TOS | ACM Transactions on Storage |
| TOSEM | ACM Transactions on Software Engineering and Methodology |
| TOSN | ACM Transactions on Sensor Networks |
| TRETS | ACM Transactions on Reconfigurable Technology and Systems |
| TSAS | ACM Transactions on Spatial Algorithms and Systems |
| TSC | ACM Transactions on Social Computing |
| TSLP | ACM Transactions on Speech and Language Processing |
| TWEB | ACM Transactions on the Web |

`\editor` In most cases, conference proceedings are edited. You can use the command `\editor{<editor>}` to set the editor of the volume. This command can be repeated, for example,

```
\editor{Jennifer B. Sartor}
\editor{Theo D'Hondt}
\editor{Wolfgang De Meuter}
```

`\title` The command `\title`, as in the `amsart` class, has two arguments: one optional, and one mandatory:

```
\title[<ShortTitle>]{<FullTitle>}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

`\subtitle` Besides title, ACM classes allow a subtitle, set with the `\subtitle{<subtitle>}` macro.

The commands for specifying authors are highly structured. The reason is they serve double duty: the authors' information is typeset in the manuscript *and* is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

`\author` The basic commands are `\author`, `\orcid` (for the researchers registered with ORCID, <http://www.orcid.org/>), `\affiliation` and `\email`. In the simplest case, you enter them in this order:

```
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
```

Do *not* use the \LaTeX `\and` macro! Each author deserves his or her own `\author` command.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: the metadata tools will get them.

Sometimes an author has several affiliations. In this case, the `\affiliation` command should be repeated:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat the `\email` command.

You may have several authors with the same affiliation, different affiliations, or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is

affiliated with I_2 only, author A_3 is affiliated with I_1 and I_3 , etc.). The recommended solution is to put the `\affiliation` commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

In some cases, when several authors share the same affiliation, you can try to save space using the format

```
\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}
```

However, this format is not generally recommended.

`\additionalaffiliation`

In some cases, too many affiliations can take too much space. The command `\additionalaffiliation{<affiliation>}` creates a footnote after an author’s name with the words “Also with {<affiliation>}”. You should use this command only as a last resort. An example of usage is:

```
\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
  \institution{The Th{\o}rv{\a}ld Group}
  \streetaddress{1 Th{\o}rv{\a}ld Circle}
  \city{Hekla}
  \country{Iceland}}
\affiliation{%
  \institution{Institute for Clarity in Documentation}
  \streetaddress{P.O. Box 1212}
  \city{Dublin}
  \state{Ohio}
  \postcode{43017-6221}}
```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørväld Group.

`\position` The `\affiliation` and `\additionalaffiliation` commands are further structured
`\institution` to interact with the metadata extraction tools. Inside these commands you should use the
`\department` `\position`, `\institution`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode`
`\streetaddress` and `\country` macros to indicate the corresponding parts of the affiliation. Note that in
`\city` some cases (for example, journals) these parts are not printed in the resulting copy, but
`\state` they *are* necessary since they are used by the XML metadata extraction programs. Do
`\postcode` *not* put commas or `\\` between the elements of `\affiliation`. They will be provided
`\country` automatically.

An example of the author block:

```

\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
  \institution{University of New South Wales}
  \department{School of Biomedical Engineering}
  \streetaddress{Samuels Building (F25), Kensington Campus}
  \city{Sidney}
  \state{NSW}
  \postcode{2052}
  \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
  \institution{University of Pennsylvania}
  \city{Philadelphia}
  \state{PA}
  \country{USA}}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}

```

Note that the old ACM conference formats did not allow more than six authors and required some effort from authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same insitution. There could be two situations: the departments are independent, or one department is within another. In the first case, just repeat the command `\department` several times. To handle

the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```
\affiliation{%
  \department[0]{Department of Lunar Studies} % 0 is the default
  \department[1]{John Doe Institute} % higher than 0
  \institution{University of San Serriffe}
  \country{San Serriffe}}
```

and

```
\affiliation{%
  \department{Department of Lunar Studies} % Not in the John Doe Institute!
  \department{John Doe Institute}
  \institution{University of San Serriffe}
  \country{San Serriffe}}
```

The command `\affiliation` formats its output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany, the postcode is put before the city and is not separated by a comma. We can handle this order using

```
\affiliation{%
  \institution{Fluginstitut}
  \streetaddress{Sonnenallee 17}
  \postcode{123456}
  \city{Helm}
  \country{Germany}}
```

However, the comma after the postcode is unfortunate: the address will be typeset (in some formats) as

```
Fluginstitut
Sonnenallee 17
123456, Helm, Germany
```

To overcome this problem, the command `\affiliation` has an optional parameter `obeypunctuation`, which can be `false` (the default) or `true`. If this parameter is `true`, `\affiliation` obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut}\\
  \streetaddress{Sonnenallee 17}\\
  \postcode{123456}
  \city{Helm},
  \country{Germany}}
```

will be typeset as

```
Fluginstitut  
Sonentallee 17  
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

`\thanks` Like `amsart` (and unlike standard \LaTeX), we allow `\thanks` only *outside* of the commands `\title` and `\author`. This command is obsolete and should *not* be used in most cases. Do not list your acknowledgments or grant sponsors here. Put this information in the `acks` environment (see Section 2.9).

`\authorsaddresses` In some formats, addresses are printed as a footnote on the first page. By default \LaTeX typesets them itself using the information you give it. However, you can override its choice using the command `\authorsaddresses{<contact addresses>}`, for example,

```
\authorsaddresses{%  
  Authors' addresses: G.~Zhou, Computer Science Department, College of  
  William and Mary, 104 Jameson Rd, Williamsburg, PA 23185, US;  
  V.~B'eranger, Inria Paris-Rocquencourt, Rocquencourt, France;  
  A.~Patel, Rajiv Gandhi University, Rono-Hills, Doimukh, Arunachal  
  Pradesh, India; H.~Chan, Tsinghua University, 30 Shuangqing Rd,  
  Haidian Qu, Beijing Shi, China; T.~Yan, Eaton Innovation Center,  
  Prague, Czech Republic; T.~He, C.~Huang, J.~A.~Stankovic University  
  of Virginia, School of Engineering Charlottesville, VA 22903, USA;  
  T. F. Abdelzaher, (Current address) NASA Ames Research Center,  
  Moffett Field, California 94035.}
```

You can *suppress* printing authors' addresses by setting them to an empty string:

```
\authorsaddresses{}
```

`\titlenote` While the command `\thanks` generates a note without a footnote mark, sometimes
`\subtitlenote` the authors might need notes more tightly connected to the title, subtitle or author. The
`\authornote` commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the corresponding
commands (`\title`, `\subtitle` and `\author`) generate such notes. For example,

```
\title{This is a title}  
\titlenote{This is a titlenote}  
\author{A. U. Thor}  
\authornote{This is an authornote}
```

Please never use a `\footnote` inside an `\author` or `\title` command since this confuses the metadata extraction software. (Actually these commands now produce errors.)

`\authornotemark` Sometimes one may need to have the same footnote connected to several authors. The command `\authornotemark[<number>]` adds just the footnote mark, for example,

```
\author{A. U. Thor}  
\authornote{Both authors contributed equally to the paper}
```

```
...
\author{A. N. Other}
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

`\acmVolume` The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are
`\acmNumber` inserted by the editor and set the journal volume, issue, article number, year and month
`\acmArticle` correspondingly. The arguments of all these commands, including `\acmMonth`, is numer-
`\acmYear` ical. For example,
`\acmMonth`

```
\acmVolume{9}
\acmNumber{4}
\acmArticle{39}
\acmYear{2010}
\acmMonth{3}
```

Note that `\acmArticle` is used not only for journals but also for some conference proceedings.

`\acmArticleSeq` The articles in the same issue of a journal have a *sequence number*. It is used to
vertically position the black blob on the first page of some formats. By default it is the
same as the article number, but the command `\acmArticleSeq{<n>}` can be used to
change it:

```
\acmArticle{39}    % The sequence number will be 39 by default
\acmArticleSeq{5} % We redefine it to 5
```

Setting this number to zero suppresses the blob.

`\acmSubmissionID` If your paper got a Submission ID from the Conference Management System, put it
here:

```
\acmSubmissionID{123-A56-BU3}
```

`\acmPrice` The macro `\acmPrice{<price>}` sets the price for the article, for example,

```
\acmPrice{25.00}
```

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to `usgov` or `rightsretained`, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN` Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}`
sets it. Normally it is set by the typesetter, for example,

```
\acmISBN{978-1-4503-3916-2}
```

| | |
|--|---|
| | Setting it to the empty string, as <code>\acmISBN{}</code> , suppresses printing the ISBN. |
| <code>\acmDOI</code> | <p>The macro <code>\acmDOI{<DOI>}</code> sets the DOI of the article, for example,</p> <pre>\acmDOI{10.1145/9999997.9999999}</pre> |
| | It is normally set by the typesetter. Setting it to the empty string, as <code>\acmDOI{}</code> , suppresses the DOI. |
| <code>\acmBadgeR</code> <code>\acmBadgeL</code> | <p>Some conference articles get special distinctions, for example, the artifact evaluation for PPOPP 2016 (see http://ctuning.org/ae/ppopp2016.html). These articles display special badges supplied by the conference organizers. This class provides commands to add these badges: <code>\acmBadgeR[<url>]{<graphics>}</code> and <code>\acmBadgeL[<url>]{<graphics>}</code>. The first command puts the badge to the right of the title, and the second one—to the left. The exception is the <code>sigchi-a</code> mode for SIGCHI extended abstracts, which puts the badges on the left margin. The arguments have the following meaning: <code>[<url>]</code>, if provided, sets the link to the badge authority in the screen version, while <code>{<graphics>}</code> sets the graphics file with the badge image. The file must be a cropped square, which is scaled to a standard size in the output. For example, if the badge image is <code>ae-logo.pdf</code>, the command is</p> <pre>\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}</pre> |
| <code>\startPage</code> | <p>The macro <code>\startPage{<page>}</code> sets the first page of the article in a journal or book. It is used by the typesetter.</p> |
| <code>\terms</code> <code>\keywords</code> | <p>The command <code>\keywords{<keyword, keyword,...>}</code> sets keywords for the article. They must be separated by commas, for example,</p> <pre>\keywords{wireless sensor networks, media access control, multi-channel, radio interference, time synchronization}</pre> |
| <code>CCSXML</code> <code>\ccsdesc</code> | <p>ACM publications are classified according to the ACM Computing Classification Scheme (CCS). CCS codes are used both in the typeset version of the publications <i>and</i> in the metadata in various databases. Therefore you need to provide both \TeX commands and XML metadata with the paper.</p> <p>The tool at http://dl.acm.org/ccs.cfm can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get results like the following:</p> <pre>\begin{CCSXML} <ccs2012> <concept> <concept_id>10010520.10010553.10010562</concept_id> <concept_desc>Computer systems organization~Embedded systems</concept_desc> <concept_significance>500</concept_significance> </concept> <concept> <concept_id>10010520.10010575.10010755</concept_id> <concept_desc>Computer systems organization~Redundancy</concept_desc> <concept_significance>300</concept_significance></pre> |


```

</concept>
<concept>
  <concept_id>10010520.10010553.10010554</concept_id>
  <concept_desc>Computer systems organization~Robotics</concept_desc>
  <concept_significance>100</concept_significance>
</concept>
<concept>
  <concept_id>10003033.10003083.10003095</concept_id>
  <concept_desc>Networks~Network reliability</concept_desc>
  <concept_significance>100</concept_significance>
</concept>
</ccs2012>
\end{CCSXML}

\ccsdesc[500]{Computer systems organization~Embedded systems}
\ccsdesc[300]{Computer systems organization~Redundancy}
\ccsdesc{Computer systems organization~Robotics}
\ccsdesc[100]{Networks~Network reliability}

```

You just need to copy this code and paste it in your paper anywhere before `\maketitle`.

`\setcopyright` There are several possibilities for the copyright of the papers published by the ACM: the authors may transfer the rights to the ACM, license them to the ACM, some or all authors might be employees of the US or Canadian governments, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 4.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear` Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this using the macro `\copyrightyear`, e.g.,

```

\acmYear{2016}
\copyrightyear{2015}

```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces a special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell \TeX about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version, the page breaks might be different between them.

`abstract` The environment `abstract` must *precede* the `\maketitle` command. Again, this is different from the standard \LaTeX .

`teaserfigure` A special kind of figure is used for many two-column conference proceedings.

Table 4: Parameters for the `\setcopyright` command

| Parameter | Meaning |
|---------------------------------|--|
| <code>none</code> | The copyright and permission information is not typeset. (This is the option for some ACM conferences.) |
| <code>acmcopyright</code> | The authors transfer the copyright to the ACM (the “traditional” choice). |
| <code>acmlicensed</code> | The authors retain the copyright but license the publication rights to the ACM. |
| <code>rightsretained</code> | The authors retain the copyright and publication rights to themselves or somebody else. |
| <code>usgov</code> | All the authors are employees of the US government. |
| <code>usgovmixed</code> | Some authors are employees of the US government. |
| <code>cagov</code> | All the authors are employees of the Canadian government. |
| <code>cagovmixed</code> | Some authors are employees of the Canadian government. |
| <code>licensedusgovmixed</code> | Some authors are employees of the US government, and the publication rights are licensed to the ACM. |
| <code>licensedcagov</code> | All the authors are employees of the Canadian government, and the publication rights are licensed to the ACM. |
| <code>licensedcagovmixed</code> | Some authors are employees of the Canadian government, and the publication rights are licensed to the ACM. |
| <code>othergov</code> | Authors are employees of a government other than the US or Canada. |
| <code>licensedothergov</code> | Authors are employees of a government other than the US or Canada, and the publication rights are licensed to the ACM. |
| <code>iw3c2w3</code> | Special statement for conferences organized by IW3C2. |
| <code>iw3c2w3g</code> | Special statement for conferences organized by IW3C2, when some authors are approved Google employees. |

Table 5: Settings for the `\settopmatter` command

| Parameter | Values | Meaning |
|----------------------------|------------|--|
| <code>printccs</code> | true/false | Whether to print CCS categories |
| <code>printacmref</code> | true/false | Whether to print the ACM bibliographic entry |
| <code>printfolios</code> | true/false | Whether to print page numbers (folios) |
| <code>authorsperrow</code> | numeric | Number of authors per row for the title page in conference proceedings formats |

This figure is placed just after the authors but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{This is a teaser}
  \label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You can override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 5. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf`, etc.). The number of boxes per row is determined automatically. If you want to override this, you can do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

However, in most cases you should *not* do this and should use the default settings. Setting `authorsperrow` to 0 will revert it to the default settings.

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The `[<stage>]` argument is optional; the default is Received for the first date and revised for the subsequent ones. For example,

```
\received{February 2007}
\received[revised]{March 2009}
\received[accepted]{June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top-matter group. That is

it must follow the commands defined in this section.

`\shortauthors` *After* the command `\maketitle`, the macro `\shortauthors` stores the names of the authors for the running head. You can redefine it if the list of author’s name is too long, e.g.,

```
\maketitle
\renewcommand{\shortauthors}{Zhou et al.}
```

2.4 Algorithms

There are now several good packages for typesetting algorithms [3, 4, 5], and the authors are free to choose their favorite one.

2.5 Figures and tables

The new ACM styles use the standard \TeX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies and for tables *before* the table bodies.
2. The ACM uses the standard types for figures and tables and adds several new ones. In total there are the following types:

figure, table: a standard figure or table taking a full text width in one-column formats and one column width in two-column formats.

figure*, table* in two-column formats, a special figure or table taking a full text width.

teaserfigure: a special figure before `\maketitle`.

sidebar, marginfigure, margintable: in the sigchi-a format, special sidebars, tables and figures in the margin.

3. Accordingly, when scaling images, one should use the following sizes:
 - (a) For `teaserfigure`, `figure` in one-column mode or `figure*` in two-column mode, use `\textwidth`. In one-column mode, you can also use `\columnwidth`, which coincides with `\textwidth` in this case.
 - (b) For `figure` in two-column mode, use `\columnwidth`.
 - (c) For `marginfigure`, use `\marginparwidth`.
 - (d) For `figure*` in SIGCHI extended abstracts, use `\fulltextwidth`.

It is strongly recommended to use the package `booktabs` [6] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.
2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in the TeX FAQ [1]. The simplest one is to use a `\minipage` environment:

```

\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a
table footnote. This is a table footnote.} &
(200\,m$\times$200\,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
sourcenote. This is a table sourcenote. This is a table
sourcenote.

\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}

```

sidebar
marginfigure
margintable

SIGCHI extended abstracts use margin space extensively. This package provides three environments for this with optional captions:

sidebar: textual information in the margin

marginfigure: a figure in the margin

margintable: a table in the margin

Tables and figures (including margin tables and margin figures) are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.6 Theorems

The ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma and corollary, and

acmdefinition: this is the style used for example and definition.

These environments are defined by default. In the unusual circumstance that a user does not wish to have these environments defined, the option `acmthm=false` in the preamble will suppress them.

2.7 Online-only and offline-only material

`printonly` Some supplementary material in ACM publications is put online but not in the printed
`screenonly` version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to `true`. Conversely, the text inside the environment `printonly` is typeset only when this option is set to `false`. For example,

```
\section{Supplementary materials}

\begin{printonly}
  Supplementary materials are available in the online version of this paper.
\end{printonly}

\begin{screenonly}
  (The actual supplementary materials.)
\end{screenonly}
```

We use the `comment` package for typesetting this code, so `\begin` and `\end` should start on a line of their own with no leading or trailing spaces.

2.8 Note about anonymous mode

`anonsuppress` When the option `anonymous` is selected, \TeX suppresses author information (including the number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper. For example,

```
\begin{anonsuppress}
  This is the continuation of the previous work by the author
  \cite{prev1, prev2}.
\end{anonsuppress}
```

As for the `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start on a line of their own with no leading or trailing spaces.

2.9 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in anonymous mode this section must be omitted: it gives too much information to reviewers. Second, data about grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

`acks` The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for the `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start on a line of their own with no leading or trailing spaces.

`\grantsponsor` All financial support *must* be listed using the commands `\grantsponsor` and
`\grantnum` `\grantnum`. These commands tell the postprocessing software about the granting organization and grant. The format of these commands is the following:

```
\grantsponsor{<sponsorID>}{<name>}{<url>}
\grantnum[<url>]{<sponsorID>}{<number>}
```

Here `{<sponsorID>}` is the unique ID used to match grants to sponsors, `{<name>}` is the name of the sponsor, `{<url>}` is its URL, and `{<number>}` is the grant number. The `{<sponsorID>}` of the `\grantnum` command must correspond to the `{<sponsorID>}` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of the `\grantnum` command.

At present `{<sponsorID>}` is chosen by the authors and can be an arbitrary key in the same way the label of a `\cite` is arbitrarily chosen. There might be a change to this policy if the ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
  The authors would like to thank Dr. Yuhua Li for providing the
  matlab code of the \textit{BEPS} method.

  The authors would also like to thank the anonymous referees for
  their valuable comments and helpful suggestions. This work is
  supported by the \grantsponsor{GS501100001809}{National Natural
  Science Foundation of
  China}{https://doi.org/10.13039/501100001809} under Grant
  No.:~\grantnum{GS501100001809}{61273304}
  and~\grantnum[http://www.nsf.cn/youngscientists]{GS501100001809}{Young
  Scientists' Support Program}.
\end{acks}
```

2.10 Bibliography

The ACM uses the `natbib` package for formatting references and the `BibTeX` style file `ACM-Reference-Format.bst` for `BibTeX` processing. You can disable loading of `natbib` using the option `natbib=false` in `\documentclass`. However, it is not recommended,

as well as the use of Bib_T_EX styles other than ACM-Reference-Format.bst, and may delay the processing of the manuscript.

`\citestyle` If you use natbib, you can select one of two predefined citation styles using the command `\citestyle`: the author-year format `acmauthoryear` or the numeric format `acmnumeric`. For example,

```
\citestyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

`\setcitestyle` You can further customize natbib using the `\setcitestyle` command, for example,

```
\setcitestyle{numbers,sort&compress}
```

One of the more common versions is

```
\setcitestyle{nosort}
```

It is useful if you do not like the way natbib sorts citation lists.

If you use natbib, then commands like `\citep` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode and cites the year in author-date mode.

Note that before version 1.48 the command `\citeyear` put the year in parentheses. In version 1.48 and later it produces just the year; the command `\citeyearpar` can be used to emulate its old behavior.

There are several customized Bib_T_EX entry types and fields in the ACM style file ACM-Reference-Format.bst that you may want to be aware of.

The style supports the fields `doi` and `url`, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

The style supports the arXiv-recommended fields `eprint` and (optionally) `primaryclass`, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <http://arxiv.org/hypertex/bibstyles/>.

There are the special entry types `online` and `game` for Web pages and games, for example,

```
@online{Thornburg01,
author = "Harry Thornburg",
year = "2001",
title = "Introduction to Bayesian Statistics",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
```



```

month =      mar,
lastaccessed = "March 2, 2005",
}

```

For these entry types you can use the `lastaccessed` field to add the access date for the URL.

There are two ways to enter video or audio sources in the bibliography corresponding to two different possibilities. For standalone sources available online, you can use an online entry and set its `howpublished` field. For example,

```

@online{Obama08,
author =      "Barack Obama",
year  =      "2008",
title  =      "A more perfect union",
howpublished = "Video",
day    =      "5",
url    =      "http://video.google.com/videoplay?docid=6528042696351994555",
month  =      mar,
lastaccessed = "March 21, 2008",
}

```

For sources available as attachments to conference proceedings and similar documents, you can use the usual `inproceedings` entry type and set its `howpublished` field:

```

@Inproceedings{Novak03,
author =      "Dave Novak",
title  =      "Solder man",
booktitle =   "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
year  =      "2003",
publisher =   "ACM Press",
address =     "New York, NY",
pages  =      "4",
month  =      "March 21, 2008",
doi    =      "10.9999/woot07-S422",
howpublished = "Video",
}

```

Sometimes you need to cite a complete issue of a journal. The periodical entry type is intended for this:

```

@periodical{JCohen96,
key =      "Cohen",
editor =   "Jacques Cohen",
title  =   "Special issue: Digital Libraries",
journal = "Communications of the {ACM}",
volume =  "39",
number  =  "11",
month  =  nov,
}

```

```
    year =      "1996",
  }
```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) to the entry.

If you do not know the author (this is often the case for online entries), use the key field to add a key for sorting and citations, for example,

```
@online{TUGInstmem,
  key =      {TUG},
  year =      2017,
  title =      "Institutional members of the {\TeX} Users Group",
  url =      "http://wwwtug.org/instmem.html",
  lastaccessed = "May 27, 2017",
}
```

2.11 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [7]: ACMBLue, ACMYellow, ACMOrange, ACMRed, ACMLightBlue, ACMGreen, ACMPurple and ACMDarkBlue. You can use them in color assignments.

The ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that differ only in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in black and white.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation) as there is bound to be someone affected!

To ensure that you are using the most accessible colors, the ACM recommends that you choose sets of colors to help ensure suitable variations in when printed in greyscale by using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.12 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package `subcaption` [8] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages `nomencl` [9] and `glossaries` [10] can be used for the automatic creation of the lists of symbols and concepts used.

By default `acmart` prevents all widows and orphans (i.e., lonely lines at the beginning or end of the page) and hyphenation at the end of the page. This is done by the rather strict settings

```
\widowpenalty=10000
\clubpenalty=10000
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware, the results might be, well, sloppy.

Note that the upercasing in section titles is done using the `textcase` package [11], so the command `\NoCaseChange` inside the title may help to prevent extraneous upercasing.

2.13 A note for wizards: `acmart-preload-hook.tex`

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded and certain decisions are made. This presents a number of problems.

For example, one may want to use the `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to a package. Suppose you want to use the `dvipsnames` option of the `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` can be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][]{\LoadClassOrig[#1]{#2}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

Important note. This hook makes it too easy to create a manuscript that is not acceptable by the ACM. It is even easier to create a file that cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decide to use this hook, you are on your own.

3 Implementation

3.1 Identification

We start with a declaration of who we are. Most .dtx files put driver code in a separate .drv driver file. We roll this code into the main file and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2018/01/24 v1.49 Typesetting articles for the Association for
7 Computing Machinery]
   And the driver code:
8 <*gobble>
9 \documentclass{ltxdoc}
10 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx}
11 \usepackage[tt=false, type1=true]{libertine}
12 \usepackage[varqu]{zi4}
13 \usepackage[libertine]{newtxmath}
14 \usepackage[tableposition=top]{caption}
15 \usepackage{hypdoc}
16 \PageIndex
17 \CodelineIndex
18 \RecordChanges
19 \EnableCrossrefs
20 \begin{document}
21   \DocInput{acmart.dtx}
22 \end{document}
23 </gobble>
24 <*class>
25 \def\@classname{acmart}
```

3.2 Preload hook

We preload acmart-preload-hook:

```
26 \InputIfFileExists{acmart-preload-hook.tex}{%
27   \ClassWarning{\@classname}{%
28     I am loading acmart-preload-hook.tex. You are fully responsible
29     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
30 \RequirePackage{xkeyval}
```

We use xstring to check whether user input is integer

```
31 \RequirePackage{xstring}
```

format The possible formats

```
32 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
33 manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
34 sigplan, sigchi, sigchi-a}[manuscript]{}{%
35 \ClassError{\@classname}{The option format must be manuscript,
36 acmsmall, acmlarge, acmtog, sigconf, siggraph,
37 sigplan, sigchi or sigchi-a}}
38 \def\@DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
39 \@DeclareACMFormat{manuscript}
40 \@DeclareACMFormat{acmsmall}
41 \@DeclareACMFormat{acmlarge}
42 \@DeclareACMFormat{acmtog}
43 \@DeclareACMFormat{sigconf}
44 \@DeclareACMFormat{siggraph}
45 \@DeclareACMFormat{sigplan}
46 \@DeclareACMFormat{sigchi}
47 \@DeclareACMFormat{sigchi-a}
48 \ExecuteOptionsX{format}
```

\if@ACM@screen Whether we use screen mode

```
49 \define@boolkey+{acmart.cls}[\ACM@]{screen}[true]{%
50 \if@ACM@screen
51 \PackageInfo{\@classname}{Using screen mode}%
52 \else
53 \PackageInfo{\@classname}{Not using screen mode}%
54 \fi}{\PackageError{\@classname}{The option screen can be either true or
55 false}}
56 \ExecuteOptionsX{screen=false}
```

\if@ACM@acmthm Whether we define theorem-like environments.

```
57 \define@boolkey+{acmart.cls}[\ACM@]{acmthm}[true]{%
58 \if@ACM@acmthm
59 \PackageInfo{\@classname}{Requiring acmthm}%
60 \else
61 \PackageInfo{\@classname}{Suppressing acmthm}%
62 \fi}{\PackageError{\@classname}{The option acmthm can be either true or
63 false}}
64 \ExecuteOptionsX{acmthm=true}
```

\if@ACM@review Whether we use review mode

```
65 \define@boolkey+{acmart.cls}[\ACM@]{review}[true]{%
66 \if@ACM@review
67 \PackageInfo{\@classname}{Using review mode}%
68 \AtBeginDocument{\ACM@printfoliostrue}%
69 \else
70 \PackageInfo{\@classname}{Not using review mode}%
71 \fi}{\PackageError{\@classname}{The option review can be either true or
72 false}}
73 \ExecuteOptionsX{review=false}
```

`\if@ACM@authorversion` Whether we use author's-version mode

```

74 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
75   \if@ACM@authorversion
76     \PackageInfo{\@classname}{Using authorversion mode}%
77   \else
78     \PackageInfo{\@classname}{Not using authorversion mode}%
79   \fi}{\PackageError{\@classname}{The option authorversion can be either true or
80     false}}
81 \ExecuteOptionsX{authorversion=false}

```

`\if@ACM@natbib@override` This macro is no longer used.

`\if@ACM@natbib` Whether we use natbib mode

```

82 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
83   \if@ACM@natbib
84     \PackageInfo{\@classname}{Explicitly selecting natbib mode}%
85   \else
86     \PackageInfo{\@classname}{Explicitly deselecting natbib mode}%
87   \fi}{\PackageError{\@classname}{The option natbib can be either true or
88     false}}
89 \ExecuteOptionsX{natbib=true}

```

`\if@ACM@anonymous` Whether we use anonymous mode

```

90 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
91   \if@ACM@anonymous
92     \PackageInfo{\@classname}{Using anonymous mode}%
93   \else
94     \PackageInfo{\@classname}{Not using anonymous mode}%
95   \fi}{\PackageError{\@classname}{The option anonymous can be either true or
96     false}}
97 \ExecuteOptionsX{anonymous=false}

```

`\if@ACM@timestamp` Whether we use timestamp mode

```

98 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
99   \if@ACM@timestamp
100     \PackageInfo{\@classname}{Using timestamp mode}%
101   \else
102     \PackageInfo{\@classname}{Not using timestamp mode}%
103   \fi}{\PackageError{\@classname}{The option timestamp can be either true or
104     false}}
105 \ExecuteOptionsX{timestamp=false}

```

`\if@ACM@authordraft` Whether we use author-draft mode

```

106 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
107   \if@ACM@authordraft
108     \PackageInfo{\@classname}{Using authordraft mode}%
109     \@ACM@timestamptrue
110     \@ACM@reviewtrue
111   \else

```

```

112 \PackageInfo{\@classname}{Not using authordraft mode}%
113 \fi}{\PackageError{\@classname}{The option authordraft can be either true or
114 false}}
115 \ExecuteOptionsX{authordraft=false}

```

`\ACM@fontsize` The font size to pass to the base class

```

116 \def\ACM@fontsize{
117 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
118 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
119 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
120 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

121 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
122 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
123 \ProcessOptionsX
124 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

`\if@ACM@manuscript` Whether we use manuscript mode

```
125 \newif\if@ACM@manuscript
```

`\if@ACM@journal` There are two kinds of publications: journals and books

```
126 \newif\if@ACM@journal
```

`\if@ACM@sigchiamode` The formatting of SIGCHI extended abstracts is quite unusual. We have a special switch for them.

```
127 \newif\if@ACM@sigchiamode
```

Setting up switches

```

128 \ifnum\ACM@format@nr=5\relax % siggraph
129 \ClassWarning{\@classname}{The format siggraph is now obsolete.
130 I am switching to sigconf.}
131 \setkeys{acmart.cls}{format=sigconf}
132 \fi
133 \ifnum\ACM@format@nr=0\relax
134 \@ACM@manuscripttrue
135 \else
136 \@ACM@manuscriptfalse
137 \fi
138 \@ACM@sigchiamodefalse
139 \ifcase\ACM@format@nr
140 \relax % manuscript
141 \@ACM@journaltrue
142 \or % acmsmall
143 \@ACM@journaltrue
144 \or % acmlarge
145 \@ACM@journaltrue

```



```

146 \or % acmtog
147 \@ACM@journaltrue
148 \or % sigconf
149 \@ACM@journalfalse
150 \or % siggraph
151 \@ACM@journalfalse
152 \or % sigplan
153 \@ACM@journalfalse
154 \or % sigchi
155 \@ACM@journalfalse
156 \or % sigchi-a
157 \@ACM@journalfalse
158 \@ACM@sigchiamodetrue
159 \fi

```

3.5 Loading the base class and package

At this point we either have \ACM@fontsize or use defaults

```

160 \ifx\ACM@fontsize\@empty
161 \ifcase\ACM@format@nr
162 \relax % manuscript
163 \def\ACM@fontsize{9pt}%
164 \or % acmsmall
165 \def\ACM@fontsize{10pt}%
166 \or % acmlarge
167 \def\ACM@fontsize{10pt}%
168 \or % acmtog
169 \def\ACM@fontsize{9pt}%
170 \or % sigconf
171 \def\ACM@fontsize{9pt}%
172 \or % siggraph
173 \def\ACM@fontsize{9pt}%
174 \or % sigplan
175 \def\ACM@fontsize{10pt}%
176 \or % sigchi
177 \def\ACM@fontsize{10pt}%
178 \or % sigchi-a
179 \def\ACM@fontsize{10pt}%
180 \fi
181 \fi
182 \ClassInfo{\@classname}{Using fontsize \ACM@fontsize}
183 \LoadClass[\ACM@fontsize, reqno]{amsart}
184 \RequirePackage{microtype}

```

We need etoolbox for delayed code

```
185 \RequirePackage{etoolbox}
```

We need totpages to calculate the number of pages and refcount to use that number

```
186 \RequirePackage{refcount}
```

```
187 \RequirePackage{totpages}
```

The `\collect@body` macro in `amsmath` is defined using `\def`. We load `environ` to access the `\long` version of this command

```
188 \RequirePackage{environ}
```

We use `setspace` for double spacing

```
189 \if@ACM@manuscript
```

```
190 \RequirePackage{setspace}
```

```
191 \onehalfspacing
```

```
192 \fi
```

We need `textcase` for better upcasing

```
193 \RequirePackage{textcase}
```

3.6 Citations

We patch `\setcitestyle` to allow, for example, `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citestyle` to warn about undefined citation styles.

```
194 \if@ACM@natbib
```

```
195 \RequirePackage{natbib}
```

```
196 \renewcommand{\bibsection}{%
```

```
197 \section*{\refname}%
```

```
198 \phantomsection\addcontentsline{toc}{section}{\refname}%
```

```
199 }
```

```
200 \renewcommand{\bibfont}{\bibliofont}
```

```
201 \renewcommand\setcitestyle[1]{
```

```
202 \@for\@tempa:=#1\do
```

```
203 {\def\@tempb{round}\ifx\@tempa\@tempb
```

```
204 \renewcommand\NAT@open{()\renewcommand\NAT@close{}}\fi
```

```
205 \def\@tempb{square}\ifx\@tempa\@tempb
```

```
206 \renewcommand\NAT@open{[]\renewcommand\NAT@close{[]}\fi
```

```
207 \def\@tempb{angle}\ifx\@tempa\@tempb
```

```
208 \renewcommand\NAT@open{<}\renewcommand\NAT@close{>}\fi
```

```
209 \def\@tempb{curly}\ifx\@tempa\@tempb
```

```
210 \renewcommand\NAT@open{\{\}\renewcommand\NAT@close{\}}\fi
```

```
211 \def\@tempb{semicolon}\ifx\@tempa\@tempb
```

```
212 \renewcommand\NAT@sep{;}\fi
```

```
213 \def\@tempb{colon}\ifx\@tempa\@tempb
```

```
214 \renewcommand\NAT@sep{:}\fi
```

```
215 \def\@tempb{comma}\ifx\@tempa\@tempb
```

```
216 \renewcommand\NAT@sep{,}\fi
```

```
217 \def\@tempb{authoryear}\ifx\@tempa\@tempb
```

```
218 \NAT@numbersfalse\fi
```

```
219 \def\@tempb{numbers}\ifx\@tempa\@tempb
```

```
220 \NAT@numberstrue\NAT@superfalse\fi
```

```
221 \def\@tempb{super}\ifx\@tempa\@tempb
```

```
222 \NAT@numberstrue\NAT@supertrue\fi
```

```
223 \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
```

```
224 \let\bibstyle=@gobble\fi
```

```

225 \def\@tempb{bibstyle}\ifx\@tempa\@tempb
226   \let\bibstyle=\@citestyle\fi
227 \def\@tempb{sort}\ifx\@tempa\@tempb
228   \def\NAT@sort{\@ne}\fi
229 \def\@tempb{nosort}\ifx\@tempa\@tempb
230   \def\NAT@sort{\z}\fi
231 \def\@tempb{compress}\ifx\@tempa\@tempb
232   \def\NAT@cmprs{\@ne}\fi
233 \def\@tempb{nocompress}\ifx\@tempa\@tempb
234   \def\NAT@cmprs{\z}\fi
235 \def\@tempb{sort&compress}\ifx\@tempa\@tempb
236   \def\NAT@sort{\@ne}\def\NAT@cmprs{\@ne}\fi
237 \def\@tempb{mcite}\ifx\@tempa\@tempb
238   \let\NAT@merge\@ne\fi
239 \def\@tempb{merge}\ifx\@tempa\@tempb
240   \@ifnum{\NAT@merge<\tw@}{\let\NAT@merge\tw@}\fi
241 \def\@tempb{elide}\ifx\@tempa\@tempb
242   \@ifnum{\NAT@merge<\thr@}{\let\NAT@merge\thr@}\fi
243 \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
244   \NAT@longnamestrue\fi
245 \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
246   \def\NAT@nmfmt#1{\mbox{\NAT@up#1}}\fi
247 \expandafter\NAT@find@eq\@tempa=\relax\@nil
248 \if\@tempc\relax\else
249   \expandafter\NAT@rem@eq\@tempc
250   \def\@tempb{open}\ifx\@tempa\@tempb
251     \xdef\NAT@open{\@tempc}\fi
252   \def\@tempb{close}\ifx\@tempa\@tempb
253     \xdef\NAT@close{\@tempc}\fi
254   \def\@tempb{aysep}\ifx\@tempa\@tempb
255     \xdef\NAT@aysep{\@tempc}\fi
256   \def\@tempb{yysep}\ifx\@tempa\@tempb
257     \xdef\NAT@yrsep{\@tempc}\fi
258   \def\@tempb{notesep}\ifx\@tempa\@tempb
259     \xdef\NAT@cmt{\@tempc}\fi
260   \def\@tempb{citesep}\ifx\@tempa\@tempb
261     \xdef\NAT@sep{\@tempc}\fi
262   \fi
263 }%
264 \NAT@@setcites
265 }
266 \renewcommand\citestyle[1]{%
267   \ifcsname bibstyle@#1\endcsname%
268   \csname bibstyle@#1\endcsname\let\bibstyle\@gobble%
269   \else%
270   \@latex@error{Undefined ‘#1’ citestyle}%
271   \fi
272 }%
273 \fi

```

`\bibstyle@acmauthoryear` The default author-year format:

```

274 \newcommand{\bibstyle@acmauthoryear}{%
275   \setcitestyle{%
276     authoryear,%
277     open={},close={},citesep={;},%
278     aysep={},yysep={,},%
279     notesep={, }}}
```

`\bibstyle@acmnumeric` The default numeric format:

```

280 \newcommand{\bibstyle@acmnumeric}{%
281   \setcitestyle{%
282     numbers,sort&compress,%
283     open={},close={},citesep={,},%
284     notesep={, }}}
```

The default is numeric:

```

285 \if@ACM@natbib
286 \citestyle{acmnumeric}
287 \fi
```

`\@startsection` Before we call `hyperref`, we redefine `\startsection` commands to their \LaTeX defaults since the `amsart` ones are too AMS-specific. We need to do this early since we want `hyperref` to have a chance to redefine them again:

```

288 \def\@startsection#1#2#3#4#5#6{%
289   \if@noskipsec \leavevmode \fi
290   \par
291   \@tempkipa #4\relax
292   \@afterindenttrue
293   \ifdim \@tempkipa <\z@
294     \@tempkipa -\@tempkipa \@afterindentfalse
295   \fi
296   \if@nobreak
297     \everypar{}%
298   \else
299     \addpenalty\@secpenalty\advspace\@tempkipa
300   \fi
301   \@ifstar
302     {\@ssect{#3}{#4}{#5}{#6}}%
303     {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}
304 \def\@sect#1#2#3#4#5#6[#7]#8{%
305   \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
306   \ifnum #2>\c@secnumdepth
307     \let\@svsec\@empty
308   \else
309     \refstepcounter{#1}%
310     \protected@edef\@svsec{\@secntformat{#1}\relax}%
311   \fi
312   \@tempkipa #5\relax
313   \ifdim \@tempkipa>\z@
```

```

314 \begingroup
315 #6{%
316 \@hangfrom{\hskip #3\relax\@svsec}%
317 \interlinepenalty \@M #8\@par}%
318 \endgroup
319 \csname #1mark\endcsname{#7}%
320 \ifnum #2>\c@secnumdepth \else
321 \@tochangmeasure{\csname the#1\endcsname}%
322 \fi
323 \addcontentsline{toc}{#1}{%
324 \ifnum #2>\c@secnumdepth \else
325 \protect\numberline{\csname the#1\endcsname}%
326 \fi
327 #7}%
328 \else
329 \def\@svsechd{%
330 #6{\hskip #3\relax
331 \@svsec #8}%
332 \csname #1mark\endcsname{#7}%
333 \ifnum #2>\c@secnumdepth \else
334 \@tochangmeasure{\csname the#1\endcsname\space}%
335 \fi
336 \addcontentsline{toc}{#1}{%
337 \ifnum #2>\c@secnumdepth \else
338 \protect\numberline{\csname the#1\endcsname}%
339 \fi
340 #7}}%
341 \fi
342 \@xsect{#5}}
343 \def\@xsect#1{%
344 \@tempskipa #1\relax
345 \ifdim \@tempskipa>\z@
346 \par \nobreak
347 \vskip \@tempskipa
348 \@afterheading
349 \else
350 \@nobreakfalse
351 \global\@noskipsectrue
352 \everypar{%
353 \if@noskipsec
354 \global\@noskipsecfalse
355 {\setbox\z@\lastbox}%
356 \clubpenalty\@M
357 \begingroup \@svsechd \endgroup
358 \unskip
359 \@tempskipa #1\relax
360 \hskip -\@tempskipa
361 \else
362 \clubpenalty \@clubpenalty
363 \everypar{}%

```

```

364     \fi}%
365 \fi
366 \ignorespaces}
367 \def\@seccntformat#1{\csname the#1\endcsname\quad}
368 \def\@ssect#1#2#3#4#5{%
369   \@tempskipa #3\relax
370   \ifdim \@tempskipa>\z@
371     \begingroup
372       #4{%
373         \@hangfrom{\hskip #1}%
374         \interlinepenalty \@M #5\@par}%
375     \endgroup
376   \else
377     \def\@svsechd{#4{\hskip #1\relax #5}}%
378   \fi
379   \@xsect{#3}}

```

`\@startsection` The `amsart` package redefines `\startsection`. Here we redefine it again to make the table of contents work.

```

380 \def\@starttoc#1#2{\begingroup\makeatletter
381   \setTrue{#1}%
382   \par\removelastskip\vskip\z@skip
383   \@startsection{section}\@M\z@{\linespacing\@plus\linespacing}%
384     {.5\linespacing}{centering\contentsnamefont}{#2}%
385   \input{\jobname.#1}%
386   \if@filesw
387     \exp\newwrite\csname tf#1\endcsname
388     \immediate\exp\openout\csname tf#1\endcsname \jobname.#1\relax
389   \fi
390   \global\@nbreakfalse \endgroup
391   \addvspace{32\p@\@plus14\p@}%
392 }

```

`\l@section` Section spacing is more generous than for `amsart`

```

393 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}

```

`\l@subsection` The spacing in `amsart` is too large

```

394 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}

```

`\l@subsubsection` The spacing in `amsart` is too large

```

395 \def\l@subsubsection{\@tocline{2}{0pt}{1pc}{5pc}{}}

```

And `hyperref`

```

396 \let\@footnotemark@nolink\@footnotemark
397 \let\@footnotetext@nolink\@footnotetext
398 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
399 \pdfstringdefDisableCommands{%
400   \def\unskip{}}%
401   \def\textbullet{- }%

```

```

402 \def\textrightarrow{ -> }%
403 \def\footnotemark{ }%
404 }
405 \urlstyle{rm}
406 \ifcase\ACM@format@nr
407 \relax % manuscript
408 \or % acmsmall
409 \or % acmlarge
410 \or % acmtog
411 \or % sigconf
412 \or % siggraph
413 \or % sigplan
414 \urlstyle{sf}
415 \or % sigchi
416 \or % sigchi-a
417 \urlstyle{sf}
418 \fi
419 \AtEndPreamble{%
420 \if@ACM@screen
421 \hypersetup{colorlinks,
422 linkcolor=ACMRed,
423 citecolor=ACMPurple,
424 urlcolor=ACMDarkBlue,
425 filecolor=ACMDarkBlue}
426 \else
427 \hypersetup{hidelinks}
428 \fi}

Bibliography mangling.
429 \if@ACM@natbib
430 \let\cite\cite
431 \let\cite\citep
432 \let\citeANP\citeauthor
433 \let\citeNN\citeyearpar
434 \let\citeyearNP\citeyear
435 \let\citeNP\citealt
436 \DeclareRobustCommand\citeA
437 {\begingroup\NAT@swafalse
438 \let\NAT@ctype\@ne\NAT@partrue\NAT@fullfalse\NAT@open\NAT@citetp}%
439 \providecommand\newblock{}%
440 \else
441 \AtBeginDocument{%
442 \let\shortcite\cite%
443 \providecommand\citename[1]{#1}}
444 \fi
445 \newcommand\shortcite[2][ ]{%
446 \ifNAT@numbers\cite[#1]{#2}\else\citeyearpar[#1]{#2}\fi}

```

`\bibliographystyle` The `amsart` package redefines `\bibliographystyle` since it prefers the AMS bibliography style. We turn it back to the \LaTeX definition:

```

447 \def\bibliographystyle#1{%
448   \ifx\@begindocumenthook\@undefined\else
449     \expandafter\AtBeginDocument
450     \fi
451     {\if@filesw
452       \immediate\write\@auxout{\string\bibstyle{#1}}%
453       \fi}}

```

Graphics and color.

```

454 \RequirePackage{graphicx}
455 \RequirePackage[prologue]{xcolor}

```

We define ACM colors according to [7]:

```

456 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
457 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
458 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
459 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
460 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
461 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
462 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
463 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}

```

Author-draft mode

```

464 \if@ACM@authordraft
465   \RequirePackage{draftwatermark}
466   \SetWatermarkFontSize{0.5in}
467   \SetWatermarkColor[gray]{.9}
468   \SetWatermarkText{\parbox{12em}{\centering
469     Unpublished working draft.\
470     Not for distribution.}}
471 \fi

```

3.7 Paper size and paragraphing

We use geometry for dimensions. Note that the present margins do not depend on the font size option—we might need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```

472 \RequirePackage{geometry}
473 \ifcase\ACM@format@nr
474 \relax % manuscript
475   \geometry{letterpaper,head=13pt,
476     marginparwidth=6pc,heightrounded}%
477 \or % acmsmall
478   \geometry{twoside=true,
479     includeheadfoot, head=13pt, foot=2pc,
480     paperwidth=6.75in, paperheight=10in,
481     top=58pt, bottom=44pt, inner=46pt, outer=46pt,
482     marginparwidth=2pc,heightrounded
483     }%
484 \or % acmlarge

```



```

485 \geometry{twoside=true, head=13pt, foot=2pc,
486   paperwidth=8.5in, paperheight=11in,
487   includeheadfoot,
488   top=78pt, bottom=114pt, inner=81pt, outer=81pt,
489   marginparwidth=4pc,heightrounded
490   }%
491 \or % acmtog
492 \geometry{twoside=true, head=13pt, foot=2pc,
493   paperwidth=8.5in, paperheight=11in,
494   includeheadfoot, columnsep=24pt,
495   top=52pt, bottom=75pt, inner=52pt, outer=52pt,
496   marginparwidth=2pc,heightrounded
497   }%
498 \or % sigconf
499 \geometry{twoside=true, head=13pt,
500   paperwidth=8.5in, paperheight=11in,
501   includeheadfoot, columnsep=2pc,
502   top=57pt, bottom=73pt, inner=54pt, outer=54pt,
503   marginparwidth=2pc,heightrounded
504   }%
505 \or % siggraph
506 \geometry{twoside=true, head=13pt,
507   paperwidth=8.5in, paperheight=11in,
508   includeheadfoot, columnsep=2pc,
509   top=57pt, bottom=73pt, inner=54pt, outer=54pt,
510   marginparwidth=2pc,heightrounded
511   }%
512 \or % sigplan
513 \geometry{twoside=true, head=13pt,
514   paperwidth=8.5in, paperheight=11in,
515   includeheadfoot=false, columnsep=2pc,
516   top=1in, bottom=1in, inner=0.75in, outer=0.75in,
517   marginparwidth=2pc,heightrounded
518   }%
519 \or % sigchi
520 \geometry{twoside=true, head=13pt,
521   paperwidth=8.5in, paperheight=11in,
522   includeheadfoot, columnsep=2pc,
523   top=66pt, bottom=73pt, inner=54pt, outer=54pt,
524   marginparwidth=2pc,heightrounded
525   }%
526 \or % sigchi-a
527 \geometry{twoside=false, head=13pt,
528   paperwidth=11in, paperheight=8.5in,
529   includeheadfoot, marginparsep=72pt,
530   marginparwidth=170pt, columnsep=20pt,
531   top=72pt, bottom=72pt, left=314pt, right=72pt
532   }%
533 \@mparswitchfalse
534 \reversemarginpar

```

535 \fi

\parindent Paragraphing

```
\parskip 536 \setlength\parindent{10\p@}
537 \setlength\parskip{\z@}
538 \ifcase\ACM@format@nr
539 \relax % manuscript
540 \or % acmsmall
541 \or % acmlarge
542 \or % acmtog
543 \setlength\parindent{9\p@}%
544 \or % sigconf
545 \or % siggraph
546 \or % sigplan
547 \or % sigchi
548 \or % sigchi-a
549 \fi
```

\normalparindent The `amsart` package defines the `\normalparindent` length and initializes it to 12pt (the value of `\parindent` in `amsart`). It is later used to set the `\listparindent` length in the quotation environment and the `\parindent` length in the `\@footnotetext` command. We set `\normalparindent` to the value of `\parindent` as selected by `acmart` for consistent paragraph indents.

```
550 \setlength\normalparindent{\parindent}
```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for the bibstrip. In the old ACM classes, the bibstrip was a `\@float`. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use `manyfoot` for layered footnotes instead.

\copyrightpermissionfootnoterule This is the footnote rule that separates the bibstrip from the rest of the paper. It is a full width rule.

```
551 \def\copyrightpermissionfootnoterule{\kern-3\p@
552 \hrule \@width \columnwidth \kern 2.6\p@}

553 \RequirePackage{manyfoot}
554 \SelectFootnoteRule[2]{copyrightpermission}
555 \DeclareNewFootnote{authorsaddresses}
556 \SelectFootnoteRule[2]{copyrightpermission}
557 \DeclareNewFootnote{copyrightpermission}
```

\footnoterule Tschichold’s rules:

```
558 \def\footnoterule{\kern-3\p@
559 \hrule \@width 4pc \kern 2.6\p@}
```

\endminipage We do not use footnote rules in minipages

```
560 \def\endminipage{%
561 \par
```

```

562 \unskip
563 \ifvoid\@mpfootins\else
564 \vskip\skip\@mpfootins
565 \normalcolor
566 \unvbox\@mpfootins
567 \fi
568 \@minipagefalse
569 \color@endgroup
570 \egroup
571 \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}

\@makefnmark We do not use indentation for footnotes
572 \def\@makefnmark{\noindent\@makefnmark}

\@footnotetext In sigchi-a mode our footnotes are in the margin!
573 \if@ACM@sigchiamode
574 \long\def\@footnotetext#1{\marginpar{%
575 \reset@font\small
576 \interlinepenalty\interfootnotelinepenalty
577 \protected@edef\@currentlabel{%
578 \csname p@footnote\endcsname\@thefnmark
579 }%
580 \color@begingroup
581 \@makefnmark{%
582 \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
583 \color@endgroup}}%
584 \fi

\@mpfootnotetext We want the footnotes in minipages centered:
585 \long\def\@mpfootnotetext#1{%
586 \global\setbox\@mpfootins\vbox{%
587 \unvbox\@mpfootins
588 \reset@font\footnotesize
589 \hsize\columnwidth
590 \@parboxrestore
591 \protected@edef\@currentlabel
592 {\csname p@mpfootnote\endcsname\@thefnmark}%
593 \color@begingroup\centering
594 \@makefnmark{%
595 \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
596 \color@endgroup}}

\@makefnmark AMS classes use a buggy definition of \makefnmark. We revert to the standard one.
597 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

\@textbottom Add some stretch according to David Carlisle's advice at http://tex.stackexchange.com/a/62318/5522
598 \def\@textbottom{\vskip \z@ \@plus 1pt}
599 \let\@texttop\relax

```

3.8 Fonts

Somehow PDFTeX and XeTeX require different incantations to make a PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```
600 \RequirePackage{iftex}
601 \ifPDFTeX
602 \input{glyphtounicode}
603 \pdfglyphtounicode{f_f}{FB00}
604 \pdfglyphtounicode{f_f_i}{FB03}
605 \pdfglyphtounicode{f_f_l}{FB04}
606 \pdfglyphtounicode{f_i}{FB01}
607 \pdfglyphtounicode{t_t}{00740074}
608 \pdfglyphtounicode{f_t}{00660074}
609 \pdfglyphtounicode{T_h}{00540068}
610 \pdfgentounicode=1
611 \fi
612 \RequirePackage{cmap}
```

`\if@ACM@newfonts` Whether we load the new fonts

```
613 \newif\if@ACM@newfonts
614 \@ACM@newfontstrue
615 \IfFileExists{libertine.sty}{\ClassWarning{\@classname}{You do not
616   have the libertine package installed. Please upgrade your
617   TeX}\@ACM@newfontsfalse}
618 \IfFileExists{zi4.sty}{\ClassWarning{\@classname}{You do not
619   have the zi4 package installed. Please upgrade your
620   TeX}\@ACM@newfontsfalse}
621 \IfFileExists{newtxmath.sty}{\ClassWarning{\@classname}{You do not
622   have the newtxmath package installed. Please upgrade your
623   TeX}\@ACM@newfontsfalse}
```

We use Libertine throughout.

```
624 \if@ACM@newfonts
625 \RequirePackage[tt=false, type1=true]{libertine}
626 \RequirePackage[varqu]{zi4}
627 \RequirePackage[libertine]{newtxmath}
628 \RequirePackage[T1]{fontenc}
629 \fi
```

`\liningnums` Libertine defines `\liningnums`, which makes `fontspec` unhappy. While we do not use `fontspec`, some users do.

```
630 \let\liningnums\@undefined
631 \AtEndPreamble{%
632   \DeclareTextFontCommand{\liningnums}{\libertineLF}}
```

The SIGCHI extended abstracts are sans serif:

```
633 \if@ACM@sigchiamode
634 \renewcommand{\familydefault}{\sfdefault}
635 \fi
```

3.9 Floats

We use the caption package

```
636 \RequirePackage{caption, float}
637 \captionsetup[table]{position=top}
638 \if@ACM@journal
639   \captionsetup{labelfont={sf, small},
640     textfont={sf, small}, margin=\z@}
641   \captionsetup[figure]{name={Fig.}}
642 \else
643   \captionsetup{labelfont={bf},
644     textfont={bf}, labelsep=colon, margin=\z@}
645   \ifcase\ACM@format@nr
646     \relax % manuscript
647     \or % acmsmall
648     \or % acmlarge
649     \or % acmtog
650     \or % sigconf
651     \or % siggraph
652     \captionsetup{textfont={it}}
653     \or % sigplan
654     \captionsetup{labelfont={bf},
655       textfont={normalfont}, labelsep=period, margin=\z@}
656     \or % sigchi
657     \captionsetup[figure]{labelfont={bf, small},
658       textfont={bf, small}}
659     \or % sigchi-a
660     \captionsetup[figure]{labelfont={bf, small},
661       textfont={bf, small}}
662   \fi
663 \fi
```

sidebar The sidebar environment:

```
664 \newfloat{sidebar}{}{sbar}
665 \floatname{sidebar}{Sidebar}
666 \renewenvironment{sidebar}{\Collect@Body\@sidebar}{}
```

\@sidebar The processing of the saved text

```
667 \long\def\@sidebar#1{\bgroup\captionsetup{type=sidebar}%
668   \marginpar{\small#1}\egroup}
```

marginfigure The marginfigure environment:

```
669 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}
```

\@marginfigure The processing of the saved text

```
670 \long\def\@marginfigure#1{\bgroup\captionsetup{type=figure}%
671   \marginpar{\centering\small#1}\egroup}
```

marginable The marginable environment:

```
672 \newenvironment{marginable}{\Collect@Body\@marginable}{}
```

`\@margintable` The processing of the saved text
673 `\long\def\@margintable#1{\bgroup\captionsetup{type=table}}%`
674 `\marginpar{\centering\small#1}\egroup}`

SIGCHI extended abstracts provide an interesting possibility to push into the margin. Here we use `figure*` and `table*` for this.

`\fulltextwidth` We define the width of the boxes as
675 `\newdimen\fulltextwidth`
676 `\fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)`

`\dblfloat` We redefine the double-float command. First, we make the size bigger. Second, our default position is going to be `tp` (to give marginalia a chance)
677 `\if@ACM@sigchiamode`
678 `\def\@dblfloat{\bgroup\columnwidth=\fulltextwidth`
679 `\let\@endfloatbox\@endwidefloatbox`
680 `\def\@fpsaddefault{\def\@fps{tp}}%`
681 `\@float}`
682 `\fi`

`\enddblfloat` And the end. Just adding a `\bgroup`.
683 `\if@ACM@sigchiamode`
684 `\def\enddblfloat{%`
685 `\end@float\egroup}`
686 `\fi`

`\@endwidefloatbox` This is the end of a wide box—we basically move everything to the left
687 `\def\@endwidefloatbox{%`
688 `\par\vskip\z@skip`
689 `\@minipagefalse`
690 `\outer@nobreak`
691 `\egroup`
692 `\color@endbox`
693 `\global\setbox\@currbox=\vbox{\moveleft`
694 `\dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%`
695 `\wd\@currbox=\textwidth`
696 `}`

3.10 Lists

```
697 \ifcase\ACM@format@nr
698 \relax % manuscript
699 \or % acsmall
700 \or % acmlarge
701 \or % acmtog
702 \or % sigconf
703 \or % siggraph
704 \or % sigplan
705 \def\labelenumi{\theenumi.}
```

```

706 \def\labelenumii{\theenumii.}
707 \def\labelenumiii{\theenumiii.}
708 \def\labelenumiv{\theenumiv.}
709 \or % sigchi
710 \or % sigchi-a
711 \fi

```

The AMS uses generous margins for lists. Note that `amsart` defines `\leftmargin` values for list levels at the beginning of the document, so we must redefine them in the same manner. Also, note that `amsart` redefines the `enumerate` and `itemize` environments with a `\makelabel` command that uses `\llap`, so the `\labelwidth` value is (effectively) irrelevant; nonetheless, we follow `amsart` and set `\labelwidth` to `\leftmargin` minus `\labelsep`.

```

712 \newdimen\@ACM@labelwidth
713 \AtBeginDocument{%
714   \setlength\labelsep{4pt}
715   \setlength{\@ACM@labelwidth}{6.5pt}
716
717   %% First-level list: when beginning after the first line of an
718   %% indented paragraph or ending before an indented paragraph, labels
719   %% should not hang to the left of the preceding/following text.
720   \setlength\leftmarginii{\z@}
721   \addtolength\leftmarginii{\parindent}
722   \addtolength\leftmarginii{2\labelsep}
723   \addtolength\leftmarginii{\@ACM@labelwidth}
724
725   %% Second-level and higher lists.
726   \setlength\leftmarginiii{\z@}
727   \addtolength\leftmarginiii{0.5\labelsep}
728   \addtolength\leftmarginiii{\@ACM@labelwidth}
729   \setlength\leftmarginiiii{\leftmarginiii}
730   \setlength\leftmarginiv{\leftmarginiii}
731   \setlength\leftmarginv{\leftmarginiv}
732   \setlength\leftmarginvi{\leftmarginiv}
733   \@listi}
734 \newskip\listisep
735 \listisep\smallskipamount
736 \def\@listI{\leftmargin\leftmarginii
737   \labelwidth\leftmarginii \advance\labelwidth-\labelsep
738   \listparindent\z@
739   \topsep\listisep}
740 \let\@listi\@listI
741 \def\@listii{\leftmargin\leftmarginii
742   \labelwidth\leftmarginiii \advance\labelwidth-\labelsep
743   \topsep\z@skip}
744 \def\@listiii{\leftmargin\leftmarginiii
745   \labelwidth\leftmarginiiii \advance\labelwidth-\labelsep}
746 \def\@listiv{\leftmargin\leftmarginiv
747   \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
748 \def\@listv{\leftmargin\leftmarginv

```

```

749 \labelwidth\leftmarginv \advance\labelwidth-\labelsep}
750 \def\@listvi{\leftmargin\leftmarginvi
751 \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}
\descriptionlabel We do not use a colon by default like amsart does:
752 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

\description Make the description environment indentation consistent with that of the itemize
and enumerate environments.
753 \renewenvironment{description}{\list{}}{%
754 \labelwidth\@ACM@labelwidth
755 \let\makelabel\descriptionlabel}%
756 }{
757 \endlist
758 }
759 \let\enddescription=\endlist % for efficiency

```

3.11 Top-matter data

We use the xkeyval interface to define journal titles and the relevant information

```

760 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
761 CIE,%
762 CSUR,%
763 DTRAP,%
764 IMMUT,%
765 JACM,%
766 JDIQ,%
767 JEA,%
768 JERIC,%
769 JETC,%
770 JOCCH,%
771 PACMHCI,%
772 PACMPL,%
773 POMACS,%
774 TAAS,%
775 TACCESS,%
776 TACO,%
777 TALG,%
778 TALLIP,%
779 TAP,%
780 TCPS,%
781 TEAC,%
782 TECS,%
783 THRI,%
784 TIIS,%
785 TISSEC,%
786 TIST,%
787 TKDD,%
788 TMIS,%

```



```

789 TOCE,%
790 TOCHI,%
791 TOCL,%
792 TOCS,%
793 TOCT,%
794 TODAES,%
795 TODS,%
796 TOG,%
797 TOIS,%
798 TOIT,%
799 TOMACS,%
800 TOMM,%
801 TOMPECS,%
802 TOMS,%
803 TOPC,%
804 TOPS,%
805 TOPLAS,%
806 TOS,%
807 TOSEM,%
808 TOSN,%
809 TRETs,%
810 TSAS,%
811 TSC,%
812 TSLP,%
813 TWEB%
814 }{%
815 \ifcase\@journalCode@nr
816 \relax % CIE
817 \def\@journalName{ACM Computers in Entertainment}%
818 \def\@journalNameShort{ACM Comput. Entertain.}%
819 \def\@permissionCodeOne{1544-3574}%
820 \or % CSUR
821 \def\@journalName{ACM Computing Surveys}%
822 \def\@journalNameShort{ACM Comput. Surv.}%
823 \def\@permissionCodeOne{0360-0300}%
824 \or % DTRAP
825 \def\@journalName{Digital Threats: Research and Practice}%
826 \def\@journalNameShort{Digit. Threat. Res. Pract.}%
827 \def\@permissionCodeOne{2576-5337}%
828 \or % IMWUT
829 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
830 Wearable and Ubiquitous Technologies}%
831 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
832 \def\@permissionCodeOne{2474-9567}%
833 \@ACM@screentruer
834 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
835 \or % JACM
836 \def\@journalName{Journal of the ACM}%
837 \def\@journalNameShort{J. ACM}%
838 \def\@permissionCodeOne{0004-5411}%

```

```

839 \or % JDIQ
840 \def\@journalName{ACM Journal of Data and Information Quality}%
841 \def\@journalNameShort{ACM J. Data Inform. Quality}%
842 \def\@permissionCodeOne{1936-1955}%
843 \or % JEA
844 \def\@journalName{ACM Journal of Experimental Algorithmics}%
845 \def\@journalNameShort{ACM J. Exp. Algor.}%
846 \def\@permissionCodeOne{1084-6654}%
847 \or % JERIC
848 \def\@journalName{ACM Journal of Educational Resources in Computing}%
849 \def\@journalNameShort{ACM J. Edu. Resources in Comput.}%
850 \def\@permissionCodeOne{1073-0516}%
851 \or % JETC
852 \def\@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
853 \def\@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
854 \def\@permissionCodeOne{1550-4832}%
855 \or % JOCCH
856 \def\@journalName{ACM Journal on Computing and Cultural Heritage}%
857 \def\@journalNameShort{ACM J. Comput. Cult. Herit.}%
858 \or % PACMHCI
859 \def\@journalName{Proceedings of the ACM on Human-Computer Interaction}%
860 \def\@journalNameShort{Proc. ACM Hum.-Comput. Interact.}%
861 \def\@permissionCodeOne{2573-0142}%
862 \@ACM@screentruer
863 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
864 \or % PACMPL
865 \def\@journalName{Proceedings of the ACM on Programming Languages}%
866 \def\@journalNameShort{Proc. ACM Program. Lang.}%
867 \def\@permissionCodeOne{2475-1421}%
868 \@ACM@screentruer
869 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
870 \or % POMACS
871 \def\@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
872 \def\@journalNameShort{Proc. ACM Meas. Anal. Comput. Syst.}%
873 \def\@permissionCodeOne{2476-1249}%
874 \@ACM@screentruer
875 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
876 \or % TAAS
877 \def\@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
878 \def\@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
879 \def\@permissionCodeOne{1556-4665}%
880 \or % TACCESS
881 \def\@journalName{ACM Transactions on Accessible Computing}%
882 \def\@journalNameShort{ACM Trans. Access. Comput.}%
883 \def\@permissionCodeOne{1936-7228}%
884 \or % TACO
885 \def\@journalName{ACM Transactions on Architecture and Code Optimization}%
886 \def\@journalNameShort{ACM Trans. Arch. Code Optim.}%
887 \or % TALG
888 \def\@journalName{ACM Transactions on Algorithms}%

```

```

889 \def\@journalNameShort{ACM Trans. Algor.}%
890 \def\@permissionCodeOne{1549-6325}%
891 \or % TALLIP
892 \def\@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
893 \def\@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
894 \def\@permissionCodeOne{2375-4699}%
895 \or % TAP
896 \def\@journalName{ACM Transactions on Applied Perception}%
897 \or % TCPS
898 \def\@journalName{ACM Transactions on Cyber-Physical Systems}%
899 \or % TEAC
900 \def\@journalName{ACM Transactions on Economics and Computation}%
901 \or % TECS
902 \def\@journalName{ACM Transactions on Embedded Computing Systems}%
903 \def\@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
904 \def\@permissionCodeOne{1539-9087}%
905 \or % THRI
906 \def\@journalName{ACM Transactions on Human-Robot Interaction}%
907 \def\@journalNameShort{ACM Trans. Hum.-Robot Interact.}%
908 \def\@permissionCodeOne{2573-9522}%
909 \or % TIIS
910 \def\@journalName{ACM Transactions on Interactive Intelligent Systems}%
911 \def\@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
912 \def\@permissionCodeOne{2160-6455}%
913 \or % TISSEC
914 \def\@journalName{ACM Transactions on Information and System Security}%
915 \def\@journalNameShort{ACM Trans. Info. Syst. Sec.}%
916 \def\@permissionCodeOne{1094-9224}%
917 \or % TIST
918 \def\@journalName{ACM Transactions on Intelligent Systems and Technology}%
919 \def\@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
920 \def\@permissionCodeOne{2157-6904}%
921 \or % TKDD
922 \def\@journalName{ACM Transactions on Knowledge Discovery from Data}%
923 \def\@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
924 \def\@permissionCodeOne{1556-4681}%
925 \or % TMIS
926 \def\@journalName{ACM Transactions on Management Information Systems}%
927 \def\@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
928 \def\@permissionCodeOne{2158-656X}%
929 \or % TOCE
930 \def\@journalName{ACM Transactions on Computing Education}%
931 \def\@journalNameShort{ACM Trans. Comput. Educ.}%
932 \def\@permissionCodeOne{1946-6226}%
933 \or % TOCHI
934 \def\@journalName{ACM Transactions on Computer-Human Interaction}%
935 \def\@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
936 \def\@permissionCodeOne{1073-0516}%
937 \or % TOCL
938 \def\@journalName{ACM Transactions on Computational Logic}%

```

939 \def\@journalNameShort{ACM Trans. Comput. Logic}%
940 \def\@permissionCodeOne{1529-3785}%
941 \or % TOCS
942 \def\@journalName{ACM Transactions on Computer Systems}%
943 \def\@journalNameShort{ACM Trans. Comput. Syst.}%
944 \def\@permissionCodeOne{0734-2071}%
945 \or % TOCT
946 \def\@journalName{ACM Transactions on Computation Theory}%
947 \def\@journalNameShort{ACM Trans. Comput. Theory}%
948 \def\@permissionCodeOne{1942-3454}%
949 \or % TODAES
950 \def\@journalName{ACM Transactions on Design Automation of Electronic Systems}%
951 \def\@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
952 \def\@permissionCodeOne{1084-4309}%
953 \or % TODS
954 \def\@journalName{ACM Transactions on Database Systems}%
955 \def\@journalNameShort{ACM Trans. Datab. Syst.}%
956 \def\@permissionCodeOne{0362-5915}%
957 \or % TOG
958 \def\@journalName{ACM Transactions on Graphics}%
959 \def\@journalNameShort{ACM Trans. Graph.}%
960 \def\@permissionCodeOne{0730-0301}%
961 \or % TOIS
962 \def\@journalName{ACM Transactions on Information Systems}%
963 \def\@permissionCodeOne{1046-8188}%
964 \or % TOIT
965 \def\@journalName{ACM Transactions on Internet Technology}%
966 \def\@journalNameShort{ACM Trans. Internet Technol.}%
967 \def\@permissionCodeOne{1533-5399}%
968 \or % TOMACS
969 \def\@journalName{ACM Transactions on Modeling and Computer Simulation}%
970 \def\@journalNameShort{ACM Trans. Model. Comput. Simul.}%
971 \or % TOMM
972 \def\@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
973 \def\@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
974 \def\@permissionCodeOne{1551-6857}%
975 \def\@permissionCodeTwo{0100}%
976 \or % TOMPECS
977 \def\@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
978 \def\@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
979 \def\@permissionCodeOne{2376-3639}%
980 \or % TOMS
981 \def\@journalName{ACM Transactions on Mathematical Software}%
982 \def\@journalNameShort{ACM Trans. Math. Softw.}%
983 \def\@permissionCodeOne{0098-3500}%
984 \or % TOPC
985 \def\@journalName{ACM Transactions on Parallel Computing}%
986 \def\@journalNameShort{ACM Trans. Parallel Comput.}%
987 \def\@permissionCodeOne{1539-9087}%
988 \or % TOPS

```

989 \def\@journalName{ACM Transactions on Privacy and Security}%
990 \def\@journalNameShort{ACM Trans. Priv. Sec.}%
991 \def\@permissionCodeOne{2471-2566}%
992 \or % TOPLAS
993 \def\@journalName{ACM Transactions on Programming Languages and Systems}%
994 \def\@journalNameShort{ACM Trans. Program. Lang. Syst.}%
995 \def\@permissionCodeOne{0164-0925}%
996 \or % TOS
997 \def\@journalName{ACM Transactions on Storage}%
998 \def\@journalNameShort{ACM Trans. Storage}%
999 \def\@permissionCodeOne{1553-3077}%
1000 \or % TOSEM
1001 \def\@journalName{ACM Transactions on Software Engineering and Methodology}%
1002 \def\@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
1003 \def\@permissionCodeOne{1049-331X}%
1004 \or % TOSN
1005 \def\@journalName{ACM Transactions on Sensor Networks}%
1006 \def\@journalNameShort{ACM Trans. Sensor Netw.}%
1007 \def\@permissionCodeOne{1550-4859}%
1008 \or % TRET
1009 \def\@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
1010 \def\@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
1011 \def\@permissionCodeOne{1936-7406}%
1012 \or % TSAS
1013 \def\@journalName{ACM Transactions on Spatial Algorithms and Systems}%
1014 \def\@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
1015 \def\@permissionCodeOne{2374-0353}%
1016 \or % TSC
1017 \def\@journalName{ACM Transactions on Social Computing}%
1018 \def\@journalNameShort{ACM Trans. Soc. Comput.}%
1019 \def\@permissionCodeOne{2469-7818}%
1020 \or % TSLP
1021 \def\@journalName{ACM Transactions on Speech and Language Processing}%
1022 \def\@journalNameShort{ACM Trans. Speech Lang. Process.}%
1023 \def\@permissionCodeOne{1550-4875}%
1024 \or % TWEB
1025 \def\@journalName{ACM Transactions on the Web}%
1026 \def\@journalNameShort{ACM Trans. Web}%
1027 \def\@permissionCodeOne{1559-1131}%
1028 \fi
1029 \ClassInfo{\@classname}{Using journal code \@journalCode}%
1030 }{%
1031 \ClassError{\@classname}{Incorrect journal #1}%
1032 }%

```

\acmJournal And the syntactic sugar around it

```
1033 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}}
```

The defaults:

```
1034 \def\@journalCode@nr{0}
```

```

1035 \def\@journalName{%
1036 \def\@journalNameShort{\@journalName}%
1037 \def\@permissionCodeOne{XXXX-XXXX}%
1038 \def\@permissionCodeTwo{%

\acmConference This is the conference command
1039 \newcommand\acmConference[4][{}%
1040 \gdef\acmConference@shortname{#1}%
1041 \gdef\acmConference@name{#2}%
1042 \gdef\acmConference@date{#3}%
1043 \gdef\acmConference@venue{#4}%
1044 \ifx\acmConference@shortname\empty
1045 \gdef\acmConference@shortname{#2}%
1046 \fi}
1047 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1048 DC, USA}

\acmBooktitle The book title of the conference:
\@acmBooktitle 1049 \def\acmBooktitle#1{\gdef\acmBooktitle{#1}}
1050 \acmBooktitle{Proceedings of \acmConference@name
1051 \ifx\acmConference@name\acmConference@shortname\else
1052 \ (\acmConference@shortname)\fi}

\@editorsAbbrev How to abbreviate editors
1053 \def\@editorsAbbrev{(Ed.)}

\@acmEditors The list of editors
1054 \def\@acmEditors{}

\editor Add a new editor to the list
1055 \def\editor#1{\ifx\@acmEditors\empty
1056 \gdef\@acmEditors{#1}%
1057 \else
1058 \gdef\@editorsAbbrev{(Eds.)}%
1059 \g@addto@macro\@acmEditors{\and#1}%
1060 \fi}

\subtitle The subtitle macro
1061 \def\subtitle#1{\def\@subtitle{#1}}
1062 \subtitle{}

\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)
1063 \newcount\num@authorgroups
1064 \num@authorgroups=0\relax

\num@authors The total number of authors
1065 \newcount\num@authors
1066 \num@authors=0\relax

```

`\if@insideauthorgroup` Whether we are continuing an author group

```
1067 \newif\if@insideauthorgroup
1068 \@insideauthorgroupfalse
```

`\author` Adding an author to the list of authors and addresses

```
1069 \renewcommand\author[2][{}%
1070 \global\advance\num@authors by 1\relax
1071 \if@insideauthorgroup\else
1072 \global\advance\num@authorgroups by 1\relax
1073 \global\@insideauthorgrouptrue
1074 \fi
1075 \ifx\addresses\@empty
1076 \if@ACM@anonymous
1077 \gdef\addresses{\@author{Anonymous Author(s)}}%
1078 \gdef\authors{Anonymous Author(s)}%
1079 \else
1080 \gdef\addresses{\@author{#2}}%
1081 \gdef\authors{#2}%
1082 \fi
1083 \else
1084 \if@ACM@anonymous\else
1085 \g@addto@macro\addresses{\and\@author{#2}}%
1086 \g@addto@macro\authors{\and#2}%
1087 \fi
1088 \fi
1089 \if@ACM@anonymous
1090 \ifx\shortauthors\@empty
1091 \gdef\shortauthors{Anon.}%
1092 \fi
1093 \else
1094 \def\@tempa{#1}%
1095 \ifx\@tempa\@empty
1096 \ifx\shortauthors\@empty
1097 \gdef\shortauthors{#2}%
1098 \else
1099 \g@addto@macro\shortauthors{\and#2}%
1100 \fi
1101 \else
1102 \ifx\shortauthors\@empty
1103 \gdef\shortauthors{#1}%
1104 \else
1105 \g@addto@macro\shortauthors{\and#1}%
1106 \fi
1107 \fi
1108 \fi}
```

`\affiliation` The macro `\affiliation` mimics `\address` from `amsart`. Note that it has an optional argument, which we use differently from `amsart`.

```
1109 \newcommand{\affiliation}[2][{}%
```

```

1110 \global\@insideauthorgroupfalse
1111 \if@ACM@anonymous\else
1112   \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1113   \fi}

@ACM@affiliation@obeypunctuation Whether to use the author's punctuation (false by default, which adds American-style
address punctuation)
1114 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1115 [true]{}{\ClassError{\@classname}{The option obeypunctuation can be either true or false}}

\additionalaffiliation Additional affiliations go to footnotes
1116 \def\additionalaffiliation#1{\authornote{\@additionalaffiliation{#1}}}

@additionalaffiliation Process \additionalaffiliation inside \authornote
1117 \def\@additionalaffiliation#1{\bgroup
1118   \def\position##1{\ignorespaces}%
1119   \def\institution##1{##1\ignorespaces}%
1120   \def\department{\@ifnextchar[{\@department}{\@department[]}}%
1121   \def\@department[##1]##2{\unskip, ##2\ignorespaces}%
1122   \let\streetaddress\position
1123   \let\city\position
1124   \let\state\position
1125   \let\postcode\position
1126   \let\country\position
1127   Also with #1\unskip.\egroup}

\email The macro \email mimics \email from amsart. Again, it has an optional argument that
we do not currently need but keep for possible future use.
1128 \renewcommand{\email}[2][{}]{%
1129   \if@ACM@anonymous\else
1130     \g@addto@macro\addresses{\email{#1}{#2}}%
1131     \fi}

\orcid Right now we do not typeset ORCIDs
1132 \def\orcid#1{\unskip\ignorespaces}

\authorsaddresses Setting up authors' addresses
1133 \def\authorsaddresses#1{\def\@authorsaddresses{#1}}
1134 \authorsaddresses{\mkauthorsaddresses}

@titlenotes The title notes
1135 \def\@titlenotes{}

\titlenote Adding a note to the title
1136 \def\titlenote#1{%
1137   \g@addto@macro\@title{\footnotemark}%
1138   \if@ACM@anonymous
1139     \g@addto@macro\@titlenotes{%

```



```

1140     \stepcounter{footnote}\footnotetext{Title note}}%
1141 \else
1142     \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1143 \fi}

\@subtitlenotes The subtitle notes
1144 \def\@subtitlenotes{}

\subtitlenote Adding a note to the subtitle
1145 \def\subtitlenote#1{%
1146     \g@addto@macro\@subtitle{\footnotemark}%
1147     \if@ACM@anonymous
1148         \g@addto@macro\@subtitlenotes{%
1149             \stepcounter{footnote}\footnotetext{Subtitle note}}%
1150     \else
1151         \g@addto@macro\@subtitlenotes{%
1152             \stepcounter{footnote}\footnotetext{#1}}%
1153 \fi}

\@authornotes The author notes
1154 \def\@authornotes{}

\authornote Adding a note to the author
1155 \def\authornote#1{%
1156     \if@ACM@anonymous\else
1157         \g@addto@macro\addresses{\@authornotemark}%
1158         \g@addto@macro\@authornotes{%
1159             \stepcounter{footnote}\footnotetext{#1}}%
1160 \fi}

\authornotemark Adding a footnote mark to the authors
1161 \newcommand\authornotemark[1][\relax]{%
1162     \ifx#1\relax\relax\relax
1163     \g@addto@macro\addresses{\@authornotemark}%
1164     \else
1165     \g@addto@macro\addresses{\@@authornotemark{#1}}%
1166 \fi}

\acmVolume The current volume
1167 \def\acmVolume#1{\def\@acmVolume{#1}}
1168 \acmVolume{1}

\acmNumber The current number
1169 \def\acmNumber#1{\def\@acmNumber{#1}}
1170 \acmNumber{1}

\acmArticle The current article
1171 \def\acmArticle#1{\def\@acmArticle{#1}}
1172 \acmArticle{}

```

`\acmArticleSeq` The sequence number
1173 `\def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}`
1174 `\acmArticleSeq{\@acmArticle}`

`\acmYear` The current year
1175 `\def\acmYear#1{\def\@acmYear{#1}}`
1176 `\acmYear{\the\year}`

`\acmMonth` The current month
1177 `\def\acmMonth#1{\def\@acmMonth{#1}}`
1178 `\acmMonth{\the\month}`

`\@acmPubDate` The publication date
1179 `\def\@acmPubDate{\ifcase\@acmMonth\or`
1180 `January\or February\or March\or April\or May\or June\or`
1181 `July\or August\or September\or October\or November\or`
1182 `December\fi\@acmYear}`

`\acmPrice` The price
1183 `\def\acmPrice#1{\def\@acmPrice{#1}}`
1184 `\acmPrice{15.00}`

`\acmSubmissionID` The submission ID
1185 `\def\acmSubmissionID#1{\def\@acmSubmissionID{#1}}`
1186 `\acmSubmissionID{}`

`\acmISBN` The book ISBN
1187 `\def\acmISBN#1{\def\@acmISBN{#1}}`
1188 `\acmISBN{978-x-xxxx-xxxx-x/YY/MM}`

`\acmDOI` The paper DOI
1189 `\def\acmDOI#1{\def\@acmDOI{#1}}`
1190 `\acmDOI{10.1145/nnnnnnn.nnnnnnn}`

`\if@ACM@badge` Whether to print a badge. Note that either a left or right badge triggers it:
1191 `\newif\if@ACM@badge`
1192 `\@ACM@badgefalse`

`\@ACM@badge@width` The width of the badge
1193 `\newlength\@ACM@badge@width`
1194 `\setlength\@ACM@badge@width{5pc}`

`\@ACM@title@width` The width of the badge
1195 `\newlength\@ACM@title@width`

`\@ACM@badge@skip` The space between the badge and the title
1196 `\newlength\@ACM@badge@skip`
1197 `\setlength\@ACM@badge@skip{1pc}`

`\acmBadgeR` Setting the right badge

```

1198 \newcommand\acmBadgeR[2][\@ACM@badgetrue
1199   \def\@acmBadgeR@url{#1}%
1200   \def\@acmBadgeR@image{#2}}
1201 \def\@acmBadgeR@url{}
1202 \def\@acmBadgeR@image{}

```

`\acmBadgeL` Setting the left badge

```

1203 \newcommand\acmBadgeL[2][\@ACM@badgetrue
1204   \def\@acmBadgeL@url{#1}%
1205   \def\@acmBadgeL@image{#2}}
1206 \def\@acmBadgeL@url{}
1207 \def\@acmBadgeL@image{}

```

`\startPage` The start page of the paper

```

1208 \def\startPage#1{\def\@startPage{#1}}
1209 \startPage{}

```

`\terms` Terms are obsolete. We use CCS now.

```

1210 \def\terms#1{\ClassWarning{\@classname}{The command \string\terms} is
1211   obsolete. I am going to ignore it}}

```

`\keywords` Keywords are mostly obsolete. We use CCS now. Still it makes sense to keep them for compatibility.

```

1212 \def\keywords#1{\def\@keywords{#1}}
1213 \keywords{}

```

`abstract` The amsart package puts abstract in a box. Since we do not know whether we will use two-column mode, we prefer to save the text

```

1214 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{}

```

`\@saveabstract` And saving the abstract

```

1215 \long\def\@saveabstract#1{\long\gdef\@abstract{#1}}
1216 \@saveabstract{}

```

`\@empty` The long version of `\@empty` (to compare with `\@abstract`)

```

1217 \long\def\@empty{}

```

`\if@ACM@printccs` Whether to print CCS

```

1218 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printccs}[true]{%
1219   \if@ACM@printccs
1220     \ClassInfo{\@classname}{Printing CCS}%
1221   \else
1222     \ClassInfo{\@classname}{Suppressing CCS}%
1223   \fi}{\ClassError{\@classname}{The option printccs can be either true or false}}

```

`\if@ACM@printacmref` Whether to print the ACM bibstrip

```

1224 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%
1225   \if@ACM@printacmref
1226   \ClassInfo{\@classname}{Printing bibformat}%
1227   \else
1228   \ClassInfo{\@classname}{Suppressing bibformat}%
1229 \fi}{\ClassError{\@classname}{The option printacmref can be either true or false}}

```

`\if@ACM@printfolios` Whether to print folios

```

1230 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%
1231   \if@ACM@printfolios
1232   \ClassInfo{\@classname}{Printing folios}%
1233   \else
1234   \ClassInfo{\@classname}{Suppressing folios}%
1235 \fi}{\ClassError{\@classname}{The option printfolios can be either true or false}}

```

`\@ACM@authorsperrrow` The number of authors per row. 0 means use the default algorithm.

```

1236 \define@cmdkey{@ACM@topmatter@}[@ACM@]{authorsperrrow}[0]{%
1237   \IfInteger{#1}{\ClassInfo{\@classname}{Setting authorsperrrow to
1238     #1}}{\ClassWarning{\@classname}{The parameter authorsperrrow must be
1239     numerical. Ignoring the input #1}}\gdef\@ACM@authorsperrrow{0}}

```

`\settopmatter` The usual syntactic sugar

```

1240 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}

```

Now the settings

```

1241 \settopmatter{printccs=true, printacmref=true}
1242 \if@ACM@manuscript
1243   \settopmatter{printfolios=true}
1244 \else
1245   \if@ACM@journal
1246     \settopmatter{printfolios=true}
1247   \else
1248     \settopmatter{printfolios=false}
1249   \fi
1250 \fi
1251 \settopmatter{authorsperrrow=0}

```

`\@received` The container for the paper history

```

1252 \def\@received{}

```

`\received` The `\received` command

```

1253 \newcommand\received[2][\def\@tempa{#1}%
1254   \ifx\@tempa\@empty
1255     \ifx\@received\@empty
1256       \gdef\@received{Received #2}%
1257     \else
1258       \g@addto@macro{\@received}{; revised #2}%
1259     \fi

```

```

1260 \else
1261 \ifx\@received\@empty
1262 \gdef\@received{#1 #2}%
1263 \else
1264 \g@addto@macro{\@received}{; #1 #2}%
1265 \fi
1266 \fi}
1267 \AtEndDocument{%
1268 \ifx\@received\@empty\else
1269 \par\bigskip\noindent\small\normalfont\@received\par
1270 \fi}

```

3.12 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```

1271 \RequirePackage{comment}
1272 \excludecomment{CCSXML}

```

\@concepts This is the storage macro for concepts

```

1273 \let\@concepts\@empty

```

\ccsdesc The first argument is the significance, the second is the concept(s)

```

1274 \newcommand\ccsdesc[2][100]{%
1275 \ccsdesc@parse#1~#2~\ccsdesc@parse@end}

```

\ccsdesc@parse The parser of the expression Significance~General~Specific (we need textcomp for \textrightarrow). Note that Specific can be empty!

```

1276 \RequirePackage{textcomp}
1277 \def\ccsdesc@parse#1~#2~#3~{%
1278 \expandafter\ifx\csname CCS@General@#2\endcsname\relax
1279 \expandafter\gdef\csname CCS@General@#2\endcsname{\textbullet\
1280 \textbf{#2}}%
1281 \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{; }%
1282 \expandafter\gdef\csname CCS@Specific@#2\endcsname{}%
1283 \g@addto@macro{\@concepts}{\csname CCS@General@#2\endcsname
1284 \csname CCS@Punctuation@#2\endcsname
1285 \csname CCS@Specific@#2\endcsname}%
1286 \fi
1287 \ifx#3\relax\relax\else
1288 \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{
1289 \textrightarrow\ }%
1290 \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@#2\endcsname}{%
1291 \ifnum#1>499\textbf{#3}; \else
1292 \ifnum#1>299\textit{#3}; \else
1293 #3; \fi\fi}%
1294 \fi
1295 \ccsdesc@parse@finish}

```

\ccdesc@parse@finish Gobble everything to \ccsdesc@parse@end

```

1296 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}

```

3.13 Copyright system

This is from acmcopyright.sty

`\if@printcopyright` Whether to print a copyright symbol
1297 `\newif\if@printcopyright`
1298 `\@printcopyrighttrue`

`\if@printpermission` Whether to print the permission block
1299 `\newif\if@printpermission`
1300 `\@printpermissiontrue`

`\if@acmowned` Whether the ACM owns the rights to the paper
1301 `\newif\if@acmowned`
1302 `\@acmownedtrue`

Keys:

```
1303 \define@choicekey*{ACM@}{acmcopyrightmode}[%
1304   \acm@copyrightinput\acm@copyrightmode]{none,%
1305     acmcopyright,acmlicensed,rightsretained,%
1306     usgov,usgovmixed,cagov,cagovmixed,licensedusgovmixed,%
1307     licensedcagov,licensedcagovmixed,othergov,licensedothergov,%
1308     iw3c2w3,iw3c2w3g}{%
1309   \@printpermissiontrue
1310   \@printcopyrighttrue
1311   \@acmownedtrue
1312   \ifnum\acm@copyrightmode=0\relax % none
1313     \@printpermissionfalse
1314     \@printcopyrightfalse
1315     \@acmownedfalse
1316   \fi
1317   \ifnum\acm@copyrightmode=2\relax % acmlicensed
1318     \@acmownedfalse
1319   \fi
1320   \ifnum\acm@copyrightmode=3\relax % rightsretained
1321     \@acmownedfalse
1322     \acmPrice{}%
1323   \fi
1324   \ifnum\acm@copyrightmode=4\relax % usgov
1325     \@printpermissiontrue
1326     \@printcopyrightfalse
1327     \@acmownedfalse
1328     \acmPrice{}%
1329   \fi
1330   \ifnum\acm@copyrightmode=6\relax % cagov
1331     \@acmownedfalse
1332   \fi
1333   \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1334     \@acmownedfalse
1335   \fi
```

```

1336 \ifnum\acm@copyrightmode=9\relax % licensedcagov
1337   \@acmownedfalse
1338 \fi
1339 \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1340   \@acmownedfalse
1341 \fi
1342 \ifnum\acm@copyrightmode=11\relax % othergov
1343   \@acmownedtrue
1344 \fi
1345 \ifnum\acm@copyrightmode=12\relax % licensedothergov
1346   \@acmownedfalse
1347 \fi
1348 \ifnum\acm@copyrightmode=13\relax % iw3c2w3
1349   \@acmownedfalse
1350 \fi
1351 \ifnum\acm@copyrightmode=14\relax % iw3c2w3g
1352   \@acmownedfalse
1353 \fi}

```

`\setcopyright` This is the syntactic sugar around setting keys.

```

1354 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1355 \setcopyright{acmcopyright}

```

`\@copyrightowner` Here is the owner of the copyright

```

1356 \def\@copyrightowner{%
1357   \ifcase\acm@copyrightmode\relax % none
1358   \or % acmcopyright
1359   Association for Computing Machinery.
1360   \or % acmlicensed
1361   Copyright held by the owner/author(s). Publication rights licensed to
1362   the Association for Computing Machinery.
1363   \or % rightsretained
1364   Copyright held by the owner/author(s).
1365   \or % usgov
1366   \or % usgovmixed
1367   Association for Computing Machinery.
1368   \or % cagov
1369   Crown in Right of Canada.
1370   \or % cagovmixed
1371   Association for Computing Machinery.
1372   \or % licensedusgovmixed
1373   Copyright held by the owner/author(s). Publication rights licensed to
1374   the Association for Computing Machinery.
1375   \or % licensedcagov
1376   Crown in Right of Canada. Publication rights licensed to
1377   the Association for Computing Machinery.
1378   \or % licensedcagovmixed
1379   Copyright held by the owner/author(s). Publication rights licensed to
1380   the Association for Computing Machinery.
1381   \or % othergov

```

1382 Association for Computing Machinery.
 1383 \or % licensedothergov
 1384 Copyright held by the owner/author(s). Publication rights licensed to
 1385 the Association for Computing Machinery.
 1386 \or % ic2w3www
 1387 IW3C2 (International World Wide Web Conference Committee), published
 1388 under Creative Commons CC~BY~4.0 License.
 1389 \or % ic2w3wwwgoogle
 1390 IW3C2 (International World Wide Web Conference Committee), published
 1391 under Creative Commons CC~BY-NC-ND~4.0 License.
 1392 \fi}

\@formatdoi Print a clickable DOI

1393 \def\@formatdoi#1{\url{https://doi.org/#1}}

\@copyrightpermission The canned permission block.

1394 \def\@copyrightpermission{%
 1395 \ifcase\acm@copyrightmode\relax % none
 1396 \or % acmcopyright
 1397 Permission to make digital or hard copies of all or part of this
 1398 work for personal or classroom use is granted without fee provided
 1399 that copies are not made or distributed for profit or commercial
 1400 advantage and that copies bear this notice and the full citation on
 1401 the first page. Copyrights for components of this work owned by
 1402 others than ACM must be honored. Abstracting with credit is
 1403 permitted. To copy otherwise, or republish, to post on servers or to
 1404 redistribute to lists, requires prior specific permission
 1405 and\hspace*{.5pt}/or a fee. Request permissions from
 1406 permissions@acm.org.
 1407 \or % acmlicensed
 1408 Permission to make digital or hard copies of all or part of this
 1409 work for personal or classroom use is granted without fee provided
 1410 that copies are not made or distributed for profit or commercial
 1411 advantage and that copies bear this notice and the full citation on
 1412 the first page. Copyrights for components of this work owned by
 1413 others than the author(s) must be honored. Abstracting with credit
 1414 is permitted. To copy otherwise, or republish, to post on servers
 1415 or to redistribute to lists, requires prior specific permission
 1416 and\hspace*{.5pt}/or a fee. Request permissions from
 1417 permissions@acm.org.
 1418 \or % rightsretained
 1419 Permission to make digital or hard copies of part or all of this work
 1420 for personal or classroom use is granted without fee provided that
 1421 copies are not made or distributed for profit or commercial advantage
 1422 and that copies bear this notice and the full citation on the first
 1423 page. Copyrights for third-party components of this work must be
 1424 honored. For all other uses, contact the
 1425 owner\hspace*{.5pt}/author(s).
 1426 \or % usgov
 1427 This paper is authored by an employee(s) of the United States

1428 Government and is in the public domain. Non-exclusive copying or
1429 redistribution is allowed, provided that the article citation is
1430 given and the authors and agency are clearly identified as its
1431 source.

1432 \or % usgovmixed
1433 ACM acknowledges that this contribution was authored or co-authored
1434 by an employee, contractor, or affiliate of the United States government. As such,
1435 the United States government retains a nonexclusive, royalty-free right to
1436 publish or reproduce this article, or to allow others to do so, for
1437 government purposes only.

1438 \or % cagov
1439 This article was authored by employees of the Government of Canada.
1440 As such, the Canadian government retains all interest in the
1441 copyright to this work and grants to ACM a nonexclusive,
1442 royalty-free right to publish or reproduce this article, or to allow
1443 others to do so, provided that clear attribution is given both to
1444 the authors and the Canadian government agency employing them.
1445 Permission to make digital or hard copies for personal or classroom
1446 use is granted. Copies must bear this notice and the full citation
1447 on the first page. Copyrights for components of this work owned by
1448 others than the Canadian Government must be honored. To copy
1449 otherwise, distribute, republish, or post, requires prior specific
1450 permission and\hspace*{.5pt}/or a fee. Request permissions from
1451 permissions@acm.org.

1452 \or % cagovmixed
1453 ACM acknowledges that this contribution was co-authored by an
1454 affiliate of the national government of Canada. As such, the Crown
1455 in Right of Canada retains an equal interest in the copyright.
1456 Reprints must include clear attribution to ACM and the author's
1457 government agency affiliation. Permission to make digital or hard
1458 copies for personal or classroom use is granted. Copies must bear
1459 this notice and the full citation on the first page. Copyrights for
1460 components of this work owned by others than ACM must be honored.
1461 To copy otherwise, distribute, republish, or post, requires prior
1462 specific permission and\hspace*{.5pt}/or a fee. Request permissions
1463 from permissions@acm.org.

1464 \or % licensedusgovmixed
1465 Publication rights licensed to ACM\@. ACM acknowledges that this
1466 contribution was authored or co-authored by an employee, contractor
1467 or affiliate of the United States government. As such, the
1468 Government retains a nonexclusive, royalty-free right to publish or
1469 reproduce this article, or to allow others to do so, for Government
1470 purposes only.

1471 \or % licensedcagov
1472 This article was authored by employees of the Government of Canada.
1473 As such, the Canadian government retains all interest in the
1474 copyright to this work and grants to ACM a nonexclusive,
1475 royalty-free right to publish or reproduce this article, or to allow
1476 others to do so, provided that clear attribution is given both to
1477 the authors and the Canadian government agency employing them.

1478 Permission to make digital or hard copies for personal or classroom
1479 use is granted. Copies must bear this notice and the full citation
1480 on the first page. Copyrights for components of this work owned by
1481 others than the Canadian Government must be honored. To copy
1482 otherwise, distribute, republish, or post, requires prior specific
1483 permission and\hspace*{.5pt}/or a fee. Request permissions from
1484 permissions@acm.org.

1485 \or % licensedcagovmixed

1486 Publication rights licensed to ACM\@. ACM acknowledges that this
1487 contribution was authored or co-authored by an employee, contractor
1488 or affiliate of the national government of Canada. As such, the
1489 Government retains a nonexclusive, royalty-free right to publish or
1490 reproduce this article, or to allow others to do so, for Government
1491 purposes only.

1492 \or % othergov

1493 ACM acknowledges that this contribution was authored or co-authored
1494 by an employee, contractor or affiliate of a national government. As
1495 such, the Government retains a nonexclusive, royalty-free right to
1496 publish or reproduce this article, or to allow others to do so, for
1497 Government purposes only.

1498 \or % licensedothergov

1499 Publication rights licensed to ACM\@. ACM acknowledges that this
1500 contribution was authored or co-authored by an employee, contractor
1501 or affiliate of a national government. As such, the Government
1502 retains a nonexclusive, royalty-free right to publish or reproduce
1503 this article, or to allow others to do so, for Government purposes
1504 only.

1505 \or % iw3c2w3

1506 This paper is published under the Creative Commons Attribution~4.0
1507 International (CC~BY~4.0) license. Authors reserve their rights to
1508 disseminate the work on their personal and corporate Web sites with
1509 the appropriate attribution. In case of republication, reuse, etc.,
1510 the following attribution should be used: ‘‘Published in
1511 WWW\@acmYear{} Proceedings \textcopyright{} \@copyrightyear{}
1512 International World Wide Web Conference Committee, published under
1513 Creative Commons~CC~BY~4.0 License.’’

1514 \or % iw3c2w3g

1515 This paper is published under the Creative Commons
1516 Attribution-NonCommercial-NoDerivs~4.0 International
1517 (CC~BY-NC-ND~4.0) license. Authors reserve their rights to
1518 disseminate the work on their personal and corporate Web sites with
1519 the appropriate attribution. In case of republication, reuse, etc.,
1520 the following attribution should be used: ‘‘Published in
1521 WWW\@acmYear{} Proceedings \textcopyright{} \@copyrightyear
1522 International World Wide Web Conference Committee, published under
1523 Creative Commons CC~BY-NC-ND~4.0 License.’’

1524 \fi}

\copyrightyear By default, the copyright year is the same as \acmYear, but one can override this:

1525 \def\copyrightyear#1{\def\@copyrightyear{#1}}

```

1526 \copyrightyear{\@acmYear}

\@teaserfigures The teaser figures container
1527 \def\@teaserfigures{}

teaserfigure The teaser figure
1528 \newenvironment{teaserfigure}{\Collect@Body\@saveteaser}{}

\@saveteaser Saving the teaser
1529 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}

\thanks We redefine amsart \thanks so the anonymous key works
1530 \renewcommand{\thanks}[1]{%
1531   \ifnotempty{#1}{%
1532     \if@ACM@anonymous
1533       \g@addto@macro\thankses{\thanks{A note}}%
1534     \else
1535       \g@addto@macro\thankses{\thanks{#1}}%
1536     \fi}}

```

3.14 Typesetting top matter

`\mktitle@bx` Some of our formats use a two-column design. Some use a one-column design. In all cases we use a wide title. Thus we typeset the top matter in a special box to be used in the construction `\@twocolumn[box]`.

```

1537 \newbox\mktitle@bx

```

`\maketitle` The (in)famous `\maketitle`. Note that in sigchi-a mode, authors are *not* in the title box.

Another note: there is a subtle difference between author notes, title notes and thanks. The latter two refer to the paper itself and therefore belong to the copyright/permission block. By the way, this was the default behavior of the old ACM classes.

```

1538 \def\maketitle{%
1539   \if@ACM@anonymous
1540     % Anonymize omission of \author-s
1541     \ifnum\@authorgroups=0\author{}\fi
1542   \fi
1543   \begingroup
1544   \let\@footnotemark\@footnotemark@nolink
1545   \let\@footnotetext\@footnotetext@nolink
1546   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1547   \global\@topnum\z@ % this prevents floats from falling
1548                       % at the top of page 1
1549   \global\@botnum\z@ % we do not want them to be on the bottom either
1550   \hsize=\textwidth
1551   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
1552   \mktitle\if@ACM@sigchiamode\else\mkauthors\fi\mkteasers
1553   \@printtopmatter

```

```

1554 \if@ACM@sigchiamode\mkauthors\fi
1555 \setcounter{footnote}{0}%
1556 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
1557 \@titlenotes
1558 \@subtitlenotes
1559 \@authornotes
1560 \let\@makefnmark\relax
1561 \let\@thefnmark\relax
1562 \let\@makefntext\noindent
1563 \ifx\@empty\thankses\else
1564   \footnotetextauthorsaddresses{%
1565     \def\par{\let\par\@par}\parindent\z@\@setthanks}%
1566 \fi
1567 \ifx\@empty\@authorsaddresses\else
1568   \if@ACM@anonymous\else
1569     \if@ACM@journal
1570       \footnotetextauthorsaddresses{%
1571         \def\par{\let\par\@par}\parindent\z@\@setauthorsaddresses}%
1572     \fi
1573   \fi
1574 \fi
1575 \footnotetextcopyrightpermission{%
1576   \if@ACM@authordraft
1577     \raisebox{-2ex}[\z@][\z@]{\makebox[0pt][l]{\large\bfseries
1578       Unpublished working draft. Not for distribution.}}%
1579     \color[gray]{0.9}%
1580   \fi
1581   \parindent\z@\parskip0.1\baselineskip
1582   \if@ACM@authorversion\else
1583     \if@printpermission\@copyrightpermission\par\fi
1584   \fi
1585   \if@ACM@manuscript\else
1586     \if@ACM@journal\else % Print the conference information
1587       {\itshape \acmConference@shortname, \acmConference@date, \acmConference@venue}\par
1588     \fi
1589   \fi
1590   \if@printcopyright
1591     \copyright\ \@copyrightyear\ \@copyrightowner\
1592   \else
1593     \@copyrightyear.\
1594   \fi
1595   \if@ACM@manuscript
1596     Manuscript submitted to ACM\
1597   \else
1598     \if@ACM@authorversion
1599       This is the author's version of the work. It is posted here for
1600       your personal use. Not for redistribution. The definitive Version
1601       of Record was published in
1602     \if@ACM@journal
1603       \emph{\@journalName}%

```

```

1604         \else
1605             \emph{\@acmBooktitle}%
1606         \fi
1607         \ifx\@acmDOI\@empty
1608             .
1609         \else
1610             , \@formatdoi{\@acmDOI}.
1611         \fi\\
1612     \else
1613         \if@ACM@journal
1614             \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
1615             \ifx\@acmPrice\@empty\else\ $\@acmPrice\fi\\
1616             \@formatdoi{\@acmDOI}%
1617         \else % Conference
1618             \ifx\@acmISBN\@empty\else ACM~ISBN~\@acmISBN
1619             \ifx\@acmPrice\@empty.\else\dots\$\@acmPrice\fi\\fi
1620             \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi%
1621         \fi
1622     \fi
1623 \fi}
1624 \endgroup
1625 \setcounter{footnote}{0}%
1626 \@mkabstract
1627 \if@ACM@printccs
1628     \ifx\@concepts\@empty\else\bgroup
1629         {\@specialsection{CCS Concepts}%
1630         \@concepts\par}\egroup
1631     \fi
1632 \fi
1633 \ifx\@keywords\@empty\else\bgroup
1634     {\if@ACM@journal
1635         \@specialsection{Additional Key Words and Phrases}%
1636     \else
1637         \@specialsection{Keywords}%
1638     \fi
1639     \@keywords}\par\egroup
1640 \fi
1641 \andify\authors
1642 \andify\shortauthors
1643 \global\let\authors=\authors
1644 \global\let\shortauthors=\shortauthors
1645 \if@ACM@printacmref
1646     \@mkbibcitation
1647 \fi
1648 \hypersetup{%
1649     pdflang={English},
1650     pdfdisplaydoctitle,
1651     pdfauthor={\authors},
1652     pdftitle={\@title},
1653     pdfsubject={\@concepts},

```

```

1654 pdfkeywords={\@keywords},
1655 pdfcreator={LaTeX with acmart
1656   \csname ver@acmart.cls\endcsname\space
1657   and hyperref
1658   \csname ver@hyperref.sty\endcsname}}%
1659 \@printendtopmatter
1660 \@afterindentfalse
1661 \@afterheading
1662 }

```

`\@specialsection` This macro starts sections for proceedings and uses `\small` for journals

```

1663 \def\@specialsection#1{%
1664   \ifcase\ACM@format@nr
1665   \relax % manuscript
1666   \par\medskip\small\noindent#1: %
1667   \or % acmsmall
1668   \par\medskip\small\noindent#1: %
1669   \or % acmlarge
1670   \par\medskip\small\noindent#1: %
1671   \or % acmtog
1672   \par\medskip\small\noindent#1: %
1673   \or % sigconf
1674   \section*{#1}%
1675   \or % siggraph
1676   \section*{#1}%
1677   \or % sigplan
1678   \paragraph*{#1}%
1679   \or % sigchi
1680   \section*{#1}%
1681   \or % sigchi-a
1682   \section*{#1}%
1683   \fi}

```

`\@printtopmatter` The printing of top matter starts a new page and uses the given title box. Note that for `sigchi-a` we print badges here rather than in `\mktitle` since we want them in the margins.

```

1684 \def\@printtopmatter{%
1685   \ifx\@startPage\@empty
1686     \gdef\@startPage{1}%
1687   \else
1688     \setcounter{page}{\@startPage}%
1689   \fi
1690   \thispagestyle{firstpagestyle}%
1691   \noindent
1692   \ifcase\ACM@format@nr
1693   \relax % manuscript
1694     \box\mktitle@bx\par
1695   \or % acmsmall
1696     \box\mktitle@bx\par

```

```

1697 \or % acmlarge
1698   \box\mktitle@bx\par
1699 \or % acmtog
1700   \twocolumn[\box\mktitle@bx]%
1701 \or % sigconf
1702   \twocolumn[\box\mktitle@bx]%
1703 \or % siggraph
1704   \twocolumn[\box\mktitle@bx]%
1705 \or % sigplan
1706   \twocolumn[\box\mktitle@bx]%
1707 \or % sigchi
1708   \twocolumn[\box\mktitle@bx]%
1709 \or % sigchi-a
1710   \par\box\mktitle@bx\par\bigskip
1711   \if@ACM@badge
1712     \marginpar{\noindent
1713       \ifx\@acmBadgeL@image\empty\else
1714         \href{\@acmBadgeL@url}{%
1715           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
1716         \hskip\@ACM@badge@skip
1717       \fi
1718       \ifx\@acmBadgeR@image\empty\else
1719         \href{\@acmBadgeR@url}{%
1720           \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%
1721         \fi}%
1722     \fi
1723 \fi
1724 }

```

\@mktitle The title of the article

```

1725 \def\@mktitle{%
1726   \ifcase\ACM@format@nr
1727   \relax % manuscript
1728   \@mktitle@i
1729   \or % acmsmall
1730   \@mktitle@i
1731   \or % acmlarge
1732   \@mktitle@i
1733   \or % acmtog
1734   \@mktitle@i
1735   \or % sigconf
1736   \@mktitle@iii
1737   \or % siggraph
1738   \@mktitle@iii
1739   \or % sigplan
1740   \@mktitle@iii
1741   \or % sigchi
1742   \@mktitle@iii
1743   \or % sigchi-a
1744   \@mktitle@iv

```

```

1745 \fi
1746 }

\@titlefont The font to typeset the title
1747 \def\@titlefont{%
1748 \ifcase\ACM@format@nr
1749 \relax % manuscript
1750 \LARGE\sffamily\bfseries
1751 \or % acmsmall
1752 \LARGE\sffamily\bfseries
1753 \or % acmlarge
1754 \LARGE\sffamily\bfseries
1755 \or % acmtog
1756 \Huge\sffamily
1757 \or % sigconf
1758 \Huge\sffamily\bfseries
1759 \or % siggraph
1760 \Huge\sffamily\bfseries
1761 \or % sigplan
1762 \Huge\bfseries
1763 \or % sigchi
1764 \Huge\sffamily\bfseries
1765 \or % sigchi-a
1766 \Huge\bfseries
1767 \fi}

\@subtitlefont The font to typeset the subtitle
1768 \def\@subtitlefont{\normalsize
1769 \ifcase\ACM@format@nr
1770 \relax % manuscript
1771 \mdseries
1772 \or % acmsmall
1773 \mdseries
1774 \or % acmlarge
1775 \mdseries
1776 \or % acmtog
1777 \LARGE
1778 \or % sigconf
1779 \LARGE\mdseries
1780 \or % siggraph
1781 \LARGE\mdseries
1782 \or % sigplan
1783 \LARGE\mdseries
1784 \or % sigchi
1785 \LARGE\mdseries
1786 \or % sigchi-a
1787 \mdseries
1788 \fi}

```


`\mktitle@i` The version of `\mktitle` for most journals

```
1789 \def\mktitle@i{\hsize=\textwidth
1790   \ACM@title@width=\hsize
1791   \ifx\@acmBadgeL@image\@empty\else
1792     \advance\ACM@title@width by -\ACM@badge@width
1793     \advance\ACM@title@width by -\ACM@badge@skip
1794   \fi
1795   \ifx\@acmBadgeR@image\@empty\else
1796     \advance\ACM@title@width by -\ACM@badge@width
1797     \advance\ACM@title@width by -\ACM@badge@skip
1798   \fi
1799   \setbox\mktitle@bx=\vbox{\noindent\@titlefont
1800     \ifx\@acmBadgeL@image\@empty\else
1801       \raisebox{- .5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
1802         \includegraphics[width=\ACM@badge@width]{\@acmBadgeL@image}}}%
1803       \hskip\ACM@badge@skip
1804     \fi
1805     \parbox[t]{\ACM@title@width}{\raggedright
1806       \@titlefont\noindent
1807       \@title
1808     \ifx\@subtitle\@empty\else
1809       \par\noindent{\@subtitlefont\@subtitle}
1810     \fi}%
1811     \ifx\@acmBadgeR@image\@empty\else
1812       \hskip\ACM@badge@skip
1813       \raisebox{- .5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
1814         \includegraphics[width=\ACM@badge@width]{\@acmBadgeR@image}}}%
1815     \fi
1816     \par\bigskip}}%
```

`\mktitle@ii` The version of `\mktitle` for TOG. Since v1.06, this is subsumed by the `\mktitle@i` macro

`\mktitle@iii` The version of `\mktitle` for SIG proceedings. Note that since the title is centered, we leave space for the left badge even if only the right badge is defined.

```
1817 \def\mktitle@iii{\hsize=\textwidth
1818   \setbox\mktitle@bx=\vbox{\@titlefont\centering
1819     \ACM@title@width=\hsize
1820     \if@ACM@badge
1821       \advance\ACM@title@width by -2\ACM@badge@width
1822       \advance\ACM@title@width by -2\ACM@badge@skip
1823       \parbox[b]{\ACM@badge@width}{\strut
1824         \ifx\@acmBadgeL@image\@empty\else
1825           \raisebox{- .5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
1826             \includegraphics[width=\ACM@badge@width]{\@acmBadgeL@image}}}%
1827         \fi}%
1828       \hskip\ACM@badge@skip
1829     \fi
1830     \parbox[t]{\ACM@title@width}{\centering\@titlefont
```

```

1831     \@title
1832     \ifx\@subtitle\@empty\else
1833         \par\noindent{\@subtitlefont\@subtitle}
1834     \fi
1835 }%
1836 \if@ACM@badge
1837     \hskip\@ACM@badge@skip
1838     \parbox[b]{\@ACM@badge@width}{\strut
1839         \ifx\@acmBadgeR@image\@empty\else
1840             \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
1841                 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
1842         \fi}%
1843     \fi
1844     \par\bigskip}}%

```

`\@mktitle@iv` The version of `\@mktitle` for `sigchi-a`

```

1845 \def\@mktitle@iv{\hsize=\textwidth
1846     \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
1847         \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
1848         \noindent\@title
1849         \ifx\@subtitle\@empty\else
1850             \par\noindent\@subtitlefont\@subtitle
1851         \fi
1852     \par\bigskip}}%

```

`\@ACM@addtoaddress` This macro adds an item to the address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted if it is at the end of a line. We use the magic `\cleaders` trick for this.

```

1853 \newbox\@ACM@commabox
1854 \def\@ACM@addtoaddress#1{%
1855     \ifvmode\else
1856         \if@ACM@affiliation@obeypunctuation\else
1857             \setbox\@ACM@commabox=\hbox{, }%
1858             \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
1859         \fi\fi
1860     #1}

```

`\institution` `\position` `\department` `\streetaddress` `\city` `\state` `\postcode` `\country` Theoretically we can define the macros for `\affiliation` inside the `\@mkauthors-style` commands. However, this would lead to a strange error if an author uses them outside `\affiliation`. Of course we can make them produce an error message, but...

```

1861 \def\streetaddress#1{\unskip\ignorespaces}
1862 \def\postcode#1{\unskip\ignorespaces}
1863 \if@ACM@journal
1864 \def\position#1{\unskip\ignorespaces}

```

```

1865 \def\institution#1{\unskip~#1\ignorespaces}
1866 \def\city#1{\unskip\ignorespaces}
1867 \def\state#1{\unskip\ignorespaces}
1868 \newcommand\department[2][0]{\unskip\ignorespaces}
1869 \def\country#1{\if@ACM@affiliation@obypunctuation\else, \fi#1\ignorespaces}
1870 \else
1871 \def\position#1{\if@ACM@affiliation@obypunctuation#1\else#1\par\fi}%
1872 \def\institution#1{\if@ACM@affiliation@obypunctuation#1\else#1\par\fi}%
1873 \newcommand\department[2][0]{\if@ACM@affiliation@obypunctuation
1874 #2\else#2\par\fi}%
1875 % \def\streetaddress#1{\if@ACM@affiliation@obypunctuation#1\else#1\par\fi}%
1876 \let\city@ACM@addtoaddress
1877 \let\state@ACM@addtoaddress
1878 % \def\postcode#1{\if@ACM@affiliation@obypunctuation#1\else\unskip\space#1\fi}%
1879 \let\country@ACM@addtoaddress
1880 \fi

```

\@mkauthors Typesetting the authors

```

1881 \def\@mkauthors{\begingroup
1882 \hspace=\textwidth
1883 \ifcase\ACM@format@nr
1884 \relax % manuscript
1885 \@mkauthors@i
1886 \or % acmsmall
1887 \@mkauthors@i
1888 \or % acmlarge
1889 \@mkauthors@i
1890 \or % acmtog
1891 \@mkauthors@i
1892 \or % sigconf
1893 \@mkauthors@iii
1894 \or % siggraph
1895 \@mkauthors@iii
1896 \or % sigplan
1897 \@mkauthors@iii
1898 \or % sigchi
1899 \@mkauthors@iii
1900 \or % sigchi-a
1901 \@mkauthors@iv
1902 \fi
1903 \endgroup
1904 }

```

\@authorfont Somehow different conferences use different fonts for author names. Why?

```

1905 \def\@authorfont{\Large\sffamily}

```

\@affiliationfont Font for affiliations

```

1906 \def\@affiliationfont{\normalsize\normalfont}

```

Adjusting fonts for different formats

```

1907 \ifcase\ACM@format@nr
1908 \relax % manuscript
1909 \or % acmsmall
1910 \def\@authorfont{\large\sffamily}
1911 \def\@affiliationfont{\small\normalfont}
1912 \or % acmlarge
1913 \or % acmtog
1914 \def\@authorfont{\LARGE\sffamily}
1915 \def\@affiliationfont{\large}
1916 \or % sigconf
1917 \def\@authorfont{\LARGE}
1918 \def\@affiliationfont{\large}
1919 \or % siggraph
1920 \def\@authorfont{\normalsize\normalfont}
1921 \def\@affiliationfont{\normalsize\normalfont}
1922 \or % sigplan
1923 \def\@authorfont{\Large\normalfont}
1924 \def\@affiliationfont{\normalsize\normalfont}
1925 \or % sigchi
1926 \def\@authorfont{\bfseries}
1927 \def\@affiliationfont{\mdseries}
1928 \or % sigchi-a
1929 \def\@authorfont{\bfseries}
1930 \def\@affiliationfont{\mdseries}
1931 \fi

```

`\@typeset@author@line` At this point we have `\@currentauthors` and `\@currentaffiliations`. We typeset them in the journal style

```

1932 \def\@typeset@author@line{%
1933 \andify\@currentauthors\par\noindent
1934 \@currentauthors\def\@currentauthors{}%
1935 \ifx\@currentaffiliations\@empty\else
1936 \andify\@currentaffiliations
1937 \unskip, {\@currentaffiliations}\par
1938 \fi
1939 \def\@currentaffiliations{}}

```

`\@mkauthors@i` This version is used in most journal formats. Note that `\and` between authors with the same affiliation becomes `_and_`:

```

1940 \def\@mkauthors@i{%
1941 \def\@currentauthors{}%
1942 \def\@currentaffiliations{}%
1943 \global\let\and\@typeset@author@line
1944 \def\@author##1{%
1945 \ifx\@currentauthors\@empty
1946 \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
1947 \else
1948 \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%

```

```

1949 \fi
1950 \gdef\and{}}%
1951 \def\email##1##2{%
1952 \def\affiliation##1##2{%
1953 \def\@tempa{##2}\ifx\@tempa\@empty\else
1954 \ifx\@currentaffiliations\@empty
1955 \gdef\@currentaffiliations{%
1956 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1957 \setkeys{@ACM@affiliation@}{##1}%
1958 \@affiliationfont##2}%
1959 \else
1960 \g@addto@macro{\@currentaffiliations}{\and
1961 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
1962 \setkeys{@ACM@affiliation@}{##1}##2}%
1963 \fi
1964 \fi
1965 \global\let\and\@typeset@author@line}%
1966 \global\setbox\mktitle@bx=\vbox{\noindent\box\mktitle@bx\par\medskip
1967 \noindent\addresses\@typeset@author@line
1968 \par\medskip}%
1969 }

```

`\mkauthors@ii` The `\mkauthors@ii` command was the version used in acmtog. It is no longer necessary.

`\author@bx` The box to put an individual author in
1970 `\newbox\author@bx`

`\author@bx@wd` The width of the author box
1971 `\newdimen\author@bx@wd`

`\author@bx@sep` The separation between author boxes
1972 `\newskip\author@bx@sep`
1973 `\author@bx@sep=1pc\relax`

`\@typeset@author@bx` Typesetting the box with authors. Note that in sigchi-a the box is not centered.
1974 `\def\@typeset@author@bx{\bgroup\hsize=\author@bx@wd\def\and{\par}%`
1975 `\global\setbox\author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi`
1976 `\@authorfont\@currentauthors\par\@affiliationfont`
1977 `\@currentaffiliation}\egroup`
1978 `\box\author@bx\hspace{\author@bx@sep}%`
1979 `\gdef\@currentauthors{}}%`
1980 `\gdef\@currentaffiliation{}}`

`\mkauthors@iii` The sigconf version. Here we use a centered design with each author in a separate box.
1981 `\def\mkauthors@iii{%`
First, we need to determine the design of the author strip. The boxes are separated by `\author@bx@sep` plus two `\author@bx@sep` margins. This means that each box must

be of width $(\text{\textwidth} - \text{\author@bx@sep})/N - \text{\author@bx@sep}$, where N is the number of boxes per row.

```

1982 \author@bx@wd=\textwidth\relax
1983 \advance\author@bx@wd by -\author@bx@sep\relax
1984 \ifnum\@ACM@authorsperrow>0\relax
1985   \divide\author@bx@wd by \@ACM@authorsperrow\relax
1986 \else
1987   \ifcase\num@authorgroups
1988   \relax % 0?
1989   \or % 1=one author per row
1990   \or % 2=two authors per row
1991     \divide\author@bx@wd by \num@authorgroups\relax
1992   \or % 3=three authors per row
1993     \divide\author@bx@wd by \num@authorgroups\relax
1994   \or % 4=two authors per row (!)
1995     \divide\author@bx@wd by 2\relax
1996   \else % three authors per row
1997     \divide\author@bx@wd by 3\relax
1998   \fi
1999 \fi
2000 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

2001 \gdef\@currentauthors{}%
2002 \gdef\@currentaffiliation{}%
2003 \def\@author##1{\ifx\@currentauthors\@empty
2004   \gdef\@currentauthors{\par##1}%
2005 \else
2006   \g@addto@macro\@currentauthors{\par##1}%
2007 \fi
2008 \gdef\and{}}%
2009 \def\@email##1##2{\ifx\@currentaffiliation\@empty
2010   \gdef\@currentaffiliation{\nolinkurl{##2}}%
2011 \else
2012   \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2013 \fi}%
2014 \def\@affiliation##1##2{\ifx\@currentaffiliation\@empty
2015   \gdef\@currentaffiliation{%
2016     \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2017     \setkeys{@ACM@affiliation@}{##1}##2}%
2018 \else
2019   \g@addto@macro\@currentaffiliation{\par
2020     \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2021     \setkeys{@ACM@affiliation@}{##1}##2}%
2022 \fi
2023 \global\let\and\@typeset@author@bx
2024 }%

```

Actual typesetting is done by the \and macro:

```

2025 \hspace=\textwidth

```

```

2026 \global\setbox\mktitle@bx=\vbox{\noindent
2027 \box\mktitle@bx\par\medskip\leavevmode
2028 \lineskip=1pc\relax\centering\hspace*{-1em}%
2029 \addresses\let\and\@typeset@author@bx\and\par\bigskip}}

```

\@mkauthors@iv The sigchi-a version. We put authors in the main text with no more than 2 authors per line, unless overridden.

```
2030 \def\@mkauthors@iv{%
```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```

2031 \author@bx@wd=\columnwidth\relax
2032 \advance\author@bx@wd by -\author@bx@sep\relax
2033 \ifnum\@ACM@authorsperrow>0\relax
2034 \divide\author@bx@wd by \@ACM@authorsperrow\relax
2035 \else
2036 \ifcase\@num@authorgroups
2037 \relax % 0?
2038 \or % 1=one author per row
2039 \else % 2=two authors per row
2040 \divide\author@bx@wd by 2\relax
2041 \fi
2042 \fi
2043 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

2044 \gdef\@currentauthors{}%
2045 \gdef\@currentaffiliation{}%
2046 \def\@author##1{\ifx\@currentauthors\@empty
2047 \gdef\@currentauthors{\par##1}%
2048 \else
2049 \g@addto@macro\@currentauthors{\par##1}%
2050 \fi
2051 \gdef\and{}}%
2052 \def\@email##1##2{\ifx\@currentaffiliation\@empty
2053 \gdef\@currentaffiliation{\nolinkurl{##2}}%
2054 \else
2055 \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2056 \fi}%
2057 \def\@affiliation##1##2{\ifx\@currentaffiliation\@empty
2058 \gdef\@currentaffiliation%
2059 \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2060 \setkeys{@ACM@affiliation@}{##1}##2}%
2061 \else
2062 \g@addto@macro\@currentaffiliation{\par
2063 \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2064 \setkeys{@ACM@affiliation@}{##1}##2}%
2065 \fi

```

```
2066 \global\let\and\@typeset@author@bx}%
2067 %
```

Actual typesetting is done by the \and macro

```
2068 \bgroup\hsize=\columnwidth
2069 \par\raggedright\leftskip=\z@
2070 \lineskip=1pc\noindent
2071 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}
```

\@mkauthorsaddresses Typesetting authors' addresses in the footnote style

```
2072 \def\@mkauthorsaddresses{%
2073 \ifnum\num@authors>1\relax
2074 Authors' \else Author's \fi
2075 \ifnum\num@authorgroups>1\relax
2076 addresses: \else address: \fi
2077 \bgroup
2078 \def\streetaddress##1{\unskip\@addpunct, ##1}%
2079 \def\postcode##1{\unskip\@addpunct, ##1}%
2080 \def\position##1{\unskip\ignorespaces}%
2081 \def\institution##1{\unskip\@addpunct, ##1}%
2082 \def\city##1{\unskip\@addpunct, ##1}%
2083 \def\state##1{\unskip\@addpunct, ##1}%
2084 \renewcommand\department[2][0]{\unskip\@addpunct, ##2}%
2085 \def\country##1{\unskip\@addpunct, ##1}%
2086 \def\and{\unskip\@addpunct; }%
2087 \def\@author##1{##1}%
2088 \def\email##1##2{\unskip\@addpunct, \nolinkurl{##2}}%
2089 \addresses
2090 \egroup}
```

\@setaddresses This is an amsart macro that we do not need.

```
2091 \def\@setaddresses{}
```

\@authornotemark Adding a footnote mark to authors. This version adds a "normal" footnote mark.

```
2092 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}
```

\@@authornotemark Adding a footnote mark to authors with a given number

```
2093 \def\@@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}
```

\@mkteasers Typesetting the teasers

```
2094 \def\@mkteasers{%
2095 \ifx\@teaserfigures\@empty\else
2096 \def\@teaser##1{\par\bigskip\bgroup
2097 \captionsetup{type=figure}##1\egroup\par}
2098 \global\setbox\mkttitle@bx=\vbox{\noindent\box\mkttitle@bx\par
2099 \noindent\@teaserfigures\par\medskip}%
2100 \fi}
```


`\@mkabstract` Typesetting the abstract

```
2101 \def\@mkabstract{\bgroup
2102   \ifx\@abstract\@empty\else
2103   {\phantomsection\addcontentsline{toc}{section}{Abstract}%
2104     \if@ACM@journal
2105       \everypar{\setbox\z@\lastbox\everypar{}}\small
2106     \else
2107       \section*{Abstract}%
2108     \fi
2109   \ignorespaces\@abstract\par}%
2110 \fi\egroup}
```

`\@mkbibcitation` Print the bibcitation format

```
2111 \def\@mkbibcitation{\bgroup
2112   \def\@pages@word{\ifnum\getrefnumber{TotPages}=1\relax page\else pages\fi}%
2113   \def\footnotemark{}%
2114   \def\@unskip{\ignorespaces}%
2115   \def\footnote{\ClassError{\@classname}{Please do not use footnotes
2116     inside a \string\title{} or \string\author{} command! Use
2117     \string\titlenote{} or \string\authornote{} instead!}}%
2118   \def\@article@string{\ifx\@acmArticle\@empty{\ } \else,
2119     Article~\@acmArticle\ \fi}%
2120   \par\medskip\small\noindent{\bfseries ACM Reference Format:}\par\nobreak
2121   \noindent\authors. \@acmYear. \@title
2122   \ifx\@subtitle\@empty. \else: \@subtitle. \fi
2123   \if@ACM@journal
2124     \textit{\@journalNameShort}
2125     \@acmVolume, \@acmNumber \@article@string (\@acmPubDate),
2126     \ref{TotPages}~\@pages@word.
2127   \else
2128     In \textit{\@acmBooktitle}%
2129     \ifx\@acmEditors\@empty\textit{.}\else
2130       \andify\@acmEditors\textit{, }\@acmEditors~\@editorsAbbrev.%
2131     \fi\
2132     ACM, New York, NY, USA%
2133     \@article@string\unskip, \ref{TotPages}~\@pages@word.
2134   \fi
2135   \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2136 \par\egroup}
```

`\@printendtopmatter` End the top matter

```
2137 \def\@printendtopmatter{\par\bigskip}
```

`\@setthanks` We redefine `\setthanks` using `\long`

```
2138 \def\@setthanks{\long\def\thanks##1{\par##1\@addpunct.}\thankses}
```

`\@setauthorsaddresses`

```
2139 \def\@setauthorsaddresses{\@authorsaddresses\unskip\@addpunct.}
```

3.15 Headers and Footers

We use fancyhdr for our headers and footers:

```
2140 \RequirePackage{fancyhdr}
```

`\ACM@linecount@bx` This is the box displayed in review mode

```
2141 \if@ACM@review
2142   \newsavebox{\ACM@linecount@bx}
2143   \newlength\ACM@linecount@bxht
2144   \newcount\ACM@linecount
2145   \ACM@linecount\@ne\relax
2146   \def\ACM@mk@linecount{%
2147     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{%
2148       \setlength{\ACM@linecount@bxht}{0pt}%
2149       \loop{\color{red}\scriptsize\the\ACM@linecount}\@
2150         \global\advance\ACM@linecount by \@ne
2151         \addtolength{\ACM@linecount@bxht}{\baselineskip}%
2152         \ifdim\ACM@linecount@bxht<\textheight\repeat
2153         {\color{red}\scriptsize\the\ACM@linecount}\hfill
2154         \global\advance\ACM@linecount by \@ne}}
2155 \fi
```

`\ACM@linecountL` How to display the box on the left

```
2156 \def\ACM@linecountL{%
2157   \if@ACM@review
2158     \ACM@mk@linecount
2159     \begin{picture}(0,0)%
2160       \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2161     \end{picture}%
2162   \fi}
```

`\ACM@linecountR` How to display the box on the right

```
2163 \def\ACM@linecountR{%
2164   \if@ACM@review
2165     \ACM@mk@linecount
2166     \begin{picture}(0,0)%
2167       \put(20,-22){\usebox{\ACM@linecount@bx}}%
2168     \end{picture}%
2169   \fi}
```

`\ACM@timestamp` The timestamp system

```
2170 \if@ACM@timestamp
2171   % Subtracting 30 from \time gives us the effect of rounding down despite
2172   % \numexpr rounding to nearest
2173   \newcounter{ACM@time@hours}
2174   \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2175   \newcounter{ACM@time@minutes}
2176   \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2177   \newcommand\ACM@timestamp{%
```

```

2178 \footnotesize%
2179 \ifx\@acmSubmissionID\@empty\relax\else
2180 Submission ID: \@acmSubmissionID.{ }%
2181 \fi
2182 \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2183 \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{. }%
2184 Page \thepage\ of \@startPage--\pageref*{TotPages}.%
2185 }
2186 \fi

\@shortauthors Even if the author redefined \@shortauthors, we do not print it in the headers when in
anonymous mode:
2187 \def\@shortauthors{\if@ACM@anonymous Anon.\else\shortauthors\fi}

\@headfootfont The font to typeset header and footer text.
2188 \def\@headfootfont{\sffamily}

standardpagestyle The page style for all pages but the first one
2189 \fancypagestyle{standardpagestyle}{%
2190 \fancyhf{}%
2191 \renewcommand{\headrulewidth}{\z@}%
2192 \renewcommand{\footrulewidth}{\z@}%
2193 \ifcase\ACM@format@nr
2194 \relax % manuscript
2195 \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2196 \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2197 \fancyhead[RE]{\@shortauthors}%
2198 \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2199 \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}%
2200 \or % acmsmall
2201 \fancyhead[LE]{\ACM@linecountL\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2202 \fancyhead[RO]{\@headfootfont\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2203 \fancyhead[RE]{\@headfootfont\@shortauthors}%
2204 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2205 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2206 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2207 \or % acmlarge
2208 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2209 \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2210 \fancyhead[LO]{\ACM@linecountL}%
2211 \fancyhead[RO]{\@headfootfont
2212 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi}%
2213 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2214 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2215 \or % acmtog
2216 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2217 \@acmArticle\if@ACM@printfolios:\thepage\fi\quad\textbullet\quad\@shortauthors}%
2218 \fancyhead[LO]{\ACM@linecountL}%
2219 \fancyhead[RE]{\ACM@linecountR}%

```

```

2220 \fancyhead[RO]{\@headfootfont
2221 \shorttitle\quad\textbullet\quad\@acmArticle\if@ACM@printfolios:\thepage\fi\ACM@linecountR}%
2222 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2223 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2224 \else % Proceedings
2225 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2226 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2227 \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2228 \fancyhead[LE]{\ACM@linecountL\@headfootfont\acmConference@shortname,
2229 \acmConference@date, \acmConference@venue}%
2230 \fancyhead[RO]{\@headfootfont\acmConference@shortname,
2231 \acmConference@date, \acmConference@venue\ACM@linecountR}%
2232 \fi
2233 \if@ACM@sigchiamode
2234 \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
2235 \fi
2236 \if@ACM@timestamp
2237 \fancyfoot[LO,RE]{\ACM@timestamp}
2238 \fi
2239 }
2240 \pagestyle{standardpagestyle}

\@folio@wd Folio blob width, height, offsets and max number
\@folio@ht
\@folio@voffset
\@folio@max
2241 \newdimen\@folio@wd
2242 \@folio@wd=\z@
2243 \newdimen\@folio@ht
2244 \@folio@ht=\z@
2245 \newdimen\@folio@voffset
2246 \@folio@voffset=\z@
2247 \def\@folio@max{1}
2248 \ifcase\ACM@format@nr
2249 \relax % manuscript
2250 \or % acmsmall
2251 \@folio@wd=45.75pt\relax
2252 \@folio@ht=1.25in\relax
2253 \@folio@voffset=.2in\relax
2254 \def\@folio@max{8}
2255 \or % acmlarge
2256 \@folio@wd=43.25pt\relax
2257 \@folio@ht=79pt\relax
2258 \@folio@voffset=.55in\relax
2259 \def\@folio@max{10}
2260 \fi

\@folioblob The macro to typeset the folio blob.
2261 \def\@folioblob{\@tempcnta=0\@acmArticleSeq\relax
2262 \ifnum\@tempcnta=0\relax\else
First, we calculate \@acmArticleSeq modulo \@folio@max
2263 \loop

```

```

2264 \ifnum\@tempcnta>\@folio@max\relax
2265 \advance\@tempcnta by - \@folio@max
2266 \repeat
2267 \advance\@tempcnta by -1\relax
2268 \@tempdima=\@folio@ht\relax
2269 \multiply\@tempdima by \the\@tempcnta\relax
2270 \advance\@tempdima by -\@folio@voffset\relax
2271 \begin{picture}(0,0)
2272 \makebox[\z@]{\raisebox{-\@tempdima}{%
2273 \rlap{%
2274 \raisebox{-0.45\@folio@ht}[\z@][\z@]{%
2275 \rule{\@folio@wd}{\@folio@ht}}}%
2276 \parbox{\@folio@wd}{%
2277 \centering
2278 \textcolor{white}{\LARGE\sfamily\bfseries\@acmArticle}}}}
2279 \end{picture}\fi}
2280

```

firstpagestyle The page style for the first page only.

```

2281 \fancypagestyle{firstpagestyle}{%
2282 \fancyhf{}%
2283 \renewcommand{\headrulewidth}{\z@}%
2284 \renewcommand{\footrulewidth}{\z@}%
2285 \ifcase\ACM@format@nr
2286 \relax % manuscript
2287 \fancyhead[L]{\ACM@linecountL}%
2288 \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
2289 \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
2290 \or % acmsmall
2291 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2292 \@acmNumber, Article \@acmArticle. Publication date:
2293 \@acmPubDate.}%
2294 \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2295 \fancyhead[LO]{\ACM@linecountL}%
2296 \fancyhead[RO]{\@folioblob}%
2297 \fancyheadoffset[RO,LE]{0.6\@folio@wd}%
2298 \or % acmlarge
2299 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2300 \@acmNumber, Article \@acmArticle. Publication date:
2301 \@acmPubDate.}%
2302 \fancyhead[RO]{\@folioblob}%
2303 \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2304 \fancyhead[LO]{\ACM@linecountL}%
2305 \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
2306 \or % acmtog
2307 \fancyfoot[RO,LE]{\footnotesize \@journalName, Vol. \@acmVolume, No.
2308 \@acmNumber, Article \@acmArticle. Publication date:
2309 \@acmPubDate.}%
2310 \fancyhead[L]{\ACM@linecountL}%

```

```

2311 \fancyhead[R]{\ACM@linecountR}%
2312 \else % Conference proceedings
2313 \fancyhead[L]{\ACM@linecountL}%
2314 \fancyhead[R]{\ACM@linecountR}%
2315 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2316 \fi
2317 \if@ACM@timestamp
2318 \ifnum\ACM@format@nr=0\relax % Manuscript
2319 \fancyfoot[LO,RE]{\ACM@timestamp\quad
2320 \footnotesize Manuscript submitted to ACM}
2321 \else
2322 \fancyfoot[LO,RE]{\ACM@timestamp}
2323 \fi
2324 \fi
2325 }

```

\ACM@restore@pagestyle The following code by Ross Moore protects against changes by the totpages package:

```

2326 \let\ACM@ps@plain\ps@plain
2327 \let\ACM@ps@myheadings\ps@myheadings
2328 \let\ACM@ps@headings\ps@headings
2329 \def\ACM@restore@pagestyle{%
2330 \let\ps@plain\ACM@ps@plain
2331 \let\ps@myheadings\ACM@ps@myheadings
2332 \let\ps@headings\ACM@ps@headings}
2333 \AtBeginDocument{\ACM@restore@pagestyle}

```

3.16 Sectioning

Sectioning is different for different levels

```

2334 \renewcommand\section{\@startsection{section}{1}{\z@}%
2335 {-0.75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2336 {0.25\baselineskip}%
2337 {\@secfont}}
2338 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
2339 {-0.75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2340 {0.25\baselineskip}%
2341 {\@subsecfont}}
2342 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{10pt}%
2343 {-0.5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2344 {-3.5\p@}%
2345 {\@subsubsecfont\@adddotafter}}
2346 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
2347 {-0.5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2348 {-3.5\p@}%
2349 {\@parfont\@adddotafter}}
2350 \renewcommand\part{\@startsection{part}{9}{\z@}%
2351 {-10\p@ \@plus -4\p@ \@minus -2\p@}%
2352 {4\p@}%
2353 {\@parfont}}

```

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase
2354 \def\section@raggedright{\@rightskip\@flushglue
2355 \rightskip\@rightskip
2356 \leftskip\z@skip
2357 \parindent\z@}

\@secfont Fonts for sections etc. are different for different formats.
\@subsecfont 2358 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
\@subsubsecfont 2359 \def\@subsubsecfont{\sffamily\bfseries\section@raggedright}
\@parfont 2360 \def\@subsubsecfont{\sffamily\itshape}
2361 \def\@parfont{\itshape}
2362 \setcounter{secnumdepth}{3}
2363 \ifcase\ACM@format@nr
2364 \or % manuscript
2365 \or % acmsmall
2366 \or % acmlarge
2367 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2368 \def\@subsecfont{\sffamily\large\section@raggedright}
2369 \or % acmtog
2370 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2371 \def\@subsecfont{\sffamily\large\section@raggedright}
2372 \or % sigconf
2373 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
2374 \def\@subsecfont{\bfseries\Large\section@raggedright}
2375 \or % siggraph
2376 \def\@secfont{\sffamily\bfseries\Large\section@raggedright\MakeTextUppercase}
2377 \def\@subsecfont{\sffamily\bfseries\Large\section@raggedright}
2378 \or % sigplan
2379 \def\@secfont{\bfseries\Large\section@raggedright}
2380 \def\@subsecfont{\bfseries\section@raggedright}
2381 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
2382 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2383 {.25\baselineskip}%
2384 {\@subsubsecfont}}
2385 \def\@subsubsecfont{\bfseries\section@raggedright}
2386 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
2387 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2388 {-3.5\p@}%
2389 {\@parfont\@addspaceafter}}
2390 \def\@parfont{\bfseries\itshape}
2391 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\z@}%
2392 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2393 {-3.5\p@}%
2394 {\@subparfont\@addspaceafter}}
2395 \def\@subparfont{\itshape}
2396 \or % sigchi
2397 \setcounter{secnumdepth}{1}
2398 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2399 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2400 \or % sigchi-a

```

```

2401 \setcounter{secnumdepth}{0}
2402 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2403 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2404 \fi

```

`\@adddotafter` Add punctuation after a sectioning command

```
2405 \def\@adddotafter#1{#1\@addpunct{.}}
```

`\@addspaceafter` Add space after a sectioning command

```
2406 \def\@addspaceafter#1{#1\@addpunct{\enspace}}
```

3.17 TOC lists

`\@dotsep` Related to the `\tableofcontents` are all the horizontal fillers. Base \TeX defines `\@dottedtocline`, which we should not disable. Yet, this command expects `\@dotsep` to be defined but leaves this to the class implementation. Since `amsart` does not provide this, we copy the standard variant from `article` here.

```
2407 \providecommand*\@dotsep{4.5}
```

3.18 Theorems

`\@acmplainbodyfont` The font to typeset the body of the `acmplain` theorem style.

```
2408 \def\@acmplainbodyfont{\itshape}
```

`\@acmplainindent` The amount to indent the `acmplain` theorem style.

```
2409 \def\@acmplainindent{\parindent}
```

`\@acmplainheadfont` The font to typeset the head of the `acmplain` theorem style.

```
2410 \def\@acmplainheadfont{\scshape}
```

`\@acmplainnotefont` The font to typeset the note of the `acmplain` theorem style.

```
2411 \def\@acmplainnotefont{\@empty}
```

Customization of the `acmplain` theorem style:

```

2412 \ifcase\ACM@format@nr
2413 \relax % manuscript
2414 \or % acsmall
2415 \or % acmlarge
2416 \or % acmtog
2417 \or % sigconf
2418 \or % siggraph
2419 \or % sigplan
2420 \def\@acmplainbodyfont{\itshape}
2421 \def\@acmplainindent{\z@}
2422 \def\@acmplainheadfont{\bfseries}
2423 \def\@acmplainnotefont{\normalfont}
2424 \or % sigchi
2425 \or % sigchi-a
2426 \fi

```


acmplain The acmplain theorem style

```
2427 \newtheoremstyle{acmplain}%
2428 { .5\baselineskip\@plus.2\baselineskip
2429 \@minus.2\baselineskip}% space above
2430 { .5\baselineskip\@plus.2\baselineskip
2431 \@minus.2\baselineskip}% space below
2432 {\@acmplainbodyfont}% body font
2433 {\@acmplainindent}% indent amount
2434 {\@acmplainheadfont}% head font
2435 { .}% punctuation after head
2436 { .5em}% spacing after head
2437 {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmplainnotefont(#3)}}}% head spec
```

\@acmdefinitionbodyfont The font to typeset the body of the acmdefinition theorem style.

```
2438 \def\@acmdefinitionbodyfont{\normalfont}
```

\@acmdefinitionindent The amount to indent the acmdefinition theorem style.

```
2439 \def\@acmdefinitionindent{\parindent}
```

\@acmdefinitionheadfont The font to typeset the head of the acmdefinition theorem style.

```
2440 \def\@acmdefinitionheadfont{\itshape}
```

\@acmdefinitionnotefont The font to typeset the note of the acmdefinition theorem style.

```
2441 \def\@acmdefinitionnotefont{\@empty}
```

Customization of the acmdefinition theorem style:

```
2442 \ifcase\ACM@format@nr
2443 \relax % manuscript
2444 \or % acmsmall
2445 \or % acmlarge
2446 \or % acmtog
2447 \or % sigconf
2448 \or % siggraph
2449 \or % sigplan
2450 \def\@acmdefinitionbodyfont{\normalfont}
2451 \def\@acmdefinitionindent{\z@}
2452 \def\@acmdefinitionheadfont{\bfseries}
2453 \def\@acmdefinitionnotefont{\normalfont}
2454 \or % sigchi
2455 \or % sigchi-a
2456 \fi
```

acmdefinition The acmdefinition theorem style

```
2457 \newtheoremstyle{acmdefinition}%
2458 { .5\baselineskip\@plus.2\baselineskip
2459 \@minus.2\baselineskip}% space above
2460 { .5\baselineskip\@plus.2\baselineskip
2461 \@minus.2\baselineskip}% space below
2462 {\@acmdefinitionbodyfont}% body font
```

```

2463 {\@acmdefinitionindent}% indent amount
2464 {\@acmdefinitionheadfont}% head font
2465 {.%} punctuation after head
2466 {.5em}% spacing after head
2467 {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmdefinitionnotefont(#3)}}}% head spec

```

Make acmplain the default theorem style.

```
2468 \theoremstyle{acmplain}
```

Delay defining the theorem environments until after other packages have been loaded. In particular, the `cleveref` package must be loaded before the theorem environments are defined in order to show the correct environment name (see <https://github.com/borisveytsman/acmart/issues/138>). The `acmthm` option is used to suppress the definition of any theorem environments. Also, to avoid obscure errors arising from these environment definitions conflicting with environments defined by the user or by user-loaded packages, we only define environments that have not yet been defined.

```

2469 \AtEndPreamble{%
2470   \if@ACM@acmthm
2471     \theoremstyle{acmplain}
2472     \@ifundefined{theorem}{%
2473       \newtheorem{theorem}{Theorem}[section]
2474     }{}
2475     \@ifundefined{conjecture}{%
2476       \newtheorem{conjecture}[theorem]{Conjecture}
2477     }{}
2478     \@ifundefined{proposition}{%
2479       \newtheorem{proposition}[theorem]{Proposition}
2480     }{}
2481     \@ifundefined{lemma}{%
2482       \newtheorem{lemma}[theorem]{Lemma}
2483     }{}
2484     \@ifundefined{corollary}{%
2485       \newtheorem{corollary}[theorem]{Corollary}
2486     }{}
2487     \theoremstyle{acmdefinition}
2488     \@ifundefined{example}{%
2489       \newtheorem{example}[theorem]{Example}
2490     }{}
2491     \@ifundefined{definition}{%
2492       \newtheorem{definition}[theorem]{Definition}
2493     }{}
2494     \fi
2495     \theoremstyle{acmplain}
2496 }

```

`\@proofnamefont` The font to typeset the proof name.

```
2497 \def\@proofnamefont{\scshape}
```

```

\@proofindent Whether or not to indent proofs.
2498 \def\@proofindent{\indent}

Customization of the proof environment.
2499 \ifcase\ACM@format@nr
2500 \relax % manuscript
2501 \or % acmsmall
2502 \or % acmlarge
2503 \or % acmtog
2504 \or % sigconf
2505 \or % siggraph
2506 \or % sigplan
2507 \def\@proofnamefont{\itshape}
2508 \def\@proofindent{\noindent}
2509 \or % sigchi
2510 \or % sigchi-a
2511 \fi

proof We want some customization of the proof environment.
2512 \renewenvironment{proof}[1][\proofname]{\par
2513 \pushQED{\qed}%
2514 \normalfont \topsep6\p@\@plus6\p@\relax
2515 \trivlist
2516 \item[\@proofindent\hskip\labelsep
2517 {\@proofnamefont #1\@addpunct{.}}]\ignorespaces
2518 }{%
2519 \popQED\endtrivlist\@endpfalse
2520 }

3.19 Acknowledgments

\acks This is a comment-like structure
2521 \specialcomment{acks}{%
2522 \begingroup
2523 \section*{Acknowledgments}
2524 \phantomsection\addcontentsline{toc}{section}{Acknowledgments}
2525 }{%
2526 \endgroup
2527 }

\grantsponsor We just typeset the name of the sponsor
2528 \def\grantsponsor#1#2#3{#2}

\grantnum
2529 \newcommand\grantnum[3][]{#3%
2530 \def\@tempa{#1}\ifx\@tempa\@empty\else\space(\url{#1})\fi}

```

3.20 Conditional typesetting

We use the comment package for conditional typesetting:

```
2531 \AtEndPreamble{%
2532 \if@ACM@screen
2533   \includecomment{screenonly}
2534   \excludecomment{printonly}
2535 \else
2536   \excludecomment{screenonly}
2537   \includecomment{printonly}
2538 \fi
2539 \if@ACM@anonymous
2540   \excludecomment{anonsuppress}
2541   \excludecomment{acks}
2542 \else
2543   \includecomment{anonsuppress}
2544 \fi}
```

3.21 Additional bibliography commands

`\showeprint` The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word 'arxiv' (see <http://arxiv.org/hypertex/bibstyles/>).

```
2545 \newcommand\showeprint[2][arxiv]{%
2546   \def\@tempa{#1}%
2547   \ifx\@tempa\@empty\def\@tempa{arxiv}\fi
2548   \def\@tempb{arxiv}%
2549   \ifx\@tempa\@tempb
2550     arXiv:\href{http://arxiv.org/abs/#2}{#2}\else arXiv:#2%
2551   \fi}
```

3.22 End of Class

```
2552 \normalsize\normalfont\frenchspacing
2553 </class>
```

References

- [1] UK T_EX Users Group. UK list of T_EX frequently asked questions. <http://www.tex.ac.uk>, 2016.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Christophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [4] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [5] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [6] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [7] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [8] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [9] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomencl>.
- [10] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.25*, June 2016. <http://www.ctan.org/pkg/subcaption>.
- [11] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

Change History

| | | | | | |
|-------|---|----|-------|---|----|
| 1.48 | General: Added prologue option to xcolor | 40 | v1.04 | \acmArticleSeq: Name change by Matthew Fluet | 58 |
| | Bib code cleanup (Zack Weinberg) | 29 | | \acmDOI: Name change by Matthew Fluet | 58 |
| | Documentation update (siggraph) | 29 | | \acmISBN: Name change by Matthew Fluet | 58 |
| 1.49 | General: New journal: DTRAP | 29 | | General: Updated bibliography for siggraph | 29 |
| v1.00 | General: First released version | 29 | v1.05 | General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib | 29 |
| v1.01 | General: Changed hyperref colors in screen mode (closes https://github.com/borisveytsman/acmart/issues/1) | 29 | | Patched \setcitestyle command; closes https://github.com/borisveytsman/acmart/issues/19 | 29 |
| | Defined ACM colors | 29 | v1.06 | \@ACM@badge@skip: Added macro | 58 |
| | Explicitly put draft option (closes https://github.com/borisveytsman/acmart/issues/4) | 32 | | \@ACM@badge@width: Added macro | 58 |
| | Set headheight to 1pc for all formats (closes https://github.com/borisveytsman/acmart/issues/5) | 29 | | \@ACM@title@width: Added macro | 58 |
| v1.02 | General: Added TOPS and TSC (closes https://github.com/borisveytsman/acmart/issues/12) | 29 | | \@mktitle@i: Added processing badges | 72 |
| | Documentation changes (closes https://github.com/borisveytsman/acmart/issues/13) | 29 | | Made generic | 72 |
| v1.03 | \@formatdoi: Added macro | 64 | | \@mktitle@ii: Now this macro is obsolete | 73 |
| | \if@ACM@authorversion: Added macro | 31 | | \@mktitle@iii: Added processing badges | 73 |
| | \maketitle: Added special case of authorversion | 67 | | Made more generic | 73 |
| | General: Added anonsuppress environment | 29 | | \@mktitle@iv: Made more generic | 74 |
| | Added authorversion option (closes https://github.com/borisveytsman/acmart/issues/9) | 29 | | \@printtopmatter: Added processing badges | 70 |
| | | | | \@subtitledfont: Added macro | 72 |
| | | | | \@titlefont: Added macro | 72 |
| | | | | \acmBadgeL: Added macro | 59 |
| | | | | \acmBadgeR: Added macro | 59 |
| | | | | \if@ACM@badge: Added macro | 58 |
| | | | v1.07 | \maketitle: Corrected a bug with abstract footnotes | 67 |
| | | | | Corrected a bug with permission and footnotes order | 67 |
| | | | v1.08 | General: SIGPLAN reformatting by Matthew Fluet | 29 |
| | | | | Typos corrected (Tobias Pape) | 29 |

| | | | | |
|-------|--|----|--|--|
| v1.09 | General: Revert SIGPLAN caption rules | 29 | Increased font size for ACM Large | 33 |
| v1.10 | \maketitle: Corrected a bug with doi in manuscript and author version, https://github.com/borisveytsman/acmart/issues/36 | 67 | Print bibliographic information by default for the proceedings | 60 |
| | General: Changes of ‘licensedothergov’ wording | 62 | standardpagestyle: Added headers for sigs | 83 |
| | standardpagestyle: Reversed folios location | 83 | Expanded headers for sigchi-a | 83 |
| v1.11 | General: Customization of ACM theorem styles and proof environment by Matthew Fluet | 29 | Suppressed folios if sig | 83 |
| v1.12 | \@marginfigure: Now centering by default | 45 | v1.14 | \bibstyle@acmauthoryear: Moved def of \bibstyle@acmauthoryear before use |
| | \@marginable: Now centering by default | 46 | | \bibstyle@acmnumeric: Moved def of \bibstyle@numeric before use |
| | \@parfont: Moved to \section@raggedright | 87 | | General: \citestyle updates (Matthew Fluet) |
| | \copyrightpermissionfootnoterule: Added macro | 42 | | Patched \citestyle |
| | \descriptionlabel: Redefined | 48 | v1.15 | \@ACM@addtoaddress: Added macro |
| | \footnoterule: Made shorter | 42 | | \@mkauthors@iii: New authors system |
| | \if@ACM@natbib@override: Added macro | 31 | | \@shortauthors: Introduced macro |
| | \if@ACM@newfonts: Added macro | 44 | | \@typeset@author@bx: Moved to separate macro |
| | \maketitle: Moved thankses to copyrightpermission box | 67 | | \acks: Added macro |
| | \section@raggedright: Introduced macro | 87 | | \affiliation: Added code for author groups |
| | General: Added graceful behavior when libertine fonts are absent | 44 | | \author: Added code for author groups |
| | Documentation updates | 29 | | \city: Added macro |
| v1.13 | \@empfootnotetext: Made minipage footnotes centered | 43 | | \country: Added macro |
| | \bibliographystyle: Redefined macro | 39 | | \department: Added macro |
| | \bibstyle@acmauthoryear: Added macro | 35 | | \grantnum: Added macro |
| | \bibstyle@acmnumeric: Added macro | 36 | | \grantsponsor: Added macro |
| | \if@ACM@printfolios: Added macro | 60 | | \if@insideauthorgroup: Introduced macro |
| | General: Font adjustments for acmsmall | 75 | | \institution: Added macro |
| | | | | \num@authorgroups: Renamed |
| | | | | \orcid: Introduced macro |
| | | | | \position: Added macro |
| | | | | \postcode: Added macro |
| | | | | \state: Added macro |
| | | | | \streetaddress: Added macro |
| | | | | standardpagestyle: Better handling of anonymous mode |
| | | | v1.16 | \@headfootfont: Added macro |
| | | | | General: Formatting header/footer (Matthew Fluet) |
| | | | | standardpagestyle: Customize header/footer text font |

| | | | |
|-------|---|-------|---|
| v1.17 | | v1.22 | |
| | <code>\@makefnmark</code> : Redefined 43 | | General: More bibliography changes for Aptara 29 |
| | <code>\@mkauthors</code> : TOG now uses the same authors block as other journals . . . 75 | v1.23 | General: Add PACMPL journal option 29 |
| | <code>\@mkauthors@ii</code> : Deleted 77 | v1.24 | General: Add IMWUT journal option 48 |
| | <code>\@mkbibcitation</code> : Added <code>\nobreak</code> Changed format for sigs 81 | v1.25 | General: Updated PACMPL 48 |
| | <code>\acmArticle</code> : The default is now numerical 57 | v1.26 | General: Corrected <code>\shortcite</code> bug . 29 |
| | <code>\acmMonth</code> : The default must be numerical. Closes #50. 58 | | Documentation typos fixed (thanks to Stephen Spencer) 29 |
| | <code>\acmNumber</code> : The default is now numerical 57 | v1.27 | <code>\if@ACM@printccs</code> : Typo corrected . 59 |
| | <code>\acmVolume</code> : The default is now numerical 57 | v1.28 | <code>\ccsdesc@parse</code> : Change from <code>\to</code> to <code>\textrightarrow</code> (Matteo Riondato) 61 |
| | <code>\acmYear</code> : The default is now numerical 58 | | General: Corrected option <code>natbib</code> behavior 36 |
| | <code>\description</code> : Decreased indent . . . 48 | | Got rid of warnings in pdf keywords 38 |
| | <code>\grantnum</code> : Added url 91 | v1.29 | |
| | <code>\grantsponsor</code> : Renamed 91 | | <code>\@mkabstract</code> : Removed spurious indentation (John Wickerson) . . . 81 |
| | <code>\if@ACM@printacmref</code> : Renamed from <code>\if@ACM@printbib</code> 60 | | <code>\ccsdesc@parse</code> : Add spacing after bullet and around <code>rightarrow</code> ; semicolon separators no longer in bold/italic (John Wickerson) 61 |
| | General: Slightly decreased margins for sigs 40 | | General: Increased head to 13pt 40 |
| | <code>standardpagestyle</code> : Added paper title to sigs 83 | | <code>standardpagestyle</code> : Corrected <code>printfolios</code> (Matthew Fluet) 83 |
| v1.18 | | v1.30 | |
| | <code>\@mkauthors@i</code> : Now we andify affiliations 76 | | <code>\department</code> : Added optional parameter 74 |
| | <code>\@typeset@author@line</code> : Added macro 76 | | General: Added <code>\frenchspacing</code> . . . 92 |
| | General: <code>natbib</code> is now the default for all formats 29 | | Bibtex style now recognizes <code>https://</code> in doi 29 |
| v1.19 | | | Switched to T1: looks like libertine has problems with <code>\l</code> in OT1 44 |
| | <code>\@mkabstract</code> : Include 'Abstract' in PDF bookmarks (Matthew Fluet) . . . 81 | | Updated IMWUT and PACMPL . . . 48 |
| | <code>\acks</code> : Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet) . . . 91 | v1.31 | |
| | General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet) 29 | | <code>\@additionalaffiliation</code> : Added macro 56 |
| | Include 'References' in PDF bookmarks (Matthew Fluet) 34 | | <code>\@mkbibcitation</code> : Disabled <code>linebreak</code> 81 |
| v1.20 | | | <code>\@startsection</code> : Added <code>\tochangmeasure</code> 36 |
| | <code>\@mkabstract</code> : Deleted spurious space 81 | | Redefined macro 38 |
| | General: Bug fixes for <code>bst</code> 29 | | <code>\@textbottom</code> : Redefined 43 |
| v1.21 | | | |
| | <code>\showeprint</code> : Added macro 92 | | |

| | | | |
|---|----|--|----|
| <code>\acmMonth</code> : The default now is the current month (Matteo Riondato) . . . | 58 | <code>\position</code> : Added obeypunctuation code | 74 |
| <code>\acmYear</code> : The default now is the current year (Matteo Riondato) . . . | 58 | <code>\postcode</code> : Added obeypunctuation code | 74 |
| <code>\additionalaffiliation</code> : Added macro | 56 | <code>\state</code> : Added obeypunctuation code | 74 |
| <code>\l@section</code> : Redefined macro . . . | 38 | <code>\streetaddress</code> : Added obeypunctuation code | 74 |
| <code>\l@subsection</code> : Redefined macro . . . | 38 | General: Added acmart-preload-hook . . . | 29 |
| General: Documentation changes . . . | 29 | Added cmap and glyphtounicode . . . | 44 |
| v1.32 | | BibTeX comma before articleno bug corrected | 29 |
| <code>\@formatdoi</code> : New doi format | 64 | BibTeX crossref bug corrected . . . | 29 |
| General: Added POMACS journal option | 29 | BibTeX numpages bug corrected . . . | 29 |
| Format siggraph is now obsolete . . . | 29 | Documentation updates | 29 |
| v1.33 | | Moved <code>\citenam</code> definition for non-natbib bibliography, so a package may redefine it | 39 |
| <code>\@ACM@addtoaddress</code> : Added obeypunctuation code | 74 | Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann) . . . | 44 |
| <code>\@mkauthors@i</code> : Added obeypunctuation code | 76 | <code>firstpagestyle</code> : Added right linecount for two-column formats . . . | 85 |
| <code>\@mkauthors@iii</code> : Added obeypunctuation code | 77 | Added timestamp (Michael D. Adams) | 85 |
| <code>\@mkauthors@iv</code> : Added obeypunctuation code | 79 | <code>standardpagestyle</code> : Added right linecount for two-column formats . . . | 83 |
| <code>\@subtitlefont</code> : Added <code>\normalsize</code> | 72 | Added timestamp (Michael D. Adams) | 83 |
| <code>\ACM@linecountL</code> : Renamed macro . . . | 82 | v1.34 | |
| <code>\ACM@linecountR</code> : Added macro . . . | 82 | <code>\@mkbibcitation</code> : Deleted DOI from doi numbers | 81 |
| <code>\ACM@timestamp</code> : Added current page number | 82 | <code>\ACM@linecount@bx</code> : Rulers now are continuous | 82 |
| Added macro (Michael D. Adams) . . . | 82 | <code>\ACM@linecountL</code> : Rulers now are continuous | 82 |
| Added submission id | 82 | <code>\ACM@linecountR</code> : Rulers now are continuous | 82 |
| <code>\acmSubmissionID</code> : Added macro . . . | 58 | <code>\maketitle</code> : Added date to the bibstrip in conf proceedings | 67 |
| <code>\city</code> : Added obeypunctuation code . . . | 74 | Deleted 'DOI' from doi numbers . . . | 67 |
| <code>\country</code> : Added obeypunctuation code | 74 | Rearranged bibstrip | 67 |
| <code>\department</code> : Added obeypunctuation code | 74 | The <code>\terms</code> command is now obsolete | 67 |
| <code>\if@ACM@affiliation@obeypunctuation</code> : Added macro | 56 | <code>\terms</code> : The <code>\terms</code> command now just produces a warning | 59 |
| <code>\if@ACM@authordraft</code> : Added macro . . . | 31 | v1.35 | |
| <code>\if@ACM@natbib@override</code> : Deleted macro | 31 | <code>\bibstyle@acmauthoryear</code> : Square brackets for author-year style | 35 |
| <code>\if@ACM@timestamp</code> : Added macro (Michael D. Adams) | 31 | General: BibTeX bug fixed: et al. | 29 |
| <code>\institution</code> : Added obeypunctuation code | 74 | | |
| <code>\maketitle</code> : Fixed the bug with figures on top and bottom of the title page, thanks to David Epstein . . . | 67 | | |

| | | | |
|---|--------|--|----|
| If the copyright is set to usgov or rightsretained, the price is suppressed | 62 | \country: Fixed bugs with extra spaces | 74 |
| v1.36 | | \l@section: Redefined macro . . . | 38 |
| \@ACM@authorsperrrow: Added macro | 60 | \postcode: We now do not print this even in SIG | 74 |
| \@mkauthors@iii: Added authorsperrrow override | 77 | \state: We now do not print this even in SIG | 74 |
| \@mkauthors@iv: Added authorsperrrow override | 79 | \streetaddress: We now do not print this even in SIG | 74 |
| \if@ACM@authordraft: Corrected typo, thanks to bargteil | 31 | General: Added ‘textcase’ package . . | 34 |
| General: Added PACMHCI journal options | 48 | Added heightrounded to geometry | 40 |
| Added the possibility to adjust number of author boxes per row in conference formats | 29 | Added new copyright version: licensedcagov | 29 |
| v1.37 | | Added package cleveref | 29 |
| \description: Reduce list indentation (Matthew Fluet) | 48 | Added Ross Moore code for glyphtounicode | 44 |
| \descriptionlabel: Reduce list indentation (Matthew Fluet) | 48 | Bibliography changes | 29 |
| \normalparindent: Set \normalparindent (Matthew Fluet) | 42 | v1.41 | |
| General: Reduce list indentation (Matthew Fluet) | 47 | General: Added new badges | 29 |
| Set \normalparindent; Reduce list indentation (Matthew Fluet) | 29 | v1.42 | |
| v1.38 | | General: Deleted ACM badges | 29 |
| General: Increase default font size for SIGPLAN | 29, 33 | v1.43 | |
| v1.39 | | \@startsection: Added \makeatletter | 38 |
| \@authornotemark: Added macro . . | 80 | \country: Added comma before country for journals | 74 |
| \authornotemark: Added macro . . . | 57 | v1.44 | |
| v1.40 | | \@acmBooktitle: Added macro | 54 |
| \@copyrightowner: Added new copyright version: licensedcagov . | 63 | \@acmEditors: Added macro | 54 |
| \@copyrightpermission: Added new copyright version: licensedcagov . | 64 | \@editorsAbbrev: Added macro . . . | 54 |
| \@mkauthors@i: Switched to MakeTextUppercase | 76 | \@folioblob: Suppress the blob if acmArticleSeq is empty | 84 |
| \@parfont: Switched to MakeTextUppercase | 87 | \@mkbibcitation: If the paper has just one page, use ‘page’ instead of ‘pages’ | 81 |
| \ACM@linecount@bx: Work around a bug in xcolor: looks like cmyk colors in boxes do not work | 82 | \ACM@restore@pagestyle: Added macro | 86 |
| \ccdesc@parse@finish: Added macro | 61 | \acmArticle: The default is now empty | 57 |
| \city: We now do not print this even in SIG | 74 | \acmArticleSeq: Now acmArticle might be empty | 58 |
| | | \acmBooktitle: Added macro | 54 |
| | | \editor: Added macro | 54 |
| | | \if@ACM@acmthm: Added macro | 30 |
| | | \maketitle: Empty DOI or ISBN are not printed (by Michael Ekstrand) | 67 |
| | | General: Added package refcount . . . | 29 |
| | | Deleted package cleveref | 29 |
| | | Put theorem defs in a separate style | 29 |

| | | | |
|-------|---------------------------------------|--------------------------------------|----|
| v1.45 | | General: Added etoolbox | 29 |
| | \@folioblob: Switched | Bst file bug fixes: label width is | |
| | \bfeseries\sffamily to | calculated correctly | 29 |
| | \sffamily\bfseries | Delayed hypersetup since journal | |
| | | options may change screen mode | 38 |
| | \@parfont: Switched | PACM now set screen to true | 48 |
| | \bfeseries\sffamily to | Restore theorem defs to class file . | 29 |
| | \sffamily\bfseries | | |
| | \@titlefont: Switched | v1.47 | |
| | \bfeseries\sffamily to | General: New journal: THRI | 29 |
| | \sffamily\bfseries | v1.48 | |
| v1.46 | | \@headfootfont: Deleted | |
| | \@mkauthorsaddresses: Introduced | unnecessary switch (Michael | |
| | macro | D. Adams) | 83 |
| | \@mkbibcitation: Added subtitle . . | \@mkabstract: Removed spurious | |
| | | indentation if abstract is followed | |
| | \@printendtopmatter: Made it | by an empty line | 81 |
| | \par\bigskip uniformly | \ACM@timestamp: Formatting change | |
| | | (Michael D. Adams) | 82 |
| | \@printtopmatter: Deleted rule . . . | \if@ACM@review: Review mode now | |
| | | switches on folios | 30 |
| | \@setauthorsaddresses: Introduced | \maketitle: Added acmart and | |
| | macro | version info to pdfcreator tag . . . | 67 |
| | \ACM@linecount@bx: Rearranged the | Added language and doctitle | |
| | code to get rid of spurious | attributes to PDF (Andreas | |
| | underfull messages (Benjamin | Reichinger) | 67 |
| | Byholm) | Suppressed empty DOI (Serguei | |
| | \author: Started counting authors . . | Mokhov) | 67 |
| | | General: \citeyear no longer | |
| | \authorsaddresses: Introduced | behaves like \citeyearpar | 39 |
| | macro | Code prettying (Michael D. Adams) | 29 |
| | \@country: Corrected spacing for | Initial support for Biblalex (Daniel | |
| | institution | Thomas) | 29 |
| | \if@ACM@acmthm: Modified | Misc entries in the bibliography no | |
| | description | longer produce a separate date . . | 29 |
| | \liningnums: Workaround for | Typos fixed (Jamie Davis) | 29 |
| | compatibility with fontspec | | |
| | \maketitle: Added authors' addresses | | |
| | Thankses go before authors' | | |
| | addresses | | |
| | \num@authors: Introduced macro . . | | |
| | | | |

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols | | |
|------------------------|--------------------------------|---|
| \\$ | 1615, 1619 | \@ACM@title@width .. 2223, 2293, 2301, 2309 |
| \@ | 1465, 1486, 1499 | <u>1195</u> , 1790, 1792, 1793, |
| \@authornotemark | .. | 1796, 1797, 1805, |
| | 1165, <u>2093</u> | 1819, 1821, 1822, 1830 |
| \@par | 317, 374 | \@DeclareACMFormat . |
| \@ACM@addtoaddress . | | ... 38, 39, 40, 41, |
| | <u>1853</u> , 1876, 1877, 1879 | 42, 43, 44, 45, 46, 47 |
| \@ACM@authorsperrow | <u>1236</u> , | \@M 317, 356, 374, 383 |
| | 1984, 1985, 2033, 2034 | \@abstract 1215, 2102, 2109 |
| \@ACM@badge@skip ... | <u>1196</u> , 1716, | \@acmArticle 1171, 1174, |
| | 1793, 1797, 1803, | 1614, 2118, 2119, |
| | 1812, 1822, 1828, 1837 | 2201, 2202, 2206, |
| \@ACM@badge@width .. | <u>1193</u> , 1715, | 2209, 2212, 2214, |
| | 1720, 1792, 1796, | 2217, 2221, 2223, |
| | 1802, 1814, 1821, | 2278, 2292, 2300, 2308 |
| | 1823, 1826, 1838, 1841 | \@acmArticleSeq 1173, 2261 |
| \@ACM@badgefalse ... | 1192 | \@acmBadgeL@image .. |
| \@ACM@badgetrue | 1198, 1203 | 1205, 1207, |
| \@ACM@commabox | | 1713, 1715, 1791, |
| | 1853, 1857, 1858 | 1800, 1802, 1824, 1826 |
| \@ACM@journalfalse . | | \@acmBadgeL@url . 1204, |
| | 149, 151, 153, 155, 157 | 1206, 1714, 1801, 1825 |
| \@ACM@journaltrue .. | | \@acmBadgeR@image .. |
| | 141, 143, 145, 147 | 1200, 1202, |
| \@ACM@labelwidth ... | | 1718, 1720, 1795, |
| | 712, 715, 723, 728, 754 | 1811, 1814, 1839, 1841 |
| \@ACM@manuscriptfalse | 136 | \@acmBadgeR@url . 1199, |
| \@ACM@manuscripttrue | 134 | 1201, 1719, 1813, 1840 |
| \@ACM@newfontsfalse | | \@acmBooktitle |
| | 617, 620, 623 | <u>1049</u> , 1605, 2128 |
| \@ACM@newfontstrue . | 614 | \@acmDOI .. 1189, 1607, |
| \@ACM@printfoliostrue | 68 | 1610, 1616, 1620, 2135 |
| \@ACM@reviewtrue ... | 110 | \@acmEditors <u>1054</u> , 1055, |
| \@ACM@screentrue ... | | 1056, 1059, 2129, 2130 |
| | 833, 862, 868, 874 | \@acmISBN 1187, 1618 |
| \@ACM@sigchiamodefalse | | \@acmMonth 1177, 1179, 1614 |
| | 138 | \@acmNumber |
| \@ACM@sigchiamodetrue | 158 | 1169, |
| \@ACM@timestamptrue | 109 | 2125, 2206, 2214, |
| | | 2223, 2292, 2300, 2308 |
| | | \@acmPrice 1183, 1615, 1619 |
| | | \@acmPubDate ... <u>1179</u> , |
| | | 2125, 2206, 2214, |
| | | \@acmSubmissionID .. |
| | | ... 1185, 2179, 2180 |
| | | \@acmVolume 1167, |
| | | 2125, 2205, 2213, |
| | | \@acmYear |
| | | |
| | | 1175, 1182, 1511, |
| | | 1521, 1526, 1614, 2121 |
| | | \@acmdefinitionbodyfont |
| | | ... <u>2438</u> , 2450, 2462 |
| | | \@acmdefinitionheadfont |
| | | ... <u>2440</u> , 2452, 2464 |
| | | \@acmdefinitionindent |
| | | ... <u>2439</u> , 2451, 2463 |
| | | \@acmdefinitionnotefont |
| | | ... <u>2441</u> , 2453, 2467 |
| | | \@acmownedfalse . 1315, |
| | | 1318, 1321, 1327, |
| | | 1331, 1334, 1337, |
| | | 1340, 1346, 1349, 1352 |
| | | \@acmownedtrue |
| | | |
| | | ... 1302, 1311, 1343 |
| | | \@acmplainbodyfont . |
| | | ... <u>2408</u> , 2420, 2432 |
| | | \@acmplainheadfont . |
| | | ... <u>2410</u> , 2422, 2434 |
| | | \@acmplainindent ... |
| | | ... <u>2409</u> , 2421, 2433 |
| | | \@acmplainnotefont . |
| | | ... <u>2411</u> , 2423, 2437 |
| | | \@adddotafter |
| | | |
| | | ... 2345, 2349, <u>2405</u> |
| | | \@additionalaffiliation |
| | | |
| | | 1116, <u>1117</u> |
| | | \@addpunct |
| | | 2078, |
| | | 2079, 2081, 2082, |
| | | 2083, 2084, 2085, |
| | | 2086, 2088, 2138, |
| | | 2139, 2405, 2406, 2517 |
| | | \@addspaceafter |
| | | |
| | | ... 2389, 2394, <u>2406</u> |

| | | |
|---|--|---|
| <code>\@affiliationfont</code> .. | <code>\@currbox</code> ... 693, 694, 695 | <code>\@folio@ht</code> |
| 1906, 1911, 1915, | <code>\@currentaffiliation</code> | 2241, 2268, 2274, 2275 |
| 1918, 1921, 1924, | 1977, 1980, 2002, | <code>\@folio@max</code> 2241, 2264, 2265 |
| 1927, 1930, 1958, 1976 | 2009, 2010, 2012, | <code>\@folio@voffset</code> 2241, 2270 |
| <code>\@afterheading</code> . 348, 1661 | 2014, 2015, 2019, | <code>\@folio@wd</code> 2241, |
| <code>\@afterindentfalse</code> . | 2045, 2052, 2053, | 2275, 2276, 2297, 2305 |
| 294, 1660 | 2055, 2057, 2058, 2062 | <code>\@folioblob</code> 2261, |
| <code>\@afterindenttrue</code> .. 292 | <code>\@currentaffiliations</code> | 2294, 2296, 2302, 2303 |
| <code>\@article@string</code> ... | 1935, | <code>\@footnotemark</code> . 396, 1544 |
| ... 2118, 2125, 2133 | 1936, 1937, 1939, | <code>\@footnotemark@nolink</code> |
| <code>\@author</code> | 1942, 1954, 1955, 1960 | 396, 1544 |
| 1077, 1080, 1085, | <code>\@currentauthors</code> ... | <code>\@footnotetext</code> |
| 1944, 2003, 2046, 2087 | 1933, 1934, | 397, 573, 1545 |
| <code>\@authorfont</code> | 1941, 1945, 1946, | <code>\@footnotetext@nolink</code> |
| 1905, 1910, 1914, | 1948, 1976, 1979, | 397, 1545 |
| 1917, 1920, 1923, | 2001, 2003, 2004, | <code>\@for</code> |
| 1926, 1929, 1946, 1976 | 2006, 2044, 2046, | <code>\@formatdoi</code> 1393, |
| <code>\@authornotemark</code> ... | 2047, 2049, 2092, 2093 | 1610, 1616, 1620, 2135 |
| ... 1157, 1163, 2092 | <code>\@currentlabel</code> . 577, 591 | <code>\@fps</code> |
| <code>\@authornotes</code> | <code>\@dblarg</code> | 680 |
| ... 1154, 1158, 1559 | <code>\@dblfloat</code> | <code>\@fpsadddfault</code> 680 |
| <code>\@authorsaddresses</code> . | <code>\@department</code> .. 1120, 1121 | <code>\@gobble</code> |
| ... 1133, 1567, 2139 | <code>\@dotsep</code> | 224, 268 |
| <code>\@auxout</code> | <code>\@editorsAbbrev</code> | <code>\@hangfrom</code> 316, 373 |
| 452 | ... 1053, 1058, 2130 | <code>\@headfootfont</code> |
| <code>\@begindocumenthook</code> 448 | <code>\@empty</code> 160, 307, 1044, | 2188, 2201, 2202, |
| <code>\@botnum</code> | 1055, 1075, 1090, | 2203, 2204, 2208, |
| 1549 | 1095, 1096, 1102, | 2211, 2216, 2220, |
| <code>\@citestyle</code> | 1254, 1255, 1261, | 2226, 2227, 2228, 2230 |
| 226 | 1268, 1273, 1563, | <code>\@ifnextchar</code> |
| <code>\@classname</code> | 1567, 1607, 1615, | 1120 |
| 25, | 1618, 1619, 1620, | <code>\@ifnotempty</code> |
| 27, 35, 51, 53, 54, | 1628, 1633, 1685, | 1531 |
| 59, 61, 62, 67, 70, | 1713, 1718, 1791, | <code>\@ifnum</code> |
| 71, 76, 78, 79, 84, | 1795, 1800, 1808, | 240, 242 |
| 86, 87, 92, 94, 95, | 1811, 1824, 1832, | <code>\@ifstar</code> |
| 100, 102, 103, 108, | 1839, 1849, 1935, | 301 |
| 112, 113, 124, 129, | 1945, 1953, 1954, | <code>\@ifundefined</code> |
| 182, 615, 618, 621, | 2003, 2009, 2014, | 2472, 2475, 2478, |
| 834, 863, 869, 875, | 2046, 2052, 2057, | 2481, 2484, 2488, 2491 |
| 1029, 1031, 1115, | 2095, 2118, 2122, | <code>\@iiiparbox</code> |
| 1210, 1220, 1222, | 2129, 2135, 2179, | 571 |
| 1223, 1226, 1228, | 2411, 2441, 2530, 2547 | <code>\@input</code> |
| 1229, 1232, 1234, | <code>\@endfloatbox</code> | 385 |
| 1235, 1237, 1238, 2115 | 679 | <code>\@insideauthorgroupfalse</code> |
| <code>\@clubpenalty</code> | <code>\@endpfalse</code> | 1068, 1110 |
| 362 | 2519 | <code>\@insideauthorgrouptrue</code> |
| <code>\@concepts</code> | <code>\@endwidfloatbox</code> 679, 687 | 1073 |
| 1273, | <code>\@finalstrut</code> ... 582, 595 | <code>\@journalCode</code> .. 760, |
| 1283, 1628, 1630, 1653 | <code>\@float</code> | 834, 863, 869, 875, 1029 |
| <code>\@copyrightowner</code> ... | <code>\@flushglue</code> | <code>\@journalCode@nr</code> ... |
| 1356, 1591 | 2354 | 760, 815, 1034 |
| <code>\@copyrightpermission</code> | <code>\@fnsymbol</code> | <code>\@journalName</code> 817, 821, |
| 1394, 1583 | 1546 | 825, 829, 836, 840, |
| <code>\@copyrighyear</code> . 1511, | | 844, 848, 852, 856, |
| 1521, 1525, 1591, 1593 | | 859, 865, 871, 877, |
| | | 881, 885, 888, 892, |
| | | 896, 898, 900, 902, |

| | | |
|---|---|---|
| 906, 910, 914, 918, | <code>\mkauthors</code> 1552, 1554, 1881 | <code>\@plus</code> .. 383, 391, 598, |
| 922, 926, 930, 934, | <code>\mkauthors@i</code> .. 1885, | 2335, 2339, 2343, |
| 938, 942, 946, 950, | 1887, 1889, 1891, 1940 | 2347, 2351, 2382, |
| 954, 958, 962, 965, | <code>\mkauthors@ii</code> 1970 | 2387, 2392, 2428, |
| 969, 972, 977, 981, | <code>\mkauthors@iii</code> . 1893, | 2430, 2458, 2460, 2514 |
| 985, 989, 993, 997, | 1895, 1897, 1899, 1981 | <code>\@printcopyrightfalse</code> |
| 1001, 1005, 1009, | <code>\mkauthors@iv</code> 1901, 2030 | 1314, 1326 |
| 1013, 1017, 1021, | <code>\mkauthorsaddresses</code> | <code>\@printcopyrighttrue</code> |
| 1025, 1035, 1036, | 1134, 2072 | 1298, 1310 |
| 1603, 2205, 2213, | <code>\mkbibcitation</code> 1646, 2111 | <code>\@printendtopmatter</code> |
| 2222, 2291, 2299, 2307 | <code>\mkteasers</code> ... 1552, 2094 | 1659, 2137 |
| <code>\@journalNameShort</code> . | <code>\mktitle</code> 1552, 1725 | <code>\@printpermissionfalse</code> |
| 818, | <code>\mktitle@i</code> 1728, | 1313 |
| 822, 826, 831, 837, | 1730, 1732, 1734, 1789 | <code>\@printpermissiontrue</code> |
| 841, 845, 849, 853, | <code>\mktitle@ii</code> 1817 | ... 1300, 1309, 1325 |
| 857, 860, 866, 872, | <code>\mktitle@iii</code> .. 1736, | <code>\@printtopmatter</code> ... |
| 878, 882, 886, 889, | 1738, 1740, 1742, 1817 | 1553, 1684 |
| 893, 903, 907, 911, | <code>\mktitle@iv</code> .. 1744, 1845 | <code>\@proofindent</code> |
| 915, 919, 923, 927, | <code>\@mpargs</code> 571 | ... 2498, 2508, 2516 |
| 931, 935, 939, 943, | <code>\@mparswitchfalse</code> .. 533 | <code>\@proofnamefont</code> |
| 947, 951, 955, 959, | <code>\@mpfootins</code> | ... 2497, 2507, 2517 |
| 966, 970, 973, 978, | 563, 564, 566, 586, 587 | <code>\@received</code> . 1252, 1255, |
| 982, 986, 990, 994, | <code>\@mpfootnotetext</code> ... 585 | 1256, 1258, 1261, |
| 998, 1002, 1006, | <code>\@ne</code> . 228, 232, 236, 238, | 1262, 1264, 1268, 1269 |
| 1010, 1014, 1018, | 438, 2145, 2150, 2154 | <code>\@rightskip</code> ... 2354, 2355 |
| 1022, 1026, 1036, 2124 | <code>\@nil</code> 247 | <code>\@saveabstract</code> 1214, 1215 |
| <code>\@keywords</code> | <code>\@nobreakfalse</code> . 350, 390 | <code>\@saveteaser</code> .. 1528, 1529 |
| 1212, 1633, 1639, 1654 | <code>\@noskipsecfalse</code> ... 354 | <code>\@secntformat</code> . 310, 367 |
| <code>\@latex@error</code> 270 | <code>\@noskipsectrue</code> 351 | <code>\@secfont</code> 2337, 2358 |
| <code>\@lempy</code> 1217, 2102 | <code>\@pages@word</code> | <code>\@secpenalty</code> 299 |
| <code>\@listI</code> 736, 740 | ... 2112, 2126, 2133 | <code>\@sect</code> 303, 304 |
| <code>\@listi</code> 733, 740 | <code>\@par</code> 1565, 1571 | <code>\@setaddresses</code> 2091 |
| <code>\@listii</code> 741 | <code>\@parboxrestore</code> 590 | <code>\@setauthorsaddresses</code> |
| <code>\@listiii</code> 744 | <code>\@parfont</code> . 2349, 2353, 2358 | 1571, 2139 |
| <code>\@listiv</code> 746 | <code>\@permissionCodeOne</code> | <code>\@setthanks</code> ... 1565, 2138 |
| <code>\@listv</code> 748 | ... 819, 823, 827, | <code>\@shortauthors</code> |
| <code>\@listvi</code> 750 | 832, 838, 842, 846, | 2187, 2197, |
| <code>\@m</code> 305 | 850, 854, 861, 867, | 2203, 2209, 2217, 2227 |
| <code>\@makefnmark</code> ... 572, | 873, 879, 883, 890, | <code>\@sidebar</code> 666, 667 |
| 597, 1551, 1556, 1560 | 894, 904, 908, 912, | <code>\@specialsection</code> ... |
| <code>\@makefnstext</code> | 916, 920, 924, 928, | 1629, 1635, 1637, 1663 |
| .. 572, 581, 594, 1562 | 932, 936, 940, 944, | <code>\@ssect</code> 302, 368 |
| <code>\@marginfigure</code> . 669, 670 | 948, 952, 956, 960, | <code>\@startPage</code> 1208, |
| <code>\@marginable</code> .. 672, 673 | 963, 967, 974, 979, | 1685, 1686, 1688, 2184 |
| <code>\@minipagefalse</code> . 568, 689 | 983, 987, 991, 995, | <code>\@startsection</code> |
| <code>\@minus</code> ... 2335, 2339, | 999, 1003, 1007, | .. 288, 380, 2334, |
| 2343, 2347, 2351, | 1011, 1015, 1019, | 2338, 2342, 2346, |
| 2382, 2387, 2392, | 1023, 1027, 1037, 1614 | 2350, 2381, 2386, 2391 |
| 2429, 2431, 2459, 2461 | <code>\@permissionCodeTwo</code> | <code>\@starttoc</code> 380 |
| <code>\@mkabstract</code> .. 1626, 2101 | 975, 1038 | <code>\@subparfont</code> .. 2394, 2395 |

| | | |
|---|---|---|
| <code>\@subsecfont</code> .. 2341, 2358 | <code>\@title</code> ... 1137, 1652, | 697, 1664, 1692, |
| <code>\@subsubsecfont</code> 2345, 2358 | 1807, 1831, 1848, 2121 | 1726, 1748, 1769, |
| <code>\@subtitle</code> . 1061, 1146, | <code>\@titlefont</code> 1747 , 1799, | 1883, 1907, 2193, |
| 1808, 1809, 1832, | 1806, 1818, 1830, 1846 | 2248, 2285, 2318, |
| 1833 , 1849, 1850, 2122 | <code>\@titlenotes</code> | 2363 , 2412 , 2442 , 2499 |
| <code>\@subtitlefont</code> | 1135 , 1139 , 1142 , 1557 | <code>\ACM@linecount</code> |
| 1768 , 1809, 1833, 1850 | <code>\@tochangmeasure</code> 321, 334 | 2144 , 2145 , |
| <code>\@subtitlenotes</code> | <code>\@toclevel</code> | 2149 , 2150 , 2153 , 2154 |
| 1144 , 1148, 1151, 1558 | <code>\@tocline</code> ... 393, 394, 395 | <code>\ACM@linecount@bx</code> .. |
| <code>\@svsec</code> . 307, 310, 316, 331 | <code>\@topnum</code> | ... 2141 , 2160 , 2167 |
| <code>\@svsechd</code> ... 329, 357, 377 | <code>\@typeset@author@bx</code> | <code>\ACM@linecount@bxht</code> |
| <code>\@teaser</code> | 1974 , | 2143 , 2148 , 2151 , 2152 |
| <code>\@teaserfigures</code> | 2023 , 2029 , 2066 , 2071 | <code>\ACM@linecountL</code> |
| 1527 , 1529, 2095, 2099 | <code>\@typeset@author@line</code> | 2156 , 2195 , |
| <code>\@tempa</code> | 1932 , 1943, 1965, 1967 | 2198, 2201, 2204, |
| 203, 205, 207, 209, | <code>\@undefined</code> | 2208, 2210, 2216, |
| 211, 213, 215, 217, | <code>\@width</code> | 2218, 2226, 2228, |
| 219, 221, 223, 225, | <code>\@exp</code> | 2287, 2294, 2295, |
| 227, 229, 231, 233, | <code>\@xsect</code> 342, 343, 379 | 2303 , 2304 , 2310 , 2313 |
| 235, 237, 239, 241, | <code>\@z</code> | <code>\ACM@linecountR</code> |
| 243, 245, 247, 250, | <code>\@</code> 469, 1591, 1596, 1611, | 2163 , 2219, 2221, |
| 252, 254, 256, 258, | 1615, 1619, 2114, 2149 | 2227 , 2231, 2311, 2314 |
| 260, 1094, 1095, | <code>\{</code> | <code>\ACM@mk@linecount</code> .. |
| 1253, 1254, 1953, | <code>\}</code> | ... 2146 , 2158 , 2165 |
| 2530 , 2546, 2547, 2549 | | <code>\ACM@ps@headings</code> ... |
| <code>\@tempb</code> 203, 205, | <code>_</code> ... 1052, 1279, 1289, | 2328 , 2332 |
| 207, 209, 211, 213, | 1591, 1593, 1615, | <code>\ACM@ps@myheadings</code> . |
| 215, 217, 219, 221, | 2118 , 2119 , 2131 , 2184 | 2327 , 2331 |
| 223, 225, 227, 229, | | <code>\ACM@ps@plain</code> . 2326 , 2330 |
| 231, 233, 235, 237, | | <code>\ACM@restore@pagestyle</code> |
| 239, 241, 243, 245, | | 2326 |
| 250, 252, 254, 256, | | <code>\ACM@timestamp</code> |
| 258 , 260, 2548, 2549 | | 2170 , 2237 , 2319 , 2322 |
| <code>\@tempboxa</code> | <code>\abstract</code> | <code>\acmArticle</code> 15 , 1171 |
| 571 | 1214 | <code>\acmArticleSeq</code> . 15 , 1173 |
| <code>\@tempc</code> . 248, 249, 251, | <code>abstract (environment)</code> 17 | <code>\acmBadgeL</code> |
| 253 , 255 , 257 , 259 , 261 | <code>acks</code> | 16 , 1203 |
| <code>\@tempcnta</code> . 2261, 2262, | <code>acks (environment)</code> 23 | <code>\acmBadgeR</code> |
| 2264 , 2265 , 2267 , 2269 | <code>\acm@copyrightinput</code> 1304 | 16 , 1198 |
| <code>\@tempdima</code> | <code>\acm@copyrightmode</code> . | <code>\acmBooktitle</code> ... 8 , 1049 |
| 2268, 2269, 2270, 2272 | 1304 , 1312 , | <code>\acmConference</code> .. 8 , 1039 |
| <code>\@tempskipa</code> | 1317 , 1320 , 1324 , | <code>\acmConference@date</code> |
| 291, 293, 294, 299, | 1330 , 1333 , 1336 , | 1042 , 1587 , 2229 , 2231 |
| 312 , 313 , 344 , 345 , | 1339 , 1342 , 1345 , | <code>\acmConference@name</code> |
| 347 , 359 , 360 , 369 , 370 | 1348 , 1351 , 1357 , 1395 | ... 1041 , 1050 , 1051 |
| <code>\@textbottom</code> | <code>\ACM@fontsize</code> | <code>\acmConference@shortname</code> |
| 598 | 116 , 160 , 163 , 165 , | 1040 , |
| <code>\@textsuperscript</code> .. | 167 , 169 , 171 , 173 , | 1044 , 1045 , 1051 , |
| 597 , 1551 , 1556 | 175 , 177 , 179 , 182 , 183 | 1052 , 1587 , 2228 , 2230 |
| <code>\@texttop</code> | <code>\ACM@format</code> | <code>\acmConference@venue</code> |
| 599 | <code>\ACM@format@nr</code> 32 , 124 , | 1043 , 1587 , 2229 , 2231 |
| <code>\@thefnmark</code> . 578, 592, | 128 , 133 , 139 , 161 , | <code>\acmdefinition</code> 2457 |
| 597 , 1551 , 1556 , 1561 | 406 , 473 , 538 , 645 , | |

| | | | | | |
|--|---|--|---|--|---|
| <code>\acmDOI</code> | 16 , 1189 | <code>\author</code> | 10 , | <code>\bibliographystyle</code> . | 447 |
| <code>\acmISBN</code> | 15 , 1187 | | 1069 , 1540 , 1541 , 2116 | <code>\bibsection</code> | 196 |
| <code>\acmJournal</code> | 7 , 1033 | <code>\author@bx</code> 1970 , 1975 , 1978 | | <code>\bibstyle</code> 224 , 226 , 268 , 452 | |
| <code>\acmMonth</code> | 15 , 1177 | <code>\author@bx@sep</code> | 1972 , 1978 , | <code>\bibstyle@acmauthoryear</code> | 274 |
| <code>\acmNumber</code> | 15 , 1169 | | 1983 , 2000 , 2032 , 2043 | <code>\bibstyle@acmnumeric</code> 280 | |
| <code>\acmplain</code> | 2427 | <code>\author@bx@wd</code> | | <code>\bigskip</code> | 1269 , 1710 , |
| <code>\acmPrice</code> | 15 , 1183 , 1322 , 1328 | | 1971 , 1974 , | 1816 , 1844 , 1852 , | |
| <code>\acmSubmissionID</code> 15 , 1185 | | | 1982 , 1983 , 1985 , | 2029 , 2071 , 2096 , 2137 | |
| <code>\acmVolume</code> | 15 , 1167 | | 1991 , 1993 , 1995 , | <code>\box</code> 694 , 1694 , 1696 , 1698 , | |
| <code>\acmYear</code> | 15 , 1175 | | 1997 , 2000 , 2031 , | 1700 , 1702 , 1704 , | |
| <code>\addcontentsline</code> 198 , | | <code>\authornote</code> | 2032 , 2034 , 2040 , 2043 | 1706 , 1708 , 1710 , | |
| 323 , 336 , 2103 , 2524 | | | <code>\authornotemark</code> . | 1966 , 1978 , 2027 , 2098 | |
| <code>\additionalaffiliation</code> | 11 , 1116 | <code>\authornotemark</code> . | 14 , 1116 , 1155 , 2117 | | |
| <code>\addpenalty</code> | 299 | <code>\authornotemark</code> . | 14 , 1161 | | |
| <code>\addresses</code> | | <code>\authors</code> | | C | |
| 1075 , 1077 , 1080 , | | | 1078 , 1081 , 1086 , | <code>\c@footnote</code> | 1546 |
| 1085 , 1112 , 1130 , | | | 1641 , 1643 , 1651 , 2121 | <code>\c@secnumdepth</code> | 306 , 320 , 324 , 333 , 337 |
| 1157 , 1163 , 1165 , | | <code>\authorsaddresses</code> 14 , 1133 | | <code>\captionsetup</code> | |
| 1967 , 2029 , 2071 , 2089 | | | B | | 637 , 639 , 641 , |
| <code>\addtolength</code> . . . | 721 , | <code>\baselineskip</code> | | 643 , 652 , 654 , 657 , | |
| 722 , 723 , 727 , 728 , 2151 | | | 1581 , 1801 , | 660 , 667 , 670 , 673 , 2097 | |
| <code>\addvspace</code> | 299 , 391 | | 1813 , 1825 , 1840 , | <code>\ccdesc@parse@finish</code> 1296 | |
| <code>\advance</code> | 737 , | | 2151 , 2335 , 2336 , | <code>\ccsdesc</code> | 16 , 1274 |
| 742 , 745 , 747 , | | | 2339 , 2340 , 2343 , | <code>\ccsdesc@parse</code> 1275 , 1276 | |
| 749 , 751 , 1070 , | | | 2347 , 2382 , 2383 , | <code>\ccsdesc@parse@end</code> . | |
| 1072 , 1792 , 1793 , | | | 2387 , 2392 , 2428 , | | 1275 , 1296 |
| 1796 , 1797 , 1821 , | | | 2429 , 2430 , 2431 , | <code>\ccsdesc@parse@finish</code> | 1295 , 1296 |
| 1822 , 1983 , 2000 , | | | 2458 , 2459 , 2460 , 2461 | CCSXML (environment) . . | 16 |
| 2032 , 2043 , 2150 , | | <code>\begin</code> | 20 , 2159 , 2166 , 2271 | <code>\centering</code> 384 , 468 , 593 , | |
| 2154 , 2265 , 2267 , 2270 | | | <code>\begingroup</code> | 671 , 674 , 1818 , | |
| <code>\affiliation</code> | 10 , | | 314 , 357 , 371 , 380 , | 1830 , 1975 , 2028 , 2277 | |
| 1109 , 1952 , 2014 , 2057 | | <code>\bfseries</code> | 437 , 1543 , 1881 , 2522 | <code>\cite</code> | 430 , 431 , 442 , 446 |
| <code>\and</code> | 1059 , 1085 , | | 1750 , 1752 , 1754 , | <code>\citeA</code> | 436 |
| 1086 , 1099 , 1105 , | | | 1758 , 1760 , 1762 , | <code>\citealt</code> | 435 |
| 1943 , 1948 , 1950 , | | | 1764 , 1766 , 1926 , | <code>\citealtNP</code> | 432 |
| 1960 , 1965 , 1974 , | | | 1929 , 2120 , 2278 , | <code>\citeauthor</code> | 432 |
| 2008 , 2023 , 2029 , | | | 2358 , 2359 , 2373 , | <code>\citeN</code> | 430 |
| 2051 , 2066 , 2071 , 2086 | | | 2374 , 2376 , 2377 , | <code>\citenam</code> | 443 |
| <code>\andify</code> | 1641 , | | 2379 , 2380 , 2385 , | <code>\citeNN</code> | 433 |
| 1642 , 1933 , 1936 , 2130 | | | 2390 , 2398 , 2399 , | <code>\citeNP</code> | 435 |
| <code>anonsuppress</code> (environ- ment) | 22 | | 2402 , 2403 , 2422 , 2452 | <code>\citepar</code> | 431 |
| <code>\AtBeginDocument</code> . . . | | <code>\bgroup</code> | 667 , 670 , 673 , | <code>\citestyle</code> | 24 , 266 , 286 |
| 68 , 441 , 449 , 713 , 2333 | | | 678 , 1117 , 1628 , | <code>\citeyear</code> | 434 |
| <code>\AtEndDocument</code> | 1267 | | 1633 , 1974 , 2068 , | <code>\citeyearNP</code> | 434 |
| <code>\AtEndPreamble</code> | | | 2077 , 2096 , 2101 , 2111 | <code>\citeyearpar</code> | 433 , 446 |
| | 419 , 631 , 2469 , 2531 | <code>\bibfont</code> | 200 | <code>\city</code> | 12 , 1123 , 1861 , 2082 |

| | | |
|---|---|---------------------|
| <code>\ClassError</code> | <code>\def</code> . . . 25, 38, 116, 163, | 979, 981, 982, 983, |
| . . . 35, 1031, 1115, | 165, 167, 169, 171, | 985, 986, 987, 989, |
| 1223, 1229, 1235, 2115 | 173, 175, 177, 179, | 990, 991, 993, 994, |
| <code>\ClassInfo</code> | 203, 205, 207, 209, | 995, 997, 998, 999, |
| . . . 124, 182, 1029, | 211, 213, 215, 217, | 1001, 1002, 1003, |
| 1220, 1222, 1226, | 219, 221, 223, 225, | 1005, 1006, 1007, |
| 1228, 1232, 1234, 1237 | 227, 228, 229, 230, | 1009, 1010, 1011, |
| <code>\ClassWarning</code> | 231, 232, 233, 234, | 1013, 1014, 1015, |
| . . . 27, 129, 615, | 235, 236, 237, 239, | 1017, 1018, 1019, |
| 618, 621, 1210, 1238 | 241, 243, 245, 246, | 1021, 1022, 1023, |
| <code>\cleaders</code> 1858 | 250, 252, 254, 256, | 1025, 1026, 1027, |
| <code>\clubpenalty</code> . . . 356, 362 | 258, 260, 288, 304, | 1033, 1034, 1035, |
| <code>\CodelineIndex</code> 17 | 329, 343, 367, 368, | 1036, 1037, 1038, |
| <code>\Collect@Body</code> . . 666, | 377, 380, 393, 394, | 1049, 1053, 1054, |
| 669, 672, 1214, 1528 | 395, 400, 401, 402, | 1055, 1061, 1094, |
| <code>\color</code> . . . 1579, 2149, 2153 | 403, 447, 551, 558, | 1116, 1117, 1118, |
| <code>\color@begingroup</code> 580, 593 | 560, 572, 574, 585, | 1119, 1120, 1121, |
| <code>\color@endbox</code> 692 | 597, 598, 667, 670, | 1132, 1133, 1135, |
| <code>\color@endgroup</code> | 673, 678, 680, 684, | 1136, 1144, 1145, |
| 569, 583, 596 | 687, 705, 706, 707, | 1154, 1155, 1167, |
| <code>\columnwidth</code> . . . 552, | 708, 736, 741, 744, | 1169, 1171, 1173, |
| 589, 678, 2031, 2068 | 746, 748, 750, 817, | 1175, 1177, 1179, |
| <code>\contentsnamefont</code> . . 384 | 818, 819, 821, 822, | 1183, 1185, 1187, |
| <code>\copy</code> 1858 | 823, 825, 826, 827, | 1189, 1199, 1200, |
| <code>\copyright</code> 1591 | 829, 831, 832, 836, | 1201, 1202, 1204, |
| <code>\copyrightpermissionfootnoterule</code> | 837, 838, 840, 841, | 1205, 1206, 1207, |
| 551 | 842, 844, 845, 846, | 1208, 1210, 1212, |
| <code>\copyrightyear</code> . . 17, 1525 | 848, 849, 850, 852, | 1215, 1217, 1240, |
| <code>\country</code> 12, 1126, 1861, 2085 | 853, 854, 856, 857, | 1252, 1253, 1277, |
| <code>\csname</code> 268, 319, | 859, 860, 861, 865, | 1296, 1354, 1356, |
| 321, 325, 332, 334, | 866, 867, 871, 872, | 1393, 1394, 1525, |
| 338, 367, 387, 388, | 873, 877, 878, 879, | 1527, 1529, 1538, |
| 578, 592, 1278, | 881, 882, 883, 885, | 1551, 1556, 1565, |
| 1279, 1281, 1282, | 886, 888, 889, 890, | 1571, 1663, 1684, |
| 1283, 1284, 1285, | 892, 893, 894, 896, | 1725, 1747, 1768, |
| 1288, 1290, 1656, 1658 | 898, 900, 902, 903, | 1789, 1817, 1845, |
| <code>\CurrentOption</code> . 117, | 904, 906, 907, 908, | 1854, 1861, 1862, |
| 118, 119, 120, 121, 122 | 910, 911, 912, 914, | 1864, 1865, 1866, |
| D | 915, 916, 918, 919, | 1867, 1869, 1871, |
| <code>\day</code> 2182 | 920, 922, 923, 924, | 1872, 1875, 1878, |
| <code>\DeclareNewFootnote</code> | 926, 927, 928, 930, | 1881, 1905, 1906, |
| 555, 557 | 931, 932, 934, 935, | 1910, 1911, 1914, |
| <code>\DeclareOptionX</code> | 936, 938, 939, 940, | 1915, 1917, 1918, |
| 38, 117, | 942, 943, 944, 946, | 1920, 1921, 1923, |
| 118, 119, 120, 121, 122 | 947, 948, 950, 951, | 1924, 1926, 1927, |
| <code>\DeclareRobustCommand</code> 436 | 952, 954, 955, 956, | 1929, 1930, 1932, |
| <code>\DeclareTextFontCommand</code> | 958, 959, 960, 962, | 1934, 1939, 1940, |
| 632 | 963, 965, 966, 967, | 1941, 1942, 1944, |
| | 969, 970, 972, 973, | 1951, 1952, 1953, |
| | 974, 975, 977, 978, | 1974, 1981, 2003, |

| | | |
|--|--|--|
| 2009, 2014, 2030, | <code>\dots</code> 1619 | 2262, 2312, 2321, |
| 2046, 2052, 2057, | | 2530, 2535, 2542, 2550 |
| 2072, 2078, 2079, | E | <code>\email</code> 10, 1128, |
| 2080, 2081, 2082, | <code>\edef</code> 117, 118, 119, 120, 305 | 1951, 2009, 2052, 2088 |
| 2083, 2085, 2086, | <code>\editor</code> 10, 1055 | <code>\emph</code> 1603, 1605 |
| 2087, 2088, 2091, | <code>\egroup</code> 570, | <code>\EnableCrossrefs</code> 19 |
| 2092, 2093, 2094, | 668, 671, 674, 685, | <code>\end</code> . . . 22, 2161, 2168, 2279 |
| 2096, 2101, 2111, | 691, 1127, 1630, | <code>\end@dblfloat</code> 683 |
| 2112, 2113, 2114, | 1639, 1977, 2071, | <code>\end@float</code> 685 |
| 2115, 2118, 2137, | 2090, 2097, 2110, 2136 | <code>\endcsname</code> 267, 268, 319, |
| 2138, 2139, 2146, | <code>\else</code> . . . 52, 60, 69, 77, | 321, 325, 332, 334, |
| 2156, 2163, 2187, | 85, 93, 101, 111, | 338, 367, 387, 388, |
| 2188, 2247, 2254, | 135, 248, 269, 298, | 578, 592, 1278, |
| 2259, 2261, 2329, | 305, 308, 320, 324, | 1279, 1281, 1282, |
| 2354, 2358, 2359, | 328, 333, 337, 349, | 1283, 1284, 1285, |
| 2360, 2361, 2367, | 361, 376, 426, 440, | 1288, 1290, 1656, 1658 |
| 2368, 2370, 2371, | 446, 448, 563, 642, | <code>\enddescription</code> 759 |
| 2373, 2374, 2376, | 1051, 1057, 1071, | <code>\endgroup</code> 318, 357, 375, |
| 2377, 2379, 2380, | 1079, 1083, 1084, | 390, 1624, 1903, 2526 |
| 2385, 2390, 2395, | 1093, 1098, 1101, | <code>\endlist</code> 757, 759 |
| 2398, 2399, 2402, | 1104, 1111, 1129, | <code>\endminipage</code> 560 |
| 2403, 2405, 2406, | 1141, 1150, 1156, | <code>\endtrivlist</code> 2519 |
| 2408, 2409, 2410, | 1164, 1221, 1227, | <code>\enspace</code> 2406 |
| 2411, 2420, 2421, | 1233, 1244, 1247, | environments: |
| 2422, 2423, 2438, | 1257, 1260, 1263, | <code>abstract</code> 17 |
| 2439, 2440, 2441, | 1268, 1287, 1291, | <code>acks</code> 23 |
| 2450, 2451, 2452, | 1292, 1534, 1552, | <code>anonsuppress</code> 22 |
| 2453, 2497, 2498, | 1563, 1567, 1568, | <code>CCSXML</code> 16 |
| 2507, 2508, 2528, | 1582, 1585, 1586, | <code>marginfigure</code> 21 |
| 2530, 2546, 2547, 2548 | 1592, 1597, 1604, | <code>marginable</code> 21 |
| <code>\define@boolkey</code> | 1609, 1612, 1615, | <code>printonly</code> 22 |
| 49, 57, 65, | 1617, 1618, 1619, | <code>screenonly</code> 22 |
| 74, 82, 90, 98, 106, | 1620, 1628, 1633, | <code>sidebar</code> 21 |
| 1114, 1218, 1224, 1230 | 1636, 1687, 1713, | <code>teaserfigure</code> 17 |
| <code>\define@choicekey</code> . . | 1718, 1791, 1795, | <code>\everypar</code> 297, 352, 363, 2105 |
| 32, 760, 1303 | 1800, 1808, 1811, | <code>\excludecomment</code> . 1272, |
| <code>\define@cmdkey</code> 1236 | 1824, 1832, 1839, | 2534, 2536, 2540, 2541 |
| <code>\definecolor</code> | 1849, 1855, 1856, | <code>\ExecuteOptionsX</code> . . . |
| . . . 456, 457, 458, | 1869, 1870, 1871, | 48, 56, 64, |
| 459, 460, 461, 462, 463 | 1872, 1874, 1875, | 73, 81, 89, 97, 105, 115 |
| <code>\department</code> | 1878, 1935, 1947, | <code>\expandafter</code> |
| . 12, 1120, 1861, 2084 | 1953, 1959, 1975, | . . . 247, 249, 449, |
| <code>\description</code> 753 | 1986, 1996, 2005, | 571, 1278, 1279, |
| <code>\descriptionlabel</code> 752, 755 | 2011, 2018, 2035, | 1281, 1282, 1288, 1290 |
| <code>\dimexpr</code> . . 676, 694, 2234 | 2039, 2048, 2054, | |
| <code>\divide</code> 1985, 1991, 1993, | 2061, 2074, 2076, | F |
| 1995, 1997, 2034, 2040 | 2095, 2102, 2106, | <code>\familydefault</code> 634 |
| <code>\do</code> 202 | 2112, 2118, 2122, | <code>\fancyfoot</code> 2199, |
| <code>\DocInput</code> 21 | 2127, 2129, 2135, | 2205, 2213, 2222, |
| <code>\documentclass</code> 9 | 2179, 2187, 2224, | 2225, 2237, 2288, |

| | | | |
|-----------------------------|--------------------------------------|------------------------|-------------------------------------|
| | 2289, 2291, 2299, | 1392, 1524, 1536, | 2225, 2289, 2291, |
| | 2307, 2315, 2319, 2322 | 1541, 1542, 1552, | 2299, 2307, 2315, 2320 |
| \fancyhead . | 2195, 2196, | 1554, 1566, 1572, | \footnotetext .. 1140, |
| | 2197, 2198, 2201, | 1573, 1574, 1580, | 1142, 1149, 1152, 1159 |
| | 2202, 2203, 2204, | 1583, 1584, 1588, | \footnotetextauthorsaddresses |
| | 2208, 2210, 2211, | 1589, 1594, 1606, | 1564, 1570 |
| | 2216, 2218, 2219, | 1611, 1615, 1619, | \footnotetextcopyrightpermission |
| | 2220, 2226, 2227, | 1620, 1621, 1622, | 1575 |
| | 2228, 2230, 2287, | 1623, 1631, 1632, | \footrulewidth 2192, 2284 |
| | 2294, 2295, 2296, | 1638, 1640, 1647, | \format 32 |
| | 2302, 2303, 2304, | 1683, 1689, 1717, | \frenchspacing 2552 |
| | 2310, 2311, 2313, 2314 | 1721, 1722, 1723, | \fulltextwidth |
| \fancyheadoffset ... | | 1745, 1767, 1788, | 675, 678, 694 |
| ... 2234, 2297, 2305 | | 1794, 1798, 1804, | |
| \fancyhf 2190, 2282 | | 1810, 1815, 1827, | G |
| \fancypagestyle 2189, 2281 | | 1829, 1834, 1842, | \g@addto@macro |
| \fi 54, 62, 71, 79, 87, 95, | | 1843, 1851, 1859, | 1059, 1085, 1086, |
| 103, 113, 132, 137, | | 1869, 1871, 1872, | 1099, 1105, 1112, |
| 159, 180, 181, 192, | | 1874, 1875, 1878, | 1130, 1137, 1139, |
| 204, 206, 208, 210, | | 1880, 1902, 1931, | 1142, 1146, 1148, |
| 212, 214, 216, 218, | | 1938, 1949, 1963, | 1151, 1157, 1158, |
| 220, 222, 224, 226, | | 1964, 1975, 1998, | 1163, 1165, 1258, |
| 228, 230, 232, 234, | | 1999, 2007, 2013, | 1264, 1283, 1290, |
| 236, 238, 240, 242, | | 2022, 2041, 2042, | 1529, 1533, 1535, |
| 244, 246, 251, 253, | | 2050, 2056, 2065, | 1948, 1960, 2006, |
| 255, 257, 259, 261, | | 2074, 2076, 2100, | 2012, 2019, 2049, |
| 262, 271, 273, 287, | | 2108, 2110, 2112, | 2055, 2062, 2092, 2093 |
| 289, 295, 300, 305, | | 2119, 2122, 2131, | \gdef 1040, |
| 311, 322, 326, 335, | | 2134, 2135, 2155, | 1041, 1042, 1043, |
| 339, 341, 364, 365, | | 2162, 2169, 2181, | 1045, 1049, 1056, |
| 378, 389, 418, 428, | | 2186, 2187, 2195, | 1058, 1077, 1078, |
| 444, 446, 450, 453, | | 2196, 2201, 2202, | 1080, 1081, 1091, |
| 471, 535, 549, 567, | | 2209, 2212, 2217, | 1097, 1103, 1215, |
| 584, 611, 629, 635, | | 2221, 2225, 2232, | 1239, 1256, 1262, |
| 662, 663, 682, 686, | | 2235, 2238, 2260, | 1279, 1281, 1282, |
| 711, 1028, 1046, | | 2279, 2288, 2315, | 1288, 1686, 1946, |
| 1052, 1060, 1074, | | 2316, 2323, 2324, | 1950, 1955, 1979, |
| 1082, 1087, 1088, | | 2404, 2426, 2456, | 1980, 2001, 2002, |
| 1092, 1100, 1106, | | 2494, 2511, 2530, | 2004, 2008, 2010, |
| 1107, 1108, 1113, | | 2538, 2544, 2547, 2551 | 2015, 2044, 2045, |
| 1131, 1143, 1153, | \firstpagestyle 2281 | | 2047, 2051, 2053, 2058 |
| 1160, 1166, 1182, | \floatname 665 | | \geometry 475, 478, 485, 492, |
| 1223, 1229, 1235, | \footnote 2115 | | 499, 506, 513, 520, 527 |
| 1249, 1250, 1259, | \footnotemark 403, 1137, | | \getrefnumber 2112 |
| 1265, 1266, 1270, | 1146, 2092, 2093, 2113 | | \global 351, 354, 390, 586, |
| 1286, 1293, 1294, | \footnoterule 558 | | 693, 1070, 1072, |
| 1316, 1319, 1323, | \footnotesep ... 582, 595 | | 1073, 1110, 1547, |
| 1329, 1332, 1335, | \footnotesize 588, 2178, 2199, | | 1549, 1643, 1644, |
| 1338, 1341, 1344, | 2205, 2213, 2222, | | |
| 1347, 1350, 1353, | | | |

| | | | |
|---|--|--|--|
| 1943, 1965, 1966, 1975, 2023, 2026, 2066, 2098, 2150, 2154 | \grantnum 23, <u>2529</u> | \ifACM@manuscript <u>125</u> , 189, 1242, 1585, 1595 | \ifnum 128, 133, 305, 306, 320, 324, 333, 337, 1291, 1292, 1312, 1317, 1320, 1324, 1330, 1333, 1336, 1339, 1342, 1345, 1348, 1351, 1541, 1984, 2033, 2073, 2075, 2112, 2262, 2264, 2318 |
| \grantsponsor . . . 23, <u>2528</u> | \ifACM@natbib <u>82</u> , 194, 285, 429 | \ifACM@natbib@override <u>82</u> | \ifPDFTeX 601 |
| H | \ifACM@natbib@override <u>82</u> | \ifACM@newfonts <u>613</u> , 624 | \ifvmode 1855 |
| \hbox . 597, 1551, 1556, 1857 | \ifACM@printacmref <u>1224</u> , 1645 | \ifACM@printccs <u>1218</u> , 1627 | \ifvoid 563 |
| \headrulewidth 2191, 2283 | \ifACM@printfolios <u>1230</u> , 2195, 2196, 2201, 2202, 2209, 2212, 2217, 2221, 2225, 2288, 2315 | \ifACM@review <u>65</u> , 2141, 2157, 2164 | \ifx . 160, 203, 205, 207, 209, 211, 213, 215, 217, 219, 221, 223, 225, 227, 229, 231, 233, 235, 237, 239, 241, 243, 245, 250, 252, 254, 256, 258, 260, 448, 1044, 1051, 1055, 1075, 1090, 1095, 1096, 1102, 1162, 1254, 1255, 1261, 1268, 1278, 1287, 1563, 1567, 1607, 1615, 1618, 1619, 1620, 1628, 1633, 1685, 1713, 1718, 1791, 1795, 1800, 1808, 1811, 1824, 1832, 1839, 1849, 1935, 1945, 1953, 1954, 2003, 2009, 2014, 2046, 2052, 2057, 2095, 2102, 2118, 2122, 2129, 2135, 2179, 2530, 2547, 2549 |
| \hfill 1847, 2153 | \ifACM@screen <u>49</u> , 420, 2532 | \ifACM@sigchiamode <u>127</u> , 573, 633, 677, 683, 1552, 1554, 1975, 2233 | \ignorespaces 366, 582, 595, 1118, 1119, 1121, 1132, 1861, 1862, 1864, 1865, 1866, 1867, 1868, 1869, 2080, 2109, 2114, 2517 |
| \href . 1714, 1719, 1801, 1813, 1825, 1840, 2550 | \ifACM@timestamp <u>98</u> , 2170, 2236, 2317 | \ifACM@timestamp <u>1301</u> | \immediate 388, 452 |
| \hrule 552, 559, 1847 | \ifacmowned <u>1301</u> | \if@filesw 386, 451 | \includecomment 2533, 2537, 2543 |
| \hsize 589, 1550, 1789, 1790, 1817, 1819, 1845, 1882, 1974, 2025, 2068 | \if@insideauthorgroup <u>1067</u> , 1071 | \if@nobreak 296 | \includegraphics |
| \hskip 316, 330, 360, 373, 377, 1716, 1803, 1812, 1828, 1837, 1858, 2516 | \if@printcopyright <u>1297</u> , 1590 | \if@printpermission <u>1299</u> , 1583 | |
| \hspace 1405, 1416, 1425, 1450, 1462, 1483, 1978, 2028 | \if@printcopyright <u>1297</u> , 1590 | \ifcase 139, 161, 406, 473, 538, 645, 697, 815, 1179, 1357, 1395, 1664, 1692, 1726, 1748, 1769, 1883, 1907, 1987, 2036, 2193, 2248, 2285, 2363, 2412, 2442, 2499 | |
| \Huge 1756, 1758, 1760, 1762, 1764, 1766 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | \ifcsname 267 | |
| \hypersetup 421, 427, 1648 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | \ifdim 293, 313, 345, 370, 2152 | |
| I | \if@timestamp <u>98</u> , 2170, 2236, 2317 | \IfFileExists 615, 618, 621 | |
| \if 248 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | \IfInteger 1237 | |
| \ifACM@acmthm . 57, 2470 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | \ifNAT@numbers 446 | |
| \ifACM@affiliation@obeynpunctation <u>1114</u> , 1856, 1869, 1871, 1872, 1873, 1875, 1878 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | | |
| \ifACM@anonymous <u>90</u> , 1076, 1084, 1089, 1111, 1129, 1138, 1147, 1156, 1532, 1539, 1568, 2187, 2539 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | | |
| \ifACM@authordraft <u>106</u> , 464, 1576 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | | |
| \ifACM@authorversion <u>74</u> , 1582, 1598 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | | |
| \ifACM@badge <u>1191</u> , 1711, 1820, 1836 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | | |
| \ifACM@journal . 126, 638, 1245, 1569, 1586, 1602, 1613, 1634, 1863, 2104, 2123 | \if@timestamp <u>98</u> , 2170, 2236, 2317 | | |

| | | |
|--|---|--|
| 1715, 1720, 1802, 1814, 1826, 1841 | \leftmargini ... 720, 721, 722, 723, 736, 737 | \marginfigure 669 |
| \indent 2498 | \leftmarginii .. 726, 727, 728, 729, 741, 742 | marginfigure (environ- ment) 21 |
| \input 602 | \leftmarginiii 729, 730, 744, 745 | \marginpar 574, 668, 671, 674, 1712 |
| \InputIfFileExists .. 26 | \leftmarginiv 730, 731, 746, 747 | \marginparsep .. 676, 2234 |
| \institution 12, 1119, 1861, 2081 | \leftmarginv 731, 732, 748, 749 | \marginparwidth . 676, 2234 |
| \interfootnotelinepenalty 576 | \leftmarginvi 732, 750, 751 | \margintable 672 |
| \interlinepenalty 317, 374, 576 | \leftskip . 1846, 2069, 2356 | margintable (environ- ment) 21 |
| \item 2516 | \let 224, 226, 238, 240, 242, 268, 307, 396, 397, 430, 431, 432, 433, 434, 435, 438, 442, 599, 630, 679, 740, 755, 759, 1122, 1123, 1124, 1125, 1126, 1273, 1544, 1545, 1560, 1561, 1562, 1565, 1571, 1643, 1644, 1876, 1877, 1879, 1943, 1965, 2023, 2029, 2066, 2071, 2326, 2327, 2328, 2330, 2331, 2332 | \mbox 246 |
| \itshape .. 1587, 2360, 2361, 2390, 2395, 2408, 2420, 2440, 2507 | \libertineLF 632 | \mdseries 1771, 1773, 1775, 1779, 1781, 1783, 1785, 1787, 1927, 1930 |
| J | \lineskip 2028, 2070 | \medskip .. 1666, 1668, 1670, 1672, 1966, 1968, 2027, 2099, 2120 |
| \jobname 385, 388 | \linespacing ... 383, 384 | \mktitle@bx 1537, 1694, 1696, 1698, 1700, 1702, 1704, 1706, 1708, 1710, 1799, 1818, 1846, 1966, 2026, 2027, 2098 |
| K | \liningnums 630 | \month 1178, 2182 |
| \kern 551, 552, 558, 559, 1847 | \list 753 | \moveleft 693 |
| \keywords 16, 1212 | \listisep ... 734, 735, 739 | \multiply 2269 |
| L | \listparindent 738 | N |
| \l@section 393 | \LoadClass 183 | \NAT@setcites 264 |
| \l@subsection .. 393, 394 | \long 574, 585, 667, 670, 673, 1215, 1217, 1529, 2138 | \NAT@aysep 255 |
| \l@subsubsection ... 395 | \loop 2149, 2263 | \NAT@citetp 438 |
| \labelenumi 705 | M | \NAT@close 204, 206, 208, 210, 253 |
| \labelenumii 706 | \makeatletter 380 | \NAT@cmprs .. 232, 234, 236 |
| \labelenumiii 707 | \makebox 1577, 2272 | \NAT@cmt 259 |
| \labelenumiv 708 | \makelabel 755 | \NAT@ctype 438 |
| \labelsep 714, 722, 727, 737, 742, 745, 747, 749, 751, 2516 | \MakeTextUppercase 1946, 1948, 2358, 2367, 2370, 2373, 2376, 2398, 2402 | \NAT@find@eq 247 |
| \labelwidth . 737, 742, 745, 747, 749, 751, 754 | \maketitle 19, 1538 | \NAT@fullfalse 438 |
| \LARGE 1750, 1752, 1754, 1777, 1779, 1781, 1783, 1785, 1914, 1917, 2278 | | \NAT@longnamestrue . 244 |
| \Large 1905, 1923, 2373, 2374, 2376, 2377, 2379 | | \NAT@merge .. 238, 240, 242 |
| \large 1577, 1910, 1915, 1918, 2367, 2368, 2370, 2371 | | \NAT@nmfmt 246 |
| \lastbox 355, 2105 | | \NAT@numbersfalse .. 218 |
| \leaders 1847 | | \NAT@numberstrue 220, 222 |
| \leavevmode 289, 1847, 2027 | | \NAT@open 204, 206, 208, 210, 251, 438 |
| \leftmargin 736, 741, 744, 746, 748, 750 | | \NAT@partrue 438 |

| | | | |
|---|------------------------|--|---------------------------------------|
| <code>\NAT@superfalse</code> | 220 | 1924, 2423, 2438, | 1375, 1378, 1381, |
| <code>\NAT@supertrue</code> | 222 | 2450, 2453, 2514, 2552 | 1383, 1386, 1389, |
| <code>\NAT@swafalse</code> | 437 | | 1396, 1407, 1418, |
| <code>\NAT@sup</code> | 246 | <code>\normalparindent</code> | 550 |
| <code>\NAT@yrsep</code> | 257 | <code>\normalsize</code> 1768, 1906, | 1426, 1432, 1438, |
| <code>\NeedsTeXFormat</code> | 1 | 1920, 1921, 1924, 2552 | 1452, 1464, 1471, |
| <code>\newblock</code> | 439 | <code>\num@authorgroups</code> | 1485, 1492, 1498, |
| <code>\newbox</code> | 1537, 1853, 1970 | 1063, | 1505, 1514, 1667, |
| <code>\newcommand</code> | 274, 280, | 1072, 1541, 1987, | 1669, 1671, 1673, |
| 445, 1039, 1109, | | 1991, 1993, 2036, 2075 | 1675, 1677, 1679, |
| 1161, 1198, 1203, | | <code>\num@author</code> | 1681, 1695, 1697, |
| 1253, 1274, 1868, | | 1065, 1070, 2073 | 1699, 1701, 1703, |
| 1873, 2177, 2529, 2545 | | <code>\number</code> | 305 |
| <code>\newcount</code> | 1063, 1065, 2144 | <code>\numberline</code> | 325, 338 |
| <code>\newcounter</code> | 2173, 2175 | <code>\numexpr</code> | 2172, 2174, 2176 |
| <code>\newdimen</code> | 675, 712, | | 1741, 1743, 1751, |
| 1971, 2241, 2243, 2245 | | O | 1753, 1755, 1757, |
| <code>\newenvironment</code> | 669, 672, 1528 | <code>\onehalfspacing</code> | 191 |
| <code>\newfloat</code> | 664 | <code>\openout</code> | 388 |
| <code>\newif</code> | 125, 126, | <code>\or</code> | 142, |
| 127, 613, 1067, | | 144, 146, 148, 150, | 1782, 1784, 1786, |
| 1191, 1297, 1299, 1301 | | 152, 154, 156, 164, | 1886, 1888, 1890, |
| <code>\newlength</code> | 1193, 1195, 1196, 2143 | 166, 168, 170, 172, | 1892, 1894, 1896, |
| <code>\newsavebox</code> | 2142 | 174, 176, 178, 408, | 1898, 1900, 1909, |
| <code>\newskip</code> | 734, 1972 | 409, 410, 411, 412, | 1912, 1913, 1916, |
| <code>\newtheorem</code> | 2473, 2476, 2479, | 413, 415, 416, 477, | 1919, 1922, 1925, |
| 2482, 2485, 2489, 2492 | | 484, 491, 498, 505, | 1928, 1989, 1990, |
| <code>\newtheoremstyle</code> | 2427, 2457 | 512, 519, 526, 540, | 1992, 1994, 2038, |
| <code>\newwrite</code> | 387 | 541, 542, 544, 545, | 2200, 2207, 2215, |
| <code>\nobreak</code> | 346, 2120 | 546, 547, 548, 647, | 2250, 2255, 2290, |
| <code>\noindent</code> | 572, | 648, 649, 650, 651, | 2298, 2306, 2365, |
| 1269, 1562, 1666, | | 653, 656, 659, 699, | 2366, 2369, 2372, |
| 1668, 1670, 1672, | | 700, 701, 702, 703, | 2375, 2378, 2396, |
| 1691, 1712, 1799, | | 704, 709, 710, 820, | 2400, 2414, 2415, |
| 1806, 1809, 1833, | | 824, 828, 835, 839, | 2416, 2417, 2418, |
| 1847, 1848, 1850, | | 843, 847, 851, 855, | 2419, 2424, 2425, |
| 1933, 1966, 1967, | | 858, 864, 870, 876, | 2444, 2445, 2446, |
| 2026, 2070, 2098, | | 880, 884, 887, 891, | 2447, 2448, 2449, |
| 2099, 2120, 2121, 2508 | | 895, 897, 899, 901, | 2454, 2455, 2501, |
| <code>\nolinkurl</code> | 2010, | 905, 909, 913, 917, | 2502, 2503, 2504, |
| 2012, 2053, 2055, 2088 | | 921, 925, 929, 933, | 2505, 2506, 2509, 2510 |
| <code>\normalcolor</code> | 565 | 937, 941, 945, 949, | <code>\orcid</code> |
| <code>\normalfont</code> 597, 1269, | | 953, 957, 961, 964, | 10, 1132 |
| 1556, 1906, 1911, | | 968, 971, 976, 980, | <code>\outer@nobreak</code> |
| 1920, 1921, 1923, | | 984, 988, 992, 996, | 690 |
| | | 1000, 1004, 1008, | |
| | | 1012, 1016, 1020, | |
| | | 1024, 1179, 1180, | |
| | | 1181, 1358, 1360, | |
| | | 1363, 1365, 1366, | |
| | | 1368, 1370, 1372, | |
| | | | P |
| | | | <code>\p@</code> |
| | | | 391, |
| | | | 536, 543, 551, 552, |
| | | | 558, 559, 2335, |
| | | | 2339, 2343, 2344, |
| | | | 2347, 2348, 2351, |
| | | | 2352, 2382, 2387, |

| | | | |
|--|---|----------------------------|---|
| | 2388, 2392, 2393, 2514 | \position | 12, 1118, 1342, 1345, 1348, |
| \PackageError | 54, 62, 1122, 1123, 1124, | | 1351, 1357, 1395, |
| | 71, 79, 87, 95, 103, 113 | | 1560, 1561, 1665, |
| \PackageInfo | 51, 1125, 1126, 1861, 2080 | \postcode | 1693, 1727, 1749, |
| | 53, 59, 61, 67, 70, | | 1770, 1884, 1908, |
| | 76, 78, 84, 86, 92, | printonly (environment) | 1973, 1982, 1983, |
| | 94, 100, 102, 108, | \ProcessOptionsX | 1984, 1985, 1988, |
| | 112, 834, 863, 869, 875 | \proof | 1991, 1993, 1995, |
| \PageIndex | 16 | \proofname | 1997, 2000, 2028, |
| \pageref | 2184 | \protect | 2031, 2032, 2033, |
| \pagestyle | 2240 | \protected@edef | 2034, 2037, 2040, |
| \par | 290, 346, 382, 561, 688, 1269, 1565, 1571, 1583, 1587, 1630, 1639, 1666, 1668, 1670, 1672, 1694, 1696, 1698, 1710, 1809, 1816, 1833, 1844, 1847, 1850, 1852, 1871, 1872, 1874, 1875, 1933, 1937, 1966, 1968, 1974, 1976, 2004, 2006, 2012, 2019, 2027, 2029, 2047, 2049, 2055, 2062, 2069, 2071, 2096, 2097, 2098, 2099, 2109, 2120, 2136, 2137, 2138, 2512 | \protected@edef | 2043, 2073, 2075, 2092, 2112, 2145, 2174, 2176, 2179, |
| \paragraph 1678, 2346, 2386 | | \providecommand | 2194, 2249, 2251, |
| \parbox 468, 1805, 1823, 1830, 1838, 2147, 2276 | | | 2252, 2253, 2256, |
| \parindent 536, 550, 721, 1565, 1571, 1581, 2346, 2357, 2409, 2439 | | \ProvidesClass | 2257, 2258, 2261, |
| \parskip | 536, 1581 | \ProvidesFile | 2262, 2264, 2267, |
| \part | 2350 | \ps@headings | 2268, 2269, 2270, |
| \PassOptionsToClass | 121, 122 | \ps@myheadings | 2286, 2318, 2364, |
| \pdfgentounicode | 610 | \ps@plain | 2413, 2443, 2500, 2514 |
| \pdfglyphtounicode | 603, 604, 605, 606, 607, 608, 609 | \pushQED | \removelastskip |
| \pdfstringdefDisableCommands | 399 | \put | 382 |
| \phantomsection | 198, 2103, 2524 | | \renewcommand |
| \popQED | 2519 | | 196, 200, 201, 204, 206, 208, 210, 212, 214, 216, 266, 634, 752, 1069, 1128, 1530, 1546, 2084, 2191, 2192, 2283, 2284, 2334, 2338, 2342, 2346, 2350, 2381, 2386, 2391 |
| | | | \renewenvironment |
| | | | 666, 753, 1214, 2512 |
| | | | \repeat |
| | | | 2152, 2266 |
| | | | \RequirePackage 30, 31, 184, 185, 186, 187, 188, 190, 193, 195, 398, 454, 455, 465, 472, 553, 600, 612, 625, 626, 627, 628, 636, 1271, 1276, 2140 |
| | | | \reset@font |
| | | | 575, 588 |
| | | | \reversemarginpar |
| | | | 534 |
| | | | \rightskip |
| | | | 2355 |
| | | | \rlap |
| | | | 2273 |
| | | | \rule |
| | | | 582, 595, 2275 |
| | | | |
| | | | S |
| | | | \savebox |
| | | | 2147 |

| | | | | |
|---|--|--|--|---|
| screenonly (environment) | 22 | 2367, 2368, 2370, 2371, 2376, 2377, 2398, 2399, 2402, 2403 | \textrightarrow | 402, 1289 |
| \scriptsize | 2149, 2153 | | \textwidth 676, 694, 695, 1550, 1789, 1817, 1845, 1882, 1982, 2025 | |
| \scshape | 2410, 2497 | | \thanks | 14, 1530, 2138 |
| \section | 197, 1674, 1676, 1680, 1682, 2107, 2334, 2523 | 1091, 1096, 1097, 1099, 1102, 1103, 1105, 1642, 1644, 2187 | \thankses | 1533, 1535, 1563, 2138 |
| \section@raggedright | 2354, 2358, 2359, 2367, 2368, 2370, 2371, 2373, 2374, 2376, 2377, 2379, 2380, 2385, 2398, 2399, 2402, 2403 | | \the | 1176, 1178, 2149, 2153, 2182, 2269 |
| \SelectFootnoteRule | 554, 556 | | \theACM@time@hours | 2176, 2183 |
| \setbox | 355, 586, 693, 1799, 1818, 1846, 1857, 1966, 1975, 2026, 2098, 2105 | | \theACM@time@minutes 2183 | |
| \setcitestyle | 24, 201, 275, 281 | | \theenumi | 705 |
| \setcopyright | 17, 1354 | | \theenumii | 706 |
| \setcounter | 1555, 1625, 1688, 2174, 2176, 2362, 2397, 2401 | | \theenumiii | 707 |
| \setkeys | 38, 131, 1033, 1240, 1354, 1956, 1957, 1961, 1962, 2016, 2017, 2020, 2021, 2059, 2060, 2063, 2064 | | \theenumiv | 708 |
| \setlength 536, 537, 543, 550, 714, 715, 720, 726, 729, 730, 731, 732, 1194, 1197, 2148 | | | \thefootnote | 1546 |
| \settopmatter | 19, 1240, 1241, 1243, 1246, 1248, 1251 | | \theoremstyle | 2468, 2471, 2487, 2495 |
| \setTrue | 381 | | \thepage | 2184, 2195, 2196, 2201, 2202, 2209, 2212, 2217, 2221, 2225, 2288, 2315 |
| \SetWatermarkColor | 467 | | \thispagestyle | 1690 |
| \SetWatermarkFontSize 466 | | | \thmname | 2437, 2467 |
| \SetWatermarkText | 468 | | \thmnote | 2437, 2467 |
| \sfdefault | 634 | | \thmnumber | 2437, 2467 |
| \sffamily | 1750, 1752, 1754, 1756, 1758, 1760, 1764, 1905, 1910, 1914, 2188, 2278, 2358, 2359, 2360, | | \thr@ | 242 |
| | | | \time | 2171, 2174, 2176 |
| | | | \title | 10, 2116 |
| | | | \titlenote | 14, 1136, 2117 |
| | | | \topsep | 739, 743, 2514 |
| | | | \trivlist | 2515 |
| | | | \tw@ | 240 |
| | | | \two@digits | 2182, 2183 |
| | | | \twocolumn | 1700, 1702, 1704, 1706, 1708 |
| T | | | | |
| \teaserfigure | 1528 | | U | |
| teaserfigure (environment) | 17 | | \unskip | 358, 400, 562, 1121, 1127, 1132, 1858, 1861, 1862, 1864, 1865, 1866, 1867, 1868, 1878, 1937, 2078, 2079, 2080, 2081, 2082, 2083, 2084, 2085, 2086, 2088, 2114, 2133, 2139 |
| \terms | 16, 1210 | | \unvbox | 566, 571, 587 |
| \textbf | 1280, 1291 | | | |
| \textbullet 401, 1279, 2209, 2212, 2217, 2221 | | | | |
| \textcolor | 2278 | | | |
| \textcopyright 1511, 1521 | | | | |
| \textheight | 2152 | | | |
| \textit | 1292, 2124, 2128, 2129, 2130 | | | |

| | | | |
|---|-------------------------|----------------------|------------------------|
| <code>\upshape</code> | 752 | | |
| <code>\url</code> | 1393, 2530 | | |
| <code>\urlstyle</code> | 405, 414, 417 | | |
| <code>\usebox</code> | 2160, 2167 | | |
| <code>\usepackage</code> | | | |
| | 10, 11, 12, 13, 14, 15 | | |
| | | V | |
| <code>\vbox</code> | 586, | | |
| | 693, 1799, 1818, | | |
| | 1846, 1966, 2026, 2098 | | |
| <code>\vskip</code> 347, 382, 564, 598, 688 | | | |
| <code>\vtop</code> | 1975 | | |
| | | W | |
| <code>\wd</code> | 695, 1858 | | 582, 595, 598, 640, |
| <code>\write</code> | 452 | | 644, 655, 720, 726, |
| | | | 738, 1547, 1549, |
| | | | 1565, 1571, 1577, |
| | | X | 1581, 1801, 1813, |
| <code>\xdef</code> | 251, | | 1825, 1840, 2069, |
| | 253, 255, 257, 259, 261 | | 2105, 2191, 2192, |
| | | | 2242, 2244, 2246, |
| | | Y | 2272, 2274, 2283, |
| <code>\year</code> | 1176, 2182 | | 2284, 2334, 2338, |
| | | | 2350, 2357, 2381, |
| | | Z | 2386, 2391, 2421, 2451 |
| <code>\z@</code> | 230, 293, 313, 345, | | |
| | 355, 370, 383, 537, | <code>\z@skip</code> | 382, 688, 743, 2356 |